
SILASTIC LS-63U RUBBER

MSDS Number

BBHPV

National Stock Number

6850-00F000984

Product Name

SILASTIC LS-63U RUBBER

Manufacturer

DOW CORNING CORP

Product Identification

Product ID: SILASTIC LS-63U RUBBER

MSDS Date: 08/24/1987

FSC: 6850

NIIN: 00F000984

MSDS Number: BBHPV

Responsible Party

DOW CORNING CORPORATION

3901 SOUTH SAGINAW RD

MIDLAND , MI 48686

Emergency Phone: (517) 496-5900

Info Phone: (517) 496-5900

Preparer: JACK L. SHENEGER

Cage: 5D028

Contractor

DOW CORNING CORP

997

MIDLAND, MI 48686-0997

US

517-496-6000/517-496-6315

Cage: 5D028

Ingredients

SILICON DIOXIDE

CAS: 7631-86-9

RTECS: VV3100000

Fraction By Weight: 27%

OSHA PEL80 MG/CUM

ACGIH TLV: 10 MG/CUM

Hazards

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: EYES: DISCOMFORT W/MILD REDNESS & DRYNESS. SKIN: REPEATED/PROLONGED EXPOSURES (24 TO 48 HRS) MAY IRRITATE. INGESTION: LARGE AMOUNTS MAY CAUSE DIGESTIVE DISCOMFORT. INHALATION: IF USE CREATES RESP IRABLE PARTICLES, SOME RESPIRATORY SYSTEM INJURY MAY OCCUR.

Explanation of Carcinogenicity: NONE

Effects of Overexposure: EYES: DISCOMFORT W/MILD REDNESS & DRYNESS.
SKIN: REPEATED/PROLONGED EXPOSURES (24 TO 48 HRS) MAY IRRITATION.
INGESTION: LARGE AMOUNTS MAY CAUSE DIGESTIVE DISCOMFORT.
INHALATION: IF USE CREATES RESPIRABLE PARTICLES, SOME RESPIRATORY SYSTEM INJURY MAY OCCUR.

First Aid

First Aid: EYES: FLUSH W/WATER. SKIN: WIPE OFF & FLUSH W/WATER. OBTAIN MEDICAL ATTENTION.

Fire Fighting

Extinguishing Media: WATER FOG, CO2, DRY CHEMICAL, FOAM
Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHING.
Unusual Fire/Explosion Hazard: EVACUATE AREA IN CASE OF OVERHEATING OR FIRE.

Accidental Release

Spill Release Procedures: USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN FOR SALVAGE OR DISPOSAL.

Handling

Handling and Storage Precautions: STORE Other Precautions: TOXIC VAPORS MAY BE EVOLVED >300F. PROVIDE ADEQUATE VENTILATION IF USED ABOVE THIS POINT.

Exposure Controls

Respiratory Protection: NONE SHOULD BE NEEDED
Ventilation: MECHANICAL: RECOMMENDED
Protective Gloves: WASHING AT MEALTIME
Eye Protection: SAFETY GLASSES
Supplemental Safety and Health

Chemical Properties

Spec Gravity: 1.45
Solubility in Water: Appearance and Odor: VERY LITTLE ODOR, RUBBER CREPE, WHITE.
Percent Volatiles by Volume:

Stability

Stability Indicator/Materials to Avoid: YES
OXIDIZING MATERIAL CAN CAUSE A REACTION.
Stability Condition to Avoid: DON'T STORE Hazardous Decomposition Products: FLUORINE COMPOUNDS, SILICON DIOXIDE, CO2, & TRACES OF INCOMPLETELY BURNED CARBON PRODUCTS.

Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.