

## **RP 3266 HARDENER**

### **MSDS Number**

BBHQB

### **National Stock Number**

8030-01-126-1431

### **Product Name**

RP 3266 HARDENER

### **Manufacturer**

CIBA GEIGY CORP

### **Product Identification**

Product ID:RP 3266 HARDENER

MSDS Date:01/01/1987

FSC:8030

NIIN:01-126-1431

MSDS Number: BBHQB

### **Responsible Party**

CIBA-GEIGY CORP

THREE SKYLINE DRIVE

HAWTHORNE , NY

Emergency Phone: (914) 347-4700

Info Phone: (914) 347-4700

Cage: 02684

### **Contractor**

CIBA SPECIALTY CHEMICALS CORPORATION

EAST LANSING, MI 48823-5691

US

517-351-5900

Cage: 02684

### **Ingredients**

AROMATIC HYDROCARBONS (NO DETECTABLE BENZENE)

CAS: 70955-17-8

TRIETHYLENETETRAMINE

CAS: 112-24-3

RTECS: YE6650000

POLYAMIDE OF C18 FATTY ACID DIMERS & TETA

CAS: 68410-23-1

TRIETHYLENE TRETRAMINE POLYMER W/METHYL OXIRANE

CAS: 26950-63-0

### **Hazards**

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INGESTION: HEATED PRODUCT MAY PRODUCE  
INHALABLE VAPORS. SKIN/EYES: IRRITATION & CORROSIVE.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:DANGER CORROSIVE. CAUSES EYE BURNS, SKIN  
IRRITATION AND ALLERGIC SKIN REACTIONS.  
Medical Cond Aggravated by Exposure:SKIN AND EYE IRRITATIONS.

## First Aid

First Aid:EYES: FLUSH WITH WATER FOR 15 MIN. SKIN: WASH WITH SOAP AND  
WATER. REMOVE CONTAMINATED CLOTHING & LAUNDER BEFORE RE-USE.  
INGESTION: IF CONSCIOUS GIVE LARGE QUANTITIES OF WATER. GET MEDICAL  
ATTENTION. INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN AND/OR  
ARTIFICIAL RESPIRATION. IF NEEDED. CALL A PHYSICIAN.

## Fire Fighting

Flash Point Method:CC  
Flash Point:193F  
Extinguishing Media:CO2, DRY CHEMICAL, FOAM, & WATER.  
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS (SCBA)  
AND FULL PROTECTIVE CLOTHING.  
Unusual Fire/Explosion Hazard:DECOMPOSITION AND COMBUSTION PRODUCTS MAY  
BE TOXIC.

## Accidental Release

Spill Release Procedures:REMOVE SPILLAGE BY ABSORBING IN ABSORBENT  
MATERIAL.

## Handling

Handling and Storage Precautions:DANGER COMBUSTIBLE, CORROSIVE-CAUSES  
EYE BURNS & EYES IRRITATION. KEEP AWAY FROM HEAT & FLAME. DON'T GET  
IN EYES. AVOID CONTACT WITH SKIN & CLOTHING.  
Other Precautions:NUISANCE DUST MAY BE GENERATED WHEN SANDING OR SAWING  
CURED MATERIAL. AVOID BREATHING VAPOR/MIST. KEEP CONTAINER CLOSED.  
USE W/ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

## Exposure Controls

Respiratory Protection:USE NIOSH APPROVED ORGANIC VAPOR CARTRIDGE  
RESPIRATOR WHEN VAPOR/MIST.  
Ventilation:GENERAL MECHANICAL AND LOCAL EXHAUST.  
Protective Gloves:IMPERMEABLE  
Eye Protection:WEAR SPLASH-PROOF CHEMICAL GOGGLES  
Supplemental Safety and Health

## Chemical Properties

Vapor Pres:1.93  
Spec Gravity:0.95-0.99  
Solubility in Water:SLIGHT  
Appearance and Odor:AMBER LIQUID. FINE ODOR  
Percent Volatiles by Volume:

## Stability

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS, ACIDS, METAL-ORGANIC COMPOUNDS.  
Stability Condition to Avoid:EXCESSIVE HEAT FOR PROLONGED PERIODS OF  
TIME.  
Hazardous Decomposition Products:CO2, CO  
Conditions to Avoid Polymerization:HEAT & FLAME

## Disposal

Waste Disposal Methods:CONSULT QUALIFIED LOCAL OR CORPORATE PERSONNEL  
FOR METHOD THAT WILL COMPLY WITH LOCAL, STATE & FEDERAL HEALTH AND  
ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.