

## **SONOLATIC NP I SEALANT**

#### **MSDS Number**

**BBHVT** 

## **National Stock Number**

6850-00F001118

#### **Product Name**

SONOLATIC NP I SEALANT

#### Manufacturer

SONNEBORN BUILDING PRODUCTS

#### **Product Identification**

Product ID:SONOLATIC NP I SEALANT MSDS Date:01/01/1985 FSC:6850 NIIN:00F001118 MSDS Number: BBHVT

## **Responsible Party**

SONNEBORN BUILDING PRODUCTS

7711 COMPUTER AVE

MINNEAPOLIS, MN 55435-5402

US

Emergency Phone: 612-834-3535

Info Phone: 612-834-3535

Cage: DO654

# **Contractor** SONNEBORN BUILDING PRODUTS

**UNKNOW** 

MINNEAPOLIS, MN 55435

(612) 835-3434 Cage: DO654

## **Ingredients**

NAPHTHA, HIGH FLASH Fraction By Weight: 13%

POLYMER, POLYISOCYANATE CONTAINING FREE NCO (ISOCYANATE)

CAS: 1305-78-8 Fraction By Weight:

ASBESTOS (BULK), AMPHIBOLE, ASBESTOS FIBER, SERPENTINE

CAS: 1332-21-4 RTECS: CI6475000

Fraction By Weight: 1.2%

OSHA PEL2 FB/CC ACGIH TLV: 2 FB/CC EPA Report Quantity: 1 LB



DOT Report Quantity: 1 LB

CALCIUM OXIDE; LIME

CAS: 1305-78-8

RTECS: EW3100000

Fraction By Weight: 9.1%

OSHA PEL5 MG/CUM

ACGIH TLV: 2 MG/CUM

SILICON TETRAHYDRIDE, SILANE

CAS: 7803-62-5

RTECS: VV1400000

Fraction By Weight: 0.7% ACGIH TLV: 7 MG/CUM

DIBUTYLTIN DILAUREATE CAS: 1332-21-4

Fraction By Weight: 0.4% EPA Report Quantity: 1 LB DOT Report Quantity: 1 LB

CRYSTALLINE-FUSED SILICA, SILICON DIOXIDE, AMORPHOUS QUARTZ

CAS: 60676-86-0 RTECS: VV7328000

Fraction By Weight: 5.6%

OSHA PEL10 MG/CUM RESP SIO2 ACGIH TLV: 0.1 MG/CUM RESP DUST

PIGMENT

Fraction By Weight: 5%

ANTIOXIDANT

Fraction By Weight: 1.1%

#### **Hazards**

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic: CAN CAUSE ALLERGIC REACTION.

Explanation of Carcinogenicity: SEE INGREDIENTS. Effects of Overexposure: DIZZINESS, HEADACHE.

#### First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. SKIN: WASH W/SOAP & WATER. EYES: FLUSH WITH COPIOUS AMOUNTS OF WATER FOR 15 MINUTES. INGESTION: INDUCE VOMITING BY GIVING SALT WATER (1 TSP PER CUP), FOLLOWED BY A QUA RT OF MILK/MILK OF MAGNESIA. OBTAIN MEDICAL



ATTENTION IN ALL CASES.

### Fire Fighting

Flash Point:144F

Extinguishing Media: FOAM, DRY CHEMICAL, CO2 EXTINGUISHERS.

Fire Fighting Procedures:TREAT AS SOLVENT FIRE.

Unusual Fire/Explosion Hazard: CAN EMIT TOXIC FUMES WHEN HEATED.

#### **Accidental Release**

Spill Release Procedures: AVOID BREATHING VAPORS. WIPE/BLOT UP W/RAGS. CLEAN FLOOR W/SOLVENT.

### Handling

Handling and Storage Precautions: STORE AWAY FROM HEAT & FLAME IN TIGHTLY CLOSED CONTAINERS.

Other Precautions: KEEP OUT OF REACH OF CHILDREN. DON'T TAKE INTERNALLY, AVOID CONTACT W/SKIN/BREATHING OF VAPORS.

#### **Exposure Controls**

Respiratory Protection: NOT NORMALLY REQUIRED. Ventilation: LOCAL EXHAUST: NORMAL VENTILATION

Protective Gloves: SOLVENT RESISTANT Eye Protection: SAFETY GLASSES Supplemental Safety and Health

#### **Chemical Properties**

Spec Gravity: 1.09

Solubility in Water:SLIGHTLY

Appearance and Odor: VISCOUS PASTE W/URETHANE ODOR

Percent Volatiles by Volume:12%

## Stability

Stability Indicator/Materials to Avoid:YES

#### Disposal

Waste Disposal Methods: ALLOW SOLVENT TO EVAPORATE FROM RAGS & THEN CLEAN /BURN RAGS, IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.