

DIP SEAL PLASTIC TYPE I

MSDS Number

BBJBj

National Stock Number

6850-00F001219

Product Name

DIP SEAL PLASTIC TYPE I

Manufacturer

DIP SEAL PLASTICS INC

Product Identification

Product ID:DIP SEAL PLASTIC TYPE I

MSDS Date:01/01/1987

FSC:6850

NIIN:00F001219

MSDS Number: BBJBj

Responsible Party

DIP SEAL PLASTICS, INC.

2311 23RD AVENUE

ROCKFORD , IL 61101

Emergency Phone: (815) 398-3533

Info Phone: (815) 398-3533

Cage: 29437

Contractor

DIP SEAL PLASTICS, INC.

ROCKFORD, IL 61108

(815) 398-3533

Cage: 29437

Ingredients

OIL PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY PARAFFINIC

CAS: 64742-65-0

RTECS: PY8038500

PARAFFIN WAX

CAS: 8002-74-2

RTECS: RV0350000

OSHA PEL2 MG/M3 (FUME)

ACGIH TLV: 2 MG/M3 (FUME); 9192

PARAPLEX G-90, FATTY ACID, SOYBEAN OIL, EPOXIDIZED

CAS: 8013-07-8

RTECS: LH8010000

2,6-DI-TERT-BUTYL-P-CRESOL

CAS: 128-37-0

RTECS: GO7875000

OSHA PEL10 MG/M3

ACGIH TLV: 10 MG/M3; 9192

ETHYL CELLULOSE PLASTIC

CAS: 9004-57-3

RTECS: FJ5950500

Hazards

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Explanation of Carcinogenicity:NONE

Effects of Overexposure:EXCESS TEMPERATURES MAY PRODUCE IRRITATION.

First Aid

First Aid:PROPER PROCEDURE FOR HOT OIL BURNS.

Fire Fighting

Flash Point Method:COC

Flash Point:395F

Extinguishing Media:WATER FOG, CO2, DRY CHEMICAL & FOAM.

Fire Fighting Procedures:PRODUCT MELTS AT 175F.

Accidental Release

Spill Release Procedures:DISAPATE HEAT WITH WATER FOG OR OTHER SUITABLE
METHOD AND MECHANICALLY CLEAN-UP.

Handling

Handling and Storage Precautions:STORE IN COOL DRY PLACE.

Other Precautions:MELTED DIP SEAL WILL PRODUCE SEVERE BURNS IF ON BODY.

Exposure Controls

Ventilation:LOCAL EXHAUST/MECHANICAL

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:>400F

Vapor Pres:Vapor Density:>10

Spec Gravity:1.0544

Evaporation Rate & Reference:(BU AC = 1): Solubility in Water:Appearance and Odor:AMBER SOLID-LUBE OIL ODOR.

Percent Volatiles by Volume:0.1

Stability

Stability Indicator/Materials to Avoid:YES

NORMALLY HAZARDOUS OR INCOMPATIBLE W/HYDROCARBON OILS.

Stability Condition to Avoid:OPEN FLAME

Hazardous Decomposition Products:CO2, CO, SMOKE & SOOT

Conditions to Avoid Polymerization:DIPPING TEMPERATURE 350F.

Disposal

Waste Disposal Methods:RECLAIM OR HAVE REMOVED BY DISPOSAL SERVICE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.