



KODAK EKTAPRINT R-1000 STOP BATH 365676

MSDS Number

BBJKL

National Stock Number

6740-00F001485

Product Name

KODAK EKTAPRINT R-1000 STOP BATH 365676

Manufacturer

EASTMAN KODAK CO

Product Identification

Product ID:KODAK EKTAPRINT R-1000 STOP BATH 365676

MSDS Date:01/01/1985

FSC:6740

NIIN:00F001485

MSDS Number: BBJKL

Responsible Party

EASTMAN KODAK CO

343 STATE ST

ROCHESTER , NY 14650-1115

US

Emergency Phone: 716-722-5151/716-724-4501

Info Phone: 716-724-6481/716-722-5151

Cage: 19139

Contractor

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

Ingredients

ACETIC ACID (GLACIAL), ETHANOIC ACID *97-2*

CAS: 64-19-7

RTECS: AF1225000

Fraction By Weight: 65-70%

OSHA PEL25 MG/CUM

ACGIH TLV: 25 MG/CUM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

WATER

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight: 15-25%



SODIUM ACETATE, ANHYDROUS

CAS: 126-96-5

RTECS: AJ4375000

Fraction By Weight: 1-10%

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: CAN CAUSE UPPER
RESPIRATORY TRACT IRRITATION. EYES: IRRITATION, SEVERE BURNS. SKIN:
SEVERE BURNS. INGESTION: HARMFUL, CAUSES SEVERE BURNS.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, BURNS

First Aid

First Aid:INHALATION: REMOVE FROM EXPOSURE. TREAT SYMPTOMATICALLY.
EYES/SKIN: FLUSH W/PLENTY OF WATER FOR 15 MINS. INGESTION: DON'T
INDUCE VOMITING. GIVE MILK/WATER. OBTAIN MEDICAL ATTENTION IN ALL
CASES.

Fire Fighting

Flash Point:NONE
Lower Limits:150 MG/L
Upper Limits:200 MG/L
Extinguishing Media:DRY CHEMICAL; C02
Fire Fighting Procedures:A NIOSH-APPROVED SELF-CONTAINED BREATHING
APPARATUS.
Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures:WEAR SUITABLE PROTECTIVE EQUIPMENT. NEUTRALIZE
W/BAKING SODA (SODIUM BICARBONATE). FLUSH MATERIAL TO SEWER W/LARGE
AMOUNTS OF WATER.

Handling

Handling and Storage Precautions:DO NOT STORE NEAR ALKALI.
Other Precautions:AVOID INHALATION/SKIN CONTACT.

Exposure Controls

Respiratory Protection:USE A NIOSH APPROVED RESPIRATOR FOR ORGANIC ACID
VAPOR.
Ventilation:LOCAL EXHAUST: RECOMMENDED. MECHANICAL (GENERAL):
RECOMMENDED AT LEAST TEN AIR CHANGES PER HOUR FOR GOOD GENERAL
ROOM.
Protective Gloves:RUBBER
Eye Protection:GOGGLES/FACE SHIELD
Other Protective Equipment:PROTECTIVE CLOTHING.
Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE
REUSE. REMOVE/DISCARD CONTAMINATED SHOES.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:>220F
Vapor Pres:17
Vapor Density:1.7
Spec Gravity:1.12
pH:3.3
Solubility in Water:COMPLETE
Appearance and Odor:CLEAR, COLORLESS SOLUTION; VINEGAR ODOR.
Percent Volatiles by Volume:90/WT

Stability



Stability Indicator/Materials to Avoid: YES

ALKALI

Hazardous Decomposition Products: CO₂, CO

Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.