

ENGINE STARTING FLUID

MSDS Number

BBJMK

National Stock Number

6850-00F001532

Product Name

ENGINE STARTING FLUID

Manufacturer

SPRAY PRODUCTS CORP

Product Identification

Product ID:ENGINE STARTING FLUID

MSDS Date:01/01/1985

FSC:6850

NIIN:00F001532

MSDS Number: BBJMK

Responsible Party

SPRAY PRODUCTS CORP

CONSHOHOCKEN RD

NORRISTOWN , PA 19404-5000

US

Emergency Phone: 215-277-1010

Info Phone: 215-277-1010

Cage: 12625

Contractor

SPRAY PRODUCTS CORPORATION

737

NORRISTOWN, PA 19404

US

610-277-1010

Cage: 12625

Ingredients

ETHYL ETHER, DIETHYL ETHER, ETHER, ANESTHETIC ETHER

CAS: 60-29-7

RTECS: KI5775000

Fraction By Weight: 60%

OSHA PEL400 PPM

ACGIH TLV: 400 PPM

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

HEPTANE *98-1*

CAS: 142-82-5

RTECS: MI7700000

Fraction By Weight: 40%
OSHA PEL2000 MG/CUM
ACGIH TLV: 1640 MG/CUM

UPPER CYLINDER LUBRICANT

Hazards

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:DROWSINESS, STUPOR/UNCONSCIOUSNESS.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:DROWSINESS, STUPOR/UNCONSCIOUSNESS.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:TCC
Flash Point:120.2F
Lower Limits:1.85
Upper Limits:48
Extinguishing Media:WATER ALCOHOL FOAM, CO2/DRY CHEMICALS.
Unusual Fire/Explosion Hazard:NOT MISCIBLE IN WATER.

Accidental Release

Spill Release Procedures:KEEP HEAT & IGNITION SOURCES AWAY. SMALL AMOUNTS MAY BE FLUSHED AWAY W/WATER.

Handling

Handling and Storage Precautions:STORE AWAY FROM HEAT/IGNITION SOURCES & OXIDIZING MATERIALS. DO NOT STORE >120F.
Other Precautions:USE ADEQUATE VENTILATION/USE ONLY OUTDOORS.

Exposure Controls

Ventilation:MECHANICAL(GENERAL)
Eye Protection:SAFETY GLASSES/GOGGLES
Supplemental Safety and Health

Chemical Properties

HCC:V3
Boiling Pt:B.P. Text:94F
Vapor Pres:442
Vapor Density:2.56
Spec Gravity:0.71
Solubility in Water:6.5%
Appearance and Odor:COLORLESS LIQUID W/CHARACTERISTIC ODOR

Stability

Stability Indicator/Materials to Avoid:NO
OXIDIZING MATERIALS
Stability Condition to Avoid:HEAT, IGNITION SOURCES, TEMPS >120F.
Hazardous Decomposition Products:CO2, PEROXIDES.

Disposal

Waste Disposal Methods:BURY DEFECTIVE CONTAINERS AT A PROPER WASTE DISPOSAL AREA, IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.