



---

## **STABOND 0206**

### **MSDS Number**

BBJNM

### **National Stock Number**

8040-00F001557

### **Product Name**

STABOND 0206

### **Manufacturer**

STABOND CORP

### **Product Identification**

Product ID: STABOND 0206  
MSDS Date: 01/01/1985  
FSC: 8040  
NIIN: 00F001557  
MSDS Number: BBJNM

### **Responsible Party**

STABOND CORP  
14010 S WESTERN AVE  
GARDENA , CA 90249-3008  
US  
Emergency Phone: 213-770-0591  
Info Phone: 213-770-0591  
Cage: 25670

### **Contractor**

STABOND CORPORATION  
GARDENA, CA 90249-3008  
US  
213-770-0591/800-4249300  
Cage: 25670

### **Ingredients**

TOLUENE,TOLUOL (IARC CARC- GROUP 3) \*98-1\*  
CAS: 108-88-3  
RTECS: XS5250000  
Fraction By Weight: 50%  
OSHA PEL100 PPM  
ACGIH TLV: 100 PPM  
EPA Report Quantity: 1000 LBS  
DOT Report Quantity: 1000 LBS

NAPHTHA  
CAS: 8030-30-6  
Fraction By Weight: 50%



## SOLVENTS

Fraction By Weight: 75%

### Hazards

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:HEADACHE, NAUSEA, NARCOSIS.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:HEADACHE, NAUSEA, NARCOSIS.

### First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR, APPLY CPR IF UNCONSCIOUS.  
OBTAIN MEDICAL ATTENTION IN ALL CASES.

### Fire Fighting

Flash Point Method:COC  
Flash Point:25F  
Lower Limits:1.2  
Upper Limits:9  
Extinguishing Media:CO2, FOAM/DRY CHEMICAL  
Unusual Fire/Explosion Hazard:HANDLE AS FLAMMABLE LIQUID HYDROCARBON IN WET STATE.

### Accidental Release

Spill Release Procedures:SOAK UP WET MATERIAL ON ABSORBENT COMPOUND.

### Handling

Handling and Storage Precautions:DON'T STORE NEAR HEATING EQUIPMENT/OXIDIZING MATERIALS.

### Exposure Controls

Respiratory Protection:RESPIRATOR W/ACTIVATED CHARCOAL FILTER FOR EXTENDED VAPOR EXPOSURE.  
Ventilation:LOCAL EXHAUST: USE ONLY IN WELL VENTILATED AREAS.  
MECHANICAL(GENERAL): REQUIRED ON LARGE SURFACE APPLICATIONS.  
Protective Gloves:POLYETHYLENE/NITRILE/POLY VINYL ALCOHOL  
Eye Protection:GLASSES W/SIDE SHIELDS  
Supplemental Safety and Health

### Chemical Properties

Boiling Pt:B.P. Text:200F  
Vapor Pres:80  
Vapor Density:3.5  
Spec Gravity:0.86  
Evaporation Rate & Reference:(N-BU AC = 1): 2-3.8  
Solubility in Water:Appearance and Odor:BIEGE LIQUID W/AROMATIC HYDROCARBON ODOR  
Percent Volatiles by Volume:82

### Stability

Stability Indicator/Materials to Avoid:YES  
OXIDIZING MATERIALS.  
Stability Condition to Avoid:FLAME.  
Hazardous Decomposition Products:TOXIC HALOGEN GASES.

### Disposal

Waste Disposal Methods:BURY IN CLOSED METAL CONTAINER, IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their



---

particular situation.