

URAFILM TANK WHITE

MSDS Number

BBJTH

National Stock Number

8010-00F001710

Product Name

URAFILM TANK WHITE

Manufacturer

ADVANCED PRODUCTS DBA ADVANCED COATINGS AND CHEMICAL

Product Identification

Product ID:URAFILM TANK WHITE

MSDS Date:01/01/1985

FSC:8010

NIIN:00F001710

MSDS Number: BBJTH

Responsible Party

ADVANCED PRODUCTS DBA ADVANCED COATINGS & CHEMICAL

4343 TEMPLE CITY BLVD

TEMPLE CITY , CA 91780-4229

US

Emergency Phone: 213-579-6270

Info Phone: 213-579-6270

Cage: 51686

Contractor

ADVANCED PRODUCTS DBA ADVANCED COATINGS & CHEMICAL

TEMPLE CITY, CA 91780-4229

US

818-579-6270

Cage: 51686

Ingredients

PIGMENT

Fraction By Weight:

VEHICLE

Fraction By Weight:

SOLVENTS

Fraction By Weight:

ESTER

Fraction By Weight:

AROMATIC HYDROCARBONS

Fraction By Weight:

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:BREATHING VAPOR MAY CAUSE IRRITATION

TO NOSE, THROAT & EYES.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION, HEADACHE, NAUSEA, DIZZINESS.

First Aid

First Aid:EYES: FLUSH W/WATER FOR 15 MINS. SKIN: WASH AFFECTED AREA W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:TCC

Flash Point:35F

Extinguishing Media:FOAM, DRY CHEMICAL, CO2.

Fire Fighting Procedures:WEAR A SCBA & FULL EMERGENCY EQUIPMENT.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY BURST WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:REMOVE IGNITION SOURCES. CLEAR FUMES FROM AREA. PREVENT LIQUID FROM ENTERING SEWERS, WATER SOURCES/LOW AREAS. ISOLATE AREA. SAFELY SHUT OFF SOURCE. CONTAIN LIQUID W/SAWDUST/OIL ABSORBING COMPOUND. WAS H AREA W/DETERGENT & WATER.

Handling

Handling and Storage Precautions:MATERIAL IS SENSITIVE TO MOISTURE & SHOULD BE KEPT IN TIGHTLY CLOSED CONTAINERS. DON'T STORE/HANDLE NEAR OPEN FLAMES, HEAT/STRONG OXIDIZING AGENTS.

Other Precautions:CONTAINERS MAY BE HAZARDOUS, EVEN WHEN EMPTIED.

Exposure Controls

Respiratory Protection:WEAR AN APPROVED AIR-SUPPLIED MASK IN NON-VENTILATED AREA.

Ventilation:LOCAL EXHAUST: REQUIRED. MECHANICAL (GENERAL): RECOMMENDED. FACE VELOCITY OF 60 FPM IN CONFINED AREAS. (SEE SUPP)

Protective Gloves:CHEMICAL RESISTANT

Eye Protection:CHEMICAL SPLASH GOGGLES/FACE SHIELD

Other Protective Equipment:EYE BATH & SAFETY SHOWER

Supplemental Safety and Health

VENTILATION: USE EXPLOSION PROOF EQUIPMENT.

Chemical Properties

Spec Gravity:1.34

Solubility in Water:INSOLUBLE

Appearance and Odor:WHITE DISPERSION W/DISTINCT SOLVENT ODOR.

Percent Volatiles by Volume:68.83

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, INORGANIC ACIDS.

Stability Condition to Avoid:EXTREME HEAT, SPARKS, OPEN FLAMES & OTHER IGNITION SOURCES.

Hazardous Decomposition Products:BY COMBUSTION: CO, CO2, OXIDES OF NITROGEN.

Disposal

Waste Disposal Methods:DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

