

ALKYD ENAMEL SHIP EXTERIOR

MSDS Number

BBJWD

National Stock Number

8010-00-936-8369

Product Name

ALKYD ENAMEL SHIP EXTERIOR

Manufacturer

ANDREW BROWN OF KOPPERS COMPANY

Product Identification

Product ID:ALKYD ENAMEL SHIP EXTERIOR

MSDS Date:01/01/1987

FSC:8010

NIIN:00-936-8369

MSDS Number: BBJWD

Responsible Party

ANDREW BROWN OF KOPPERS COMPANY

5431 DISTRICT BOULEVARD

LOS ANGELES , CA 90040

Emergency Phone: (213) 587-5201

Info Phone: (213) 587-5201

Cage: MO096

Contractor

KOPPERS CO INC

VERNON, CA 90040

US

Cage: 71191

Ingredients

MINERAL SPIRITS, PETROLEUM SPIRITS

CAS: 64475-85-0

RTECS: PY8240000

Fraction By Weight: 32.0%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

LEAD NAPHTHENATE

CAS: 61790-14-5

RTECS: QK9150000

Fraction By Weight:

ACGIH TLV: 0.15 MG/CUM INORG PB

COBALT NAPHTHENATE

CAS: 61789-51-3

RTECS: QK8925000

Fraction By Weight:

MANGANESE NAPHTHANATE

CAS: 1336-93-2

Fraction By Weight:

OSHA PEL5 MG/CUM (MN)

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 6%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: HEADACHE & NAUSEA.

SKIN/EYES: IRRITATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHALATION: HEADACHE & NAUSEA. SKIN/EYES: IRRITATION.

First Aid

First Aid:INHALATION: REMOVE VICTIMS FORM VAPORS. RESTORE BREATHING IF NECESSARY. SKIN: REMOVE FORM SOAP & WATER. EYES: FLUSH W/WATER.

Fire Fighting

Flash Point Method:CC

Flash Point:90F

Lower Limits:1.2%

Extinguishing Media:CO2, FOAM, DRY CHEMICAL

Fire Fighting Procedures:DON'T USE WATER.

Unusual Fire/Explosion Hazard:VAPOR MAY FORM EXPLOSIVE MIXTURE BETWEEN UPPER & LOW EXPLOSIVE LIMITS.

Accidental Release

Spill Release Procedures:REMOVE SOURCES OF IGNITION. APPLY SAWDUST OR OTHER ABSORBENT MATERIAL. KEEP MATERIAL FROM SPREADING. FLAMMABLE.

Handling

Handling and Storage Precautions:KEEP CONTAINERS CLOSED. AVOID FLAMES, WELDING, SMOKING, SPARKS, OPEN LIGHTS, ETC.

Other Precautions:MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN CONFINED AREAS, TANK OR PIT WITHOUT ADEQUATE VENTILATION.

Exposure Controls

Respiratory Protection:FOR CONFINED AREAS USE BUREAU OF MINES RESPIRATORY DEVICE APROVAL BM 2304 FACE PIECE, BM 2304 CARTRIDGE, BM 23-13 FILTERS, & BM 23-13 FILTER CLIPS.

Ventilation:VENTILATUION SHOULD BE ADEQUATE TO KEEP Protective Gloves:RUBBER

Eye Protection:GOGGLES

Other Protective Equipment:RUBBER SOLES MUST BE WORN (NO STATIC ELECTRICITY).

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:203-390F
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:50.12%

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:IGNITION SOURCES, HEAT, OPEN FLAMES
Hazardous Decomposition Products:CO, CO2, ALDEHYDES, & ORGANICS

Disposal

Waste Disposal Methods:PUT IN METAL CONTAINER & SEAL FOR DISPOSAL.
DISPOSE IN ACCORDANCE W/FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.