https://msdsreport.com/msds/BBKCW

•

PARKS PAINT THINNER

MSDS Number

BBKCW

National Stock Number

8010-00F001904

Product Name

PARKS PAINT THINNER

Manufacturer

PARKS CORP

Product Identification

Product ID:PARKS PAINT THINNER MSDS Date:09/30/1985 FSC:8010 NIIN:00F001904 MSDS Number: BBKCW

Responsible Party

PARKS CORPORATION

SOMERSET, MA 02726

Emergency Phone: (617) 679-5938

Info Phone: (617) 679-5938

Cage: 20450

Contractor

PARKS CORPORATION

5

SOMERSET, MA 02726

(617) 679-5938

Cage: 20450

Ingredients

MINERAL SPIRITS

CAS: 64742-86-5

RTECS: LX3296500

Fraction By Weight: 100%

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN: DRYING. INHALATION: HEADACHE, DIZZINESS, NAUSEA, & RESPIRATORY TRACT IRRITATION. Explanation of Carcinogenicity:NONE

Effects of Overexposure:EYES: IRRITATION. SKIN: DRYING. INHALATION: HEADACE, DIZZINESS, NAUSEA, RESPIRATORY TRACT IRRITATION & CENTRAL NERVOUS SYSTEM DEPRESSION IN HIGH CONCENTRATIONS.

First Aid

First Aid:EYES: FLUSH W/WATER FOR 15 MINUTES. SEEK MED ATTN. SKIN: WASH W/SOAP & WATER. SEEK MED ATTN. REMOVE CONTAMINATED CLOTHING & FLUSH AFFECTED AREAS W/WATER. INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFIC IAL RESPIRATION IF NECESSARY. SEEK MED ATTN. INGESTION:

https://msdsreport.com/msds/BBKCW

DON'T INDUCE VOMITING. SEEK MED ATTN.

Fire Fighting

Flash Point Method:TCC Flash Point:105F Lower Limits:0.7% Upper Limits:6.0% Extinguishing Media:WATER SPRAY, CO2, FOAM, DRY CHEMICAL Fire Fighting Procedures:SCBA FOR FIRE FIGHTERS. WATER MAY BE UNSUITABLE AS AN EXTINGUISHING MEDIA BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL. Unusual Fire/Explosion Hazard:AVOID SPREADING BURNING LIQUID W/WATER USED FOR COOLING PURPOSES.

•

Accidental Release

Spill Release Procedures:FLUSH W/WATER INTO RETAINING AREA/CONTAINER. AVOID EXPOSURE TO SPARKS, FIRE, HOT METAL SURFACES. SMALL SPILLS: ABSORB INTO AN APPROPRIATE ABSORBENT. LARGE SPILL: USE SAND, EARTH, CLAY & FLOOR ABSORBEN T & SHOVEL INTO CONTAINERS FOR DISPOSAL.

Handling

Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS & OPEN FLAMES. USE W/ADEQUATE VENTILATION. KEEP CONTAINER CLOSED. PERSONNEL SHOULD AVOID INHALATION OF VAPORS. Other Precautions: PERSONAL CONTACT W/PRODUCT SHOULD BE AVOIDED. REMOVE SATURATED CLOTHING & FLUSH AFFECTED AREAS W/WATER IN CASE OF CONTACT.

Exposure Controls

Respiratory Protection:SELF CONTAINED BREATHING APPARATUS FOR CONCENTRATIONS ABOVE TLV. Ventilation:LOCAL EXHAUST Protective Gloves:IMPERMEABLE Eye Protection:SAFETY GOGGLES Other Protective Equipment:EYE BATH, SAFETY SHOWER, & IMPERMEABLE APRON. Work Hygienic Practices:NO SMOKING. Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:315-380F Vapor Pres:2 Vapor Density:>AIR Spec Gravity:0.766 Evaporation Rate & Reference:(ETHER = 1): Solubility in Water:NEGLIGIBLE Appearance and Odor:WATER WHITE CLEAR. HYDROCARBON TYPE ODOR. Percent Volatiles by Volume:100%

Stability

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, STRONG ACIDS, BASES, & SELECTED AMINES. Stability Condition to Avoid:HEAT, SPARKS, FIRE, OPEN FLAME Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CO/CO2.

Disposal

Waste Disposal Methods: INCINERATE UNDER SAFE CONDITIONS OR DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. PREVENT RUNOFF TO STREAMS, SEWRES OR OTHER BODIES OF WATER.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their



https://msdsreport.com/msds/BBKCW

-

particular situation.