

2-92448 FLEET-X ALKYD ENAMEL INTERMIX BLUE

MSDS Number

BBKFZ

National Stock Number

8010-00F001953

Product Name

2-92448 FLEET-X ALKYD ENAMEL INTERMIX BLUE

Manufacturer

ACME QUALITY PAINTS COMPANY

Product Identification

Product ID: 2-92448 FLEET-X ALKYD ENAMEL INTERMIX BLUE

MSDS Date: 03/22/1982

FSC: 8010

NIIN: 00F001953

MSDS Number: BBKFZ

Responsible Party

ACME QUALITY PAINTS COMPANY

101 PROSPECT AVENUE

CLEVELAND , OH 44101-5000

Emergency Phone: 216-566-2917

Info Phone: 216-566-2902

Cage: 00002

Contractor

ACME QUALITY PAINTS COMPANY

(216) 566-2917

Cage: 00002

Ingredients

V M & P NAPHTHA, LIGROINE, MINERAL SPIRITS *97-2*

CAS: 8032-32-4

RTECS: OI6180000

Fraction By Weight: 5%

ACGIH TLV: 300 PPM

MINERAL SPIRITS, PETROLEUM SPIRITS *97-2*

CAS: 64475-85-0

RTECS: PY8240000

Fraction By Weight: 15%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

XYLENE, DIMETHYLBENZENE, XYLOL (IARC - GROUP 3) *97-2*

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 5%
OSHA PEL100 PPM
ACGIH TLV: 100 PPM, SKIN
EPA Report Quantity: 1000 LBS
DOT Report Quantity: 1000 LBS

AROMATIC NAPHTHA
CAS: 8030-30-6
Fraction By Weight: 15%
ACGIH TLV: 100 PPM

O-CRESOL *97-2*
CAS: 95-48-7
RTECS: GO6300000
Fraction By Weight:
OSHA PEL22 MG/CUM
ACGIH TLV: 5 PPM
EPA Report Quantity: 1000 LBS
DOT Report Quantity: 1000 LBS

LEAD (ANIMAL CARCINOGEN BY ACGIH, IARC CARC GROUP 2B)
CAS: 7439-92-1
RTECS: OF7525000
Fraction By Weight: 0.26%
ACGIH TLV: 0.15 MG/CUM
EPA Report Quantity: 1 LB
DOT Report Quantity: 1 LB

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO
Health Hazards Acute and Chronic:SKIN: MAY CAUSE IRRITATION.
INHALATION: MAY CAUSE UPPER RESPIRATORY SYSTEM IRRITATION. IN A
CONFINED AREA, VAPORS IN HIGH CONCENTRATION ARE ANESTHETIC.
Explanation of Carcinogenicity:SEE INGREDIENTS.
Effects of Overexposure:IRRITATION, LIGHTHEADEDNESS, STAGGERING GAIT.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. KEEP WARM
& QUIET. EYES/SKIN: FLUSH W/COPIOUS QUANTITIES OF WATER FOR 15
MINS. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:PMCC
Flash Point:70F
Lower Limits:0.7
Extinguishing Media:CO2, DRY CHEMICAL, FOAM.
Fire Fighting Procedures:WEAR A SCBA & FULL PROTECTIVE EQUIPMENT. WATER
SPRAY MAY BE INEFFECTIVE BUT MAY BE USED TO COOL CONTAINERS. IF
WATER IS USED, FOG NOZZLES ARE PREFERABLE.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN

EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures: REMOVE IGNITION SOURCES. VENTILATE & REMOVE W/INERT ABSORBENT.

Handling

Handling and Storage Precautions: KEEP AWAY FROM IGNITION SOURCES. USE ONLY W/ADEQUATE VENTILATION. KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions: DON'T TRANSFER CONTENTS TO OTHER CONTAINERS FOR STORAGE. APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS. AVOID BREATHING VAPOR & SPRAY MIST. AVOID CONTACT W/SKIN & EYES. DON'T TAKE INTERNAL Y. KEPE OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection: WEAR NIOSH/MESA APPROVED RESPIRATOR IF ENGINEERING & ADMINISTRATIVE CONTROLS OF AIR CONTAMINANTS AREN'T FEASIBLE.

Ventilation: LOCAL EXHAUST: PREFERABLE. MECHANICAL (GENERAL): ACCEPTABLE. SPECIAL: REQUIRED TO KEEP Protective Gloves: REQUIRED

Eye Protection: SAFETY GLASSES W/UNPERFORATED SIDESHIELD

Work Hygienic Practices: REMOVE/LAUNDER CONTAMIANTED CLOTHING BEFORE REUSE. WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

Chemical Properties

Boiling Pt: B.P. Text: 240-395F

Vapor Density: >1

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 59.6

Stability

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: EXTREME HEAT, SPARKS, OPEN FLAME & OTHER IGNITION SOURCES.

Hazardous Decomposition Products: BY FIRE: CO, CO2 & OXIDES OF LEAD.

Disposal

Waste Disposal Methods: INCINERATE IN APPROVED FACILITY IAW/FEDERAL, STATE & LOCAL REGULATIONS. DON'T INCINERATE CLOSED CONTAINER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.