2-92448 FLEET-X ALKYD ENAMEL INTERMIX BLUE

MSDS Number

BBKFZ

National Stock Number

8010-00F001953

Product Name

2-92448 FLEET-X ALKYD ENAMEL INTERMIX BLUE

Manufacturer

ACME QUALITY PAINTS COMPANY

Product Identification

Product ID:2-92448 FLEET-X ALKYD ENAMEL INTERMIX BLUE
MSDS Date:03/22/1982
FSC:8010
NIIN:00F001953
MSDS Number: BBKFZ

Responsible Party

ACME QUALITY PAINTS COMPANY

101 PROSPECT AVENUE

CLEVELAND , OH 44101-5000

Emergency Phone: 216-566-2917

Info Phone: 216-566-2902

Cage: OOOO2

Contractor

ACME QUALITY PAINTS COMPANY

(216) 566-2917

Cage: OOOO2

Ingredients

V M & P NAPHTHA, LIGROINE, MINERAL SPIRITS *97-2*

CAS: 8032-32-4

RTECS: OI6180000

Fraction By Weight: 5%

ACGIH TLV: 300 PPM

MINERAL SPIRITS, PETROLEUM SPIRITS *97-2*

CAS: 64475-85-0

RTECS: PY8240000

Fraction By Weight: 15%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

XYLENE, DIMETHYLBENZENE, XYLOL (IARC - GROUP 3) *97-2*

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 5%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM, SKIN

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

AROMATIC NAPHTHA

CAS: 8030-30-6

Fraction By Weight: 15%

ACGIH TLV: 100 PPM

O-CRESOL *97-2*

CAS: 95-48-7

RTECS: GO6300000

Fraction By Weight:

OSHA PEL22 MG/CUM

ACGIH TLV: 5 PPM

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

LEAD (ANIMAL CARCINOGEN BY ACGIH, IARC CARC GROUP 2B)

CAS: 7439-92-1

RTECS: OF7525000

Fraction By Weight: 0.26%

ACGIH TLV: 0.15 MG/CUM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO
Health Hazards Acute and Chronic:SKIN: MAY CAUSE IRRITATION.
INHALATION: MAY CAUSE UPPER RESPIRATORY SYSTEM IRRITATION. IN A CONFINED AREA, VAPORS IN HIGH CONCENTRATION ARE ANESTHETIC.
Explanation of Carcinogenicity:SEE INGREDIENTS.
Effects of Overexposure:IRRITATION, LIGHTHEADEDNESS, STAGGERING GAIT.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. KEEP WARM & QUIET. EYES/SKIN: FLUSH W/COPIOUS QUANTITIES OF WATER FOR 15 MINS. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:PMCC
Flash Point:70F
Lower Limits:0.7
Extinguishing Media:CO2, DRY CHEMICAL, FOAM.
Fire Fighting Procedures:WEAR A SCBA & FULL PROTECTIVE EQUIPMENT. WATER SPRAY MAY BE INEFFECTIVE BUT MAY BE USED TO COOL CONTAINERS. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN

EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:REMOVE IGNITION SOURCES. VENTILATE & REMOVE W/INERT ABSORBENT.

Handling

Handling and Storage Precautions:KEEP AWAY FROM IGNITION SOURCES. USE ONLY W/ADEQUATE VENTILATION. KEEP CONTAINER CLOSED WHEN NOT IN USE.
Other Precautions:DON'T TRANSFER CONTENTS TO OTHER CONTAINERS FOR STORAGE. APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS. AVOID BREATHING VAPOR & SPRAY MIST. AVOID CONTACT W/SKIN & EYES. DON'T TAKE INTERNALL Y. KEPE OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:WEAR NIOSH/MESA APPROVED RESPIRATOR IF ENGINEERING & ADMINISTRATIVE CONTROLS OF AIR CONTAMINANTS AREN'T FEASIBLE.
Ventilation:LOCAL EXHAUST: PREFERABLE. MECHANICAL (GENERAL): ACCEPTABLE. SPECIAL: REQUIRED TO KEEP Protective Gloves:REQUIRED
Eye Protection:SAFETY GLASSES W/UNPERFORATED SIDESHIELD
Work Hygienic Practices:REMOVE/LAUNDER CONTAMIANTED CLOTHING BEFORE REUSE. WASH THOROUGHLY AFTER HANDLING.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:240-395F
Vapor Density:>1
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:59.6

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:EXTREME HEAT, SPARKS, OPEN FLAME & OTHER IGNITION SOURCES.
Hazardous Decomposition Products:BY FIRE: CO, CO2 & OXIDES OF LEAD.

Disposal

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY IAW/FEDERAL, STATE & LOCAL REGULATIONS. DON'T INCINERATE CLOSED CONTAINER.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.