

446 ROTUNDA RED URETHANE COLOR COAT

MSDS Number

BBKSJ

National Stock Number

8010-00F002328

Product Name

446 ROTUNDA RED URETHANE COLOR COAT

Manufacturer

TENNANT COMPANY

Product Identification

Product ID:446 ROTUNDA RED URETHANE COLOR COAT

MSDS Date:11/01/1985

FSC:8010

NIIN:00F002328

MSDS Number: BBKSJ

Responsible Party

TENNANT COMPANY

MINNEAPOLIS , MN 55440

Emergency Phone: (612) 540-1381

Info Phone: (612) 544-5163

Cage: D0218

Contractor

TENNANT COMPANY

1452

MINNEAPOLIS, MN 55440-1452

US

612-540-1556/800-553-8033

Cage: D0218

Ingredients

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 10-20%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

N-BUTYL ACETATE (SARA III)

CAS: 123-86-4

RTECS: AF7350000

Fraction By Weight: 10-20%

OSHA PEL150 PPM/200 STEL

ACGIH TLV: 150 PPM/200STEL;9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

VM&P NAPHTHA (LIGROINE)

CAS: 8032-32-4

RTECS: OI6180000

Fraction By Weight: 5-15%

OSHA PEL300 PPM/400 STEL

ACGIH TLV: 300 PPM; 9192

GARNET TONER

Fraction By Weight: 5-15%

URETHANE PREPOLYMER

CAS: 9040-80-6

Fraction By Weight: 1-10%

OSHA PELNONE

ACGIH TLV: NONE

ALKYD RESIN

CAS: 67700-92-9

Fraction By Weight: 20-30%

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN/EYES: IRRITATION & INJURY.

INGESTION: BURNING SENSATION, VOMITING, DIARRHEA, DROWSINESS, &

TISSUE DAMAGE. INHALATION: ANESTHETIC. IRRITATION OF THE

RESPIRATORY TRACT & NERVOUS SYSTEM DEPRESSION, HEADACHE,

DIZZINESS, STAGGERING GAIT, CONFUSION & UNCONSCIOUSNESS.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:SKIN/EYES: IRRITATION & INJURY. INGESTION:

BURNING SENSATION, VOMITING, DIARRHEA, DROWSINESS, & TISSUE DAMAGE.

INHALATION: ANESTHETIC. IRRITATION OF THE RESPIRATORY TRACT/ACUTE

NERVOUS SYSTEM DEPRESSI ON, HEADACHE, DIZZINESS, STAGGERING GAIT,

CONFUSION & UNCONSCIOUSNESS.

First Aid

First Aid:SKIN: WASH THOROUGHLY W/SOAP & WATER. EYES: FLUSH W/WATER FOR

15 MINUTES. CALL PHYSICIAN. INGESTION: CALL PHYSICIAN. DON'T INDUCE

VOMITING. INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING IF

REQUIR ED. IF BREATHING DIFFICULTY PERSISTS OROCCURS LATER, CONSULT

A PHYSICIAN.

Fire Fighting

Flash Point Method:SCC

Flash Point:80F

Lower Limits:1.0%

Upper Limits:7.0%

Extinguishing Media:CO2, DRY CHEMICAL OR FOAM.

Fire Fighting Procedures:WATER TO COOL CLOSED CONTAINERS TO PREVENT

PRESSURE BUILDUP/POSSIBLE AUTOIGNITION WHEN EXPOSED TO EXTREME HEAT (FOG NOZZLES PREFERRED). USE SCBA.
Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES/HOT SURFACES/ELECTRICAL/STATIC/FRICTIONAL SPAS). AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT/SCRUB WITH SOAP AND WATER.

Handling

Handling and Storage Precautions:STORE IN COOL, DRY PLACE. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS 1C FLAMMABLE LIQUIDS.

Other Precautions:DON'T TAKE INTERNALLY. AVOID PROLONGED CONTACT W/SKIN. CONTAMINATED CLOTHING SHOULD BE REMOVED. CONTAINER SHOULD BE GROUNDED WHILE POURING. AVOID FREE FALL OF LIQ IN EXCESS OF A FEW INCHES.

Exposure Controls

Respiratory Protection:WEAR A CHEMICAL RESPIRATOR APPROVED FOR ORGANIC VAPORS DURING THE APPLICATION & UNTIL WORK AREA HAS BEEN EXHAUSTED OF ALL VAPORS.

Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV/LEL.

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES

Other Protective Equipment:SAFETY SHOWER AND EYEWASH FACILITY.

Work Hygienic Practices:REMOVE CONTAMINATED CLOTHING.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:260F

Vapor Pres:8.4

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN BUTYL ACETATE

Solubility in Water:NOT SOLUBLE

Appearance and Odor:RED/FRUITY ODOR.

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HEAT, ELECTRICAL EQUIPMENT, SPARKS, OPEN FLAME, & HOT SURFACES

Hazardous Decomposition Products:CO₂, CO, NITROGEN OXIDES/LEAD/CHROMIUM

Disposal

Waste Disposal Methods:INCINERATE IN FURNACE OR BURY IN LANDFILL IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.