ELECTROSTATIC TONER PREMIX

MSDS Number

BBKVR

National Stock Number

6850-00F002378

Product Name

ELECTROSTATIC TONER PREMIX

Manufacturer

GRAPHIC CONTROLS CORP

Product Identification

Product ID:ELECTROSTATIC TONER PREMIX
MSDS Date:07/01/1985
FSC:6850
NIIN:00F002378
MSDS Number: BBKVR

Responsible Party

GRAPHIC CONTROLS CORPORATION

189 VAN RESSELAER STREET

BUFFALO , NY 14240-1271

Emergency Phone: (716) 853-7500

Info Phone: (716) 853-7500

Cage: DO308

Contractor

GRAPHIC CONTROLS CORP

BUFFALO, NY 14240

216-328-7000

Cage: DO308

Ingredients

CARBON BLACK

CAS: 1333-86-4

RTECS: FF5800000

Fraction By Weight:

OSHA PEL3.5 MG/M3

ACGIH TLV: 3.5 MG/M3; 9192

POLYVINYL ACETATE

CAS: 9003-20-7

RTECS: AK0920000

Fraction By Weight:

PETROLEUM DISTILLATE, PETROLEUM OIL, BASE OIL

CAS: 8002-05-9

RTECS: SE7175000

Fraction By Weight: 98%

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: MILD DEPRESSION & RESPIRATORY TRACT IRRITATION. SKIN/EYES/INGESTION: IRRITATION.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:INHALATION: MILD DEPRESSION & IRRITATION OF THE RESPIRATORY TRACT. SKIN/EYES/INGESTION: IRRITATION.

First Aid

First Aid:INHALATION: IF OVERCOME BY VAPOR, REMOVE TO FRESH AIR. INGESSTION: DON'T INDUCE VOMITING. EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINUTES. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:TCC
Flash Point:105F
Lower Limits:0.8%
Upper Limits:7.0%
Extinguishing Media:FOAM, DRY CHEMICAL, CO2, WATER FOG OR SPRAY
Fire Fighting Procedures:USE AIR SUPPLED RESCUE EQUIPMENT FOR ENCLOSED AREA.
Unusual Fire/Explosion Hazard:DON'T STORE OR MIX W/STRONG OXIDANTS. COMBUSTIBLE LIQUID.

Accidental Release

Spill Release Procedures:KEEP OUT OF PUBLIC SEWERS, STREAMS, & WATERWAYS.

Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT & OPEN FLAME.
Other Precautions:AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. WASH SKIN WITH SOAP AND WATER AFTER CONTACT.

Exposure Controls

Respiratory Protection:AS NEEDED
Ventilation:LOCAL EXHAUST: RECOMMENDED
Protective Gloves:AS NEEDED
Eye Protection:AS NEEDED
Other Protective Equipment:OIL-IMPERVIOUS APRON
Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:319-345F
Vapor Pres: 2
Vapor Density:5
Spec Gravity:0.750
Evaporation Rate & Reference:(N-BU AC = 1): 0.45
Solubility in Water:NEGLIGIBLE
Appearance and Odor:BLACK, MOBILE LIQUID W/MILD ISOPARAFFINIC HYDROCARBON ODOR
Percent Volatiles by Volume:98%

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS LIKE LIQUID CHLORINE & CONCENTRATED OXYGEN
Hazardous Decomposition Products:CO IN THE CASE OF INCOMPLETE COMBUSTION

Disposal

Waste Disposal Methods:USE COMMERCIAL DISPOSAL FACILITIES. INCINERATE.

Disclaimer (provided with this information by the compiling agencies):

msdsreport
your source for safety

https://msdsreport.com/msds/BBKVR

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.