



M-3226 ZINC CHROMATE PRIMER CATALYST

MSDS Number

BBKVY

National Stock Number

8010-00F002385

Product Name

M-3226 ZINC CHROMATE PRIMER CATALYST

Manufacturer

STERLING LACQUER MFG CO

Product Identification

Product ID:M-3226 ZINC CHROMATE PRIMER CATALYST
MSDS Date:01/01/1987
FSC:8010
NIIN:00F002385
MSDS Number: BBKVY

Responsible Party

STERLING LACQUER MFG CO

3150 BRANNON AVE

ST LOUIS , MO 63139-1422

US

Emergency Phone: 314-776-4450

Info Phone: 314-776-4450

Cage: 60003

Contractor

STERLING LACQUER MFG CO

ST. LOUIS, MO 63139-1422

US

314-776-4450

Cage: 60003

Ingredients

ADDITIVES

Fraction By Weight: 2%

ACGIH TLV: 1 MG/CUM

ALCOHOLS

CAS: 64-17-5

Fraction By Weight: 100%

ACGIH TLV: 50 MG/CUM

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES/SKIN: IRRITATION. INHALATION:
IRRITATION OF THE RESPIRATORY TRACT.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, NARCOSIS.



First Aid

First Aid: EYES: FLUSH W/WATER FOR 15 MINS. SKIN: WASH W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. TREAT FOR EFFECTS OF SOLVENT FUMES. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method: OC
Flash Point: 55F
Lower Limits: 1.45
Upper Limits: 11.25
Extinguishing Media: CO₂, FOAM/DRY CHEMICAL.
Fire Fighting Procedures: DON'T USE WATER.
Unusual Fire/Explosion Hazard: FLAMMABLE LIQUID. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS & OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures: REMOVE SOURCES OF IGNITION (FLAMES/HOT SURFACES/ELECTRICAL STATIC/FRICTIONAL SPARKS). AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE W/INERT ABSORBENT & NON SPARKING TOOLS.

Handling

Handling and Storage Precautions: DON'T STORE > 120F. GROUND CONTAINERS WHEN POURING. AVOID FREE FALL POURING IN EXCESS OF A FEW INCHES. STORE LARGE AMOUNTS & PROTECT FOR STORAGE.
Other Precautions: DON'T TAKE INTERNALLY. GROUNDING & AVOIDANCE OF FREE FALL POURING IS FOR HANDLING LARGE VOLUMES.

Exposure Controls

Respiratory Protection: APPROVED BUREAU OF MINE DEVICE FOR TYPE AREA (OUTDOOR, RESTRICTED, VENTILATED/CONFINED).
Ventilation: GENERAL DILUTION/LOCAL EXHAUST IN VOLUME PATTERN TO KEEP TLV BELOW ACCEPTABLE LIMIT.
Protective Gloves: REQUIRED
Eye Protection: REQUIRED
Work Hygienic Practices: PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING.
Supplemental Safety and Health

Chemical Properties

Boiling Pt: B.P. Text: 140F
Vapor Pres: 31.2
Vapor Density: > 1
Spec Gravity: 0.828
Evaporation Rate & Reference: (BU AC = 1): 1.7
Solubility in Water: SLIGHT
Appearance and Odor: CLEAR LIQUID W/ALCOHOL ODOR
Percent Volatiles by Volume: 98

Stability

Stability Indicator/Materials to Avoid: YES
NONE
Stability Condition to Avoid: HEAT, SPARKS & OPEN FLAME, HOT SURFACES, SOURCES OF IGNITION.
Hazardous Decomposition Products: NONE

Disposal

Waste Disposal Methods: DISPOSE/INCINERATE IN AN APPROVED FACILITY, IAW/FEDERAL, STATE & LOCAL REGULATIONS. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,



expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.