

## **01920 BLACK LACQ 17038**

### **MSDS Number**

BBKXZ

### **National Stock Number**

8010-00F002429

### **Product Name**

01920 BLACK LACQ 17038

### **Manufacturer**

SPRAYON PRODUCTS

### **Product Identification**

Product ID:01920 BLACK LACQ 17038

MSDS Date:08/17/1990

FSC:8010

NIIN:00F002429

MSDS Number: BBKXZ

### **Responsible Party**

SPRAYON PRODUCTS

26300 FARGO AVE

BEDFORD HTS , OH 44146

Emergency Phone: (216) 292-7400

Info Phone: (216) 292-7400

Cage: 09800

### **Contractor**

SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.

BEDFORD HEIGHTS, OH 44146

US

216-292-7400 OR 216-595-8634

Cage: 09800

### **Ingredients**

ISOBUTYL ALCOHOL (SARA III)

CAS: 78-83-1

RTECS: NP9625000

Fraction By Weight:

OSHA PEL100 PPM

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ISOBUTYL ACETATE (SARA III)

CAS: 110-19-0

RTECS: AI4025000

Fraction By Weight:

OSHA PEL150 PPM

ACGIH TLV: 150 PPM; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

BUTYL BENZYL PHTHALATE (SARA III)

CAS: 85-68-7

RTECS: TH9990000

Fraction By Weight:

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

ETHYL 3-ETHOXYPROPIONATE

CAS: 763-69-9

RTECS: UF3325000

Fraction By Weight: 5%

ACGIH TLV: 50 PPM

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight:

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

LIGHT ALIPHATIC NAPHTHA, VM & P NAPHTHA

CAS: 64742-89-8

Fraction By Weight:

ACGIH TLV: 300 PPM

VM&P NAPHTHA (LIGROINE)

CAS: 8032-32-4

RTECS: OI6180000

Fraction By Weight:

OSHA PEL300 PPM/400 STEL

ACGIH TLV: 300 PPM; 9192

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight:

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 50%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 15%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIAANT; 9192

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight:

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight:

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

METHYL ALCOHOL (METHANOL) (SARA III)

CAS: 67-56-1

RTECS: PC1400000

Fraction By Weight:

OSHA PELS,200PPM/250STEL

ACGIH TLV: S,200PPM/250STEL; 93

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: ANESTHETIC, UPPER RESPIRATORY SYSTEM IRRITATION, LIGHT-HEADEDNESS, STAGGERING GAIT, GIDDINESS, & NAUSEA. INGESTION: HARMFUL OR FATAL. SKIN: IRRITATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHALATION: ANESTHETIC, UPPER RESPIRATORY

SYSTEM IRRITATION, LIGHT-HEADEDNESS, STAGGERING GAIT, GIDDINESS, NAUSEA, PERMANENT BRAIN, NERVOUS SYSTEM, KIDNEY, & LIVER DAMAGE. INGESTION: HARMFUL OR FATAL. SKIN: IRRITATION.

### First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH W/WATER FOR AT LEAST 15 MINUTES. SKIN: WASH WITH SOAP AND WATER. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

### Fire Fighting

Flash Point Method:TOC  
Flash Point:Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL OR FOAM.  
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE. USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL.  
Unusual Fire/Explosion Hazard:DON'T SPRAY NEAR OPEN FLAME. KEEP AT ROOM TEMPERATURE AS EXPOSURE TO DIRECT SUNLIGHT OR OTHER HEAT CAUSE BURSTING.

### Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES IF IGNITION. VENTILATE AREA & REMOVE W/INERT ABSORBENT.

### Handling

Handling and Storage Precautions:KEEP AT ROOM TEMPERATURE AS EXPOSURE TO DIRECT SUNLIGHT OR HEAT MAY CAUSE BURSTING. DON'T STORE >120F.  
Other Precautions:KEEP AWAY FROM CHILDREN. DON'T PUNCTURE OR INCINERATE. DO NOT SPRAY NEAR FIRE OR OPEN FLAME. AVOID BREATHING VAPOR OR SPRAY MIST.

### Exposure Controls

Respiratory Protection:IF PERSONAL EXPOSURE CANNOT BE CONTROLLED USE A PROPERLY APPROVED NIOSH/MSHA FITTED ORGANIC VAPOR/PAR RESPIRATOR. WHEN SANDING OR ABRADING, USE AN APPROVED NIOSH/MSHA APPROVED DUST/MIST RESPIRATOR.  
Ventilation:LOCAL EXHAUST IN VOLUME & PATTERN TO KEEP Protective Gloves:RECOMMENDED  
Eye Protection:SAFETY GLASSES W/UNPERFORATED SIDESHIELD  
Other Protective Equipment:APRON, FACE SHIELD  
Supplemental Safety and Health  
CHEMICALS OF THIS PRODUCT ARE IDENTIFIED AS A SARA SECTION 313 TOXIC CHEMICAL. CERTAIN RAW MATERIALS USED IN MAKING THIS PRODUCT MAY CONTAIN SMALL AMOUNTS OF MATERIALS AS IMPURITIES WHICH ARE REGULATE D BY PROPOSITION 65.

### Chemical Properties

Boiling Pt:B.P. Text:Vapor Density:>AIR  
Evaporation Rate & Reference:FASTER THAN ETHER  
Appearance and Odor:COATINGS  
Percent Volatiles by Volume:89%/WT

### Stability

Stability Indicator/Materials to Avoid:YES  
Stability Condition to Avoid:TEMPERATURES >120F, DIRECT SUNLIGHT, HEAT, FIRE, OPEN FLAMES, OR OTHER SOURCES OF IGNITION.  
Hazardous Decomposition Products:CO & CO2.

### Disposal

Waste Disposal Methods:DON'T INCINERATE. DISPOSE IN ACCORDANCE W/FEDERAL, STATE AND LOCAL REGULATIONS REGARDING POLLUTION. DOT: CONSUMER COMMODITY ORM-D.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.