
1075/1090/4050/4090/4650 DRY INK, 1075/1090 TONER

MSDS Number

BBKYL

National Stock Number

6750-00F002437

Product Name

1075/1090/4050/4090/4650 DRY INK, 1075/1090 TONER

Manufacturer

XEROX CORP

Product Identification

Product ID:1075/1090/4050/4090/4650 DRY INK, 1075/1090 TONER

MSDS Date:04/10/1990

FSC:6750

NIIN:00F002437

MSDS Number: BBKYL

Responsible Party

XEROX CORPORATION

XEROX SQ 100 CLINTON AVE S

ROCHESTER , NY 14644-1877

US

Emergency Phone: 716-422-2177/800-828-6571

Info Phone: 800-828-6571/716-422-2177

Cage: 26921

Contractor

XEROX CORPORATION

ROCHESTER, NY 14644-1877

US

800-828-6571/716-422-2177

Cage: 26921

Ingredients

ETHENYLBENZENE, BUTYL METHACRYLATE POLYMER

CAS: 25213-39-2

Fraction By Weight: >90%

COLUMBIA CARBON, CARBON BLACK, LAMPBLACK, BLACK PEARLS

CAS: 1333-86-4

RTECS: FF5800000

Fraction By Weight: 5-10%

OSHA PEL3.5 MG/CUM

ACGIH TLV: 3.5 MG/CUM

HEXADECYLPYRIDINIUM CHLORIDE

CAS: 123-03-5

RTECS: UU4900000

Fraction By Weight:

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MINIMAL RESPIRATORY TRACT IRRITATION
MAY OCCUR AS W/EXPOSURE TO LARGE AMOUNTS OF ANY NON-TOXIC DUST.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:MINIMAL RESPIRATORY TRACT IRRITATION MAY OCCUR
AS W/EXPOSURE TO LARGE AMOUNTS OF ANY NON-TOXIC DUST.

First Aid

First Aid:EYES: FLUSH W/WATER. SKIN; WASH W/SOAP & WATER. INHALATION:
REMOVE FROM EXPOSURE. INGESTION: DILUTE STOMACH CONTENTS W/SEVERAL
GLASSES OF WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Extinguishing Media:WATER, DRY CHEMICAL, CO2, FOAM.

Fire Fighting Procedures:WEAR A SELF CONTAINED BREATHING APPARATUS &
PROTECTIVE CLOTHING. AVOID INHALATION OF SMOKE.

Unusual Fire/Explosion Hazard:LIKE MOST ORGANIC MATERIALS IN POWDER
FORM, WHEN DISPERSED IN AIR, IT CAN FORM EXPLOSIVE MIXTURES.

Accidental Release

Spill Release Procedures:SWEEP UP/VACUUM TONER/CAREFULLY TRANSFER TO
SEALABLE WASTE CONTAINER. SWEEP SLOWLY TO MINIMIZE GENERATION OF
DUST. IF VACUUM IS USED, MOTOR MUST BE RATED AS DUST TIGHT.
CONDUCTIVE HOSE BONDED TO MACHINE SHOULD BE USED TO REDUCE STATIC
BUILDUP. (SUPP)

Handling

Handling and Storage Precautions:AVOID PROLONGED INHALATION OF
EXCESSIVE DUST.

Exposure Controls

Respiratory Protection:WEAR A RESPIRATOR FOR BULK TONER PROCESSING.

Ventilation:NONE REQUIRED WHEN USED AS INTENDED.

Protective Gloves:NONE REQUIRED WHEN USED AS INTENDED.

Eye Protection:GOGGLES FOR BULK TONER PROCESSING.

Supplemental Safety and Health

SPIILLS CONT'D: RESIDUE CAN BE REMOVED W/SOAP & COLD WATER.

Chemical Properties

Spec Gravity: 1

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLACK POWDER W/FAINT ODOR.

Stability

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:PRODUCTS OF COMBUSTION ARE TOXIC.

Disposal

Waste Disposal Methods:DISPOSE OF IAW/FEDERAL, STATE & LOCAL
REGULATIONS. INCINERATE ONLY IN A CLOSED CONTAINER.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.