msds report

https://msdsreport.com/msds/BBLDD

BURNLEY SOLDERING PASTE

MSDS Number

BBLDD

National Stock Number

3439-00-255-4571

Product Name

BURNLEY SOLDERING PASTE

Manufacturer

BURNLEY BATTERY AND MFG CO INC

Product Identification

Product ID:BURNLEY SOLDERING PASTE MSDS Date:05/06/1988 FSC:3439 NIIN:00-255-4571 MSDS Number: BBLDD

Responsible Party

BURNLEY BATTERY & MFG CO INC

103 CLAY STREET

NORTH EAST , PA 16428

Emergency Phone: (814) 725-3595

Info Phone: (814) 725-3595

Cage: 19530

Contractor

BURNLEY BATTERY AND MFG CO

511

NORTH EAST, PA 16428-1537

US

814-725-3595

Cage: 19530

Ingredients

PETROLEUM DISTILLATE, PETROLEUM OIL, BASE OIL CAS: 8002-05-9 RTECS: SE7175000 Fraction By Weight: 70.8% OSHA PEL5 MG/CUM MIST ACGIH TLV: 5 MG/CUM MIST

ZINC CHLORIDE CAS: 7646-85-7 RTECS: ZH1400000 Fraction By Weight: 25.3% OSHA PEL1 MG/M3/2 STEL ACGIH TLV: 1 MG/M3/2STEL FUME93 EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION: IRRITATION & DAMAGE TO EYES, LUNGS, & MUCOUS MEMBRANES. SKIN: ULCERATION. Explanation of Carcinogenicity:PETROLATUM IS AN EXPERIMENTAL CARCINOGEN. Effects of Overexposure:INHALATION: IRRITATION & DAMAGE TO EYES, LUNGS, & MUCOUS MEMBRANES. SKIN: ULCERATION. Medical Cond Aggravated by Exposure:SKIN CONDITIONS OR RESPIRATORY PROBLEMS

•

First Aid

First Aid:SKIN: FLUSH W/SOAP & WATER. EYES: FLUSH W/WATER. INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point:>356F Extinguishing Media:DRY CHEMICAL, CO2 Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures:NORMAL CLEAN-UP PROCEDURES ARE SUFFICIENT.

Handling

Handling and Storage Precautions:STORE BELOW MELTING TEMPERATURE. DON'T EXPOSE TO HEAT IN STORAGE. Other Precautions:AVOID CONTACT W/SKIN & EYES. AVOID INHALATION OF FUMES.

Exposure Controls

Respiratory Protection:IF >TLV, USE HIGH EFFICIENCY PARTICULATE RESPIRATOR. Ventilation:LOCAL EXHAUST: RECOMMENDED. MECHANICAL: AS REQUIRED. Protective Gloves:RECOMMENDED Eye Protection:RECOMMENDED Other Protective Equipment:PROTECTIVE CLOTHING Work Hygienic Practices:WASH THOROUGHLY AFTER TO USE. Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:165.2F Melt/Freeze Pt:M.P/F.P Text:152.6F Vapor Pres:Spec Gravity:0.9 Solubility in Water:INSOLUBLE Appearance and Odor:AMBER COLORED JELLY.

Stability

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:HEAT

Disposal

Waste Disposal Methods: PERMITTED LANDFILL ACCORDING TO LOCAL, STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and



https://msdsreport.com/msds/BBLDD

assume responsibility for the suitability of this information to their particular situation.