

PREMIER DIESEL FUEL

MSDS Number

BBLFV

National Stock Number

9150-00F002561

Product Name

PREMIER DIESEL FUEL

Manufacturer

AMOCO OIL COMPANY

Product Identification

Product ID:PREMIER DIESEL FUEL

MSDS Date:09/16/1992

FSC:9150

NIIN:00F002561

MSDS Number: BBLFV

Responsible Party

AMOCO OIL COMPANY

200 EAST RANDOLPH DRIVE

CHICAGO , IL 60601-6401

US

Emergency Phone: 800-447-8735

Info Phone: 312-856-3907

Preparer: G I BRESNICK

Cage: 15958

Contractor

AMOCO OIL CO

CHICAGO, IL 60601-6401

US

800 447-8735

Cage: 15958

Ingredients

PETROLEUM OIL (NO. 2 DIESEL), DIESEL FUEL & OIL

CAS: 68334-30-5

RTECS: HZ1800000

NAPHTHALENE; MOTH FLAKES; MOTH BALLS; NAPHTHALIN; CAMPHOR

CAS: 91-20-3

RTECS: QJ0525000

Fraction By Weight: 1%

OSHA PEL50 MG/CUM

ACGIH TLV: 52 MG/CUM

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

XYLENE, DIMETHYLBENZENE, XYLOL

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 1%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM, SKIN

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INGESTION: HARMFUL OR FATAL.
INHALATION: DIZZINESS, HEADACHE, NAUSEA, NOSE & THROAT IRRITATION.
EYES: IRRITATION.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:SKIN: IRRITATION.

First Aid

First Aid:SKIN: WASH W/SOAP & WATER. INGESTION: DON'T INDUCE VOMITING.
ASPIRATION OF THIS PRODUCT INTO THE LUNGS CAN CAUSE CHEMICAL
PNEUMONIA & CAN BE FATAL. ASPIRATION INTO THE LUNGS CAN OCCUR WHILE
VOMITING A FTER INGESTION OF THIS PRODUCT. OBTAIN MEDICAL ATTENTION
IN ALL CASES.

Fire Fighting

Flash Point Method:TCC
Flash Point:130F
Lower Limits:1.3%
Upper Limits:6%
Extinguishing Media:DRY CHEMICAL, CO2, HALOGENATED AGENTS, FOAM, STEAM
OR WATER FOG.
Unusual Fire/Explosion Hazard:PRODUCT CAN PRESENT AN EXPLOSION OR FIRE
HAZARD EVEN WHEN EMPTIED. DON'T CUT, PUNCTURE OR WELD ON OR NEAR
CONTAINER.

Accidental Release

Spill Release Procedures:REMOVE OR SHUT OFF ALL SOURCES OF IGNITION.
PREVENT SPREADING BY DIKING, DITCHING, OR ABSORBING ON INERT
MATERIALS.

Handling

Handling and Storage Precautions:STORE AWAY FROM HEAT, IGNITION SOURCES
& OPEN FLAME IN ACCORDANCE W/APPLICABLE REGULATIONS. STORE IN
COMBUSTIBLE LIQUIDS STORAGE AREA.
Other Precautions:AVOID CONTACT W/SKIN.

Exposure Controls

Ventilation:ADEQUATE
Protective Gloves:PROTECTIVE
Eye Protection:SAFETY GLASSES
Work Hygienic Practices:REMOVE CONTAMINATED CLOTHING, INCLUDING SHOES &
THOROUGHLY CLEAN & DRY BEFORE REUSE.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:460-650F
Spec Gravity:0.82 TO 0.86
Solubility in Water:NEGLIGIBLE
Appearance and Odor:CLEAR, RED OR PURPLE LIQUID.

Stability

Stability Indicator/Materials to Avoid: YES

CHLORINE, FLUORINE & OTHER STRONG OXIDIZERS.

Stability Condition to Avoid: HEAT, OPEN FLAME OR OTHER IGNITION SOURCES.

Hazardous Decomposition Products: CO, CO₂ & OTHER HARMFUL PRODUCTS.

Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE W/LOCAL, STATE OR FEDERAL REGULATIONS. ENCLOSED-CONTROLLED INCINERATION UNLESS DIRECTED OTHERWISE BY APPLICABLE ORDINANCES.

=====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.