

MOBIL VACTRA OIL NO. 2

MSDS Number

BBLMQ

National Stock Number

9150-00-045-4317

Product Name

MOBIL VACTRA OIL NO. 2

Manufacturer

MOBIL OIL CORP

Product Identification

Product ID: MOBIL VACTRA OIL NO. 2

MSDS Date: 06/29/1994

FSC: 9150

NIIN: 00-045-4317

MSDS Number: BBLMQ

Responsible Party

MOBIL OIL CORPORATION

3225 GALLOWES ROAD

FAIRFAX, VA 22037

Emergency Phone: (800) 662-4525

Info Phone: (800) 662-4525

Cage: 1G112

Contractor

MOBIL OIL CORPORATION

FAIRFAX, VA 22037-0001

US

(703) 846-1482

Cage: 1G112

Ingredients

9-OCTADECEN-1-AMINE,(Z) (OLEYL AMINE) *95-4*

CAS: 112-90-3

RTECS: RG4130000

ANIMAL FATTY OIL *95-4*

CAS: 8016-28-2

CAS: 64741-88-4

RTECS: 9999999VO

Hazards

LD50 LC50 Mixture: ORAL DL50(RATS): >2000 MG/KG

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PRACTICALLY NON-TOXIC. NO SIGNIFICANT EFFECTS EXPECTED.

Explanation of Carcinogenicity:NONE
Effects of Overexposure:PRACTICALLY NON-TOXIC. NO SIGNIFICANT EFFECTS EXPECTED.

First Aid

First Aid:EYES: FLUSH THOROUGHLY W/WATER. SKIN: WASH W/SOAP & WATER.
INHALATION: REMOVE FROM EXPOSURE. IF BREATHING HAS STOPPED, USE MOUTH TO MOUTH RESUSCITATION. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:COC
Flash Point:>350F
Lower Limits:0.6
Upper Limits:7
Extinguishing Media:CO2, FOAM, DRY CHEMICAL & WATER FOG.
Fire Fighting Procedures:WATER/FOAM MAY CAUSE FROTHING. USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL. WATER SPRAY MAY BE USED TO FLUSH SPILL FROM EXPOSURE. WEAR SCBA IN ENCLOSED AREA.

Accidental Release

Spill Release Procedures:ABSORB ON FIRE RETARDANT TREATED SAWDUST, DIATOMACEOUS EARTH. SHOVEL UP & DISPOSE.

Exposure Controls

Respiratory Protection:NONE REQUIRED IF USED W/ADEQUATE VENTILATION
Ventilation:USE IN WELL VENTILATED AREA.
Protective Gloves:NO SPECIAL EQUIPMENT REQUIRED
Eye Protection:NORMAL INDUSTRIAL PROTECTION EMPLOYED
Work Hygienic Practices:GOOD PERSONAL HYGIENE PRACTICES SHOULD ALWAYS BE FOLLOWED.
Supplemental Safety and Health
FIRE PROC CONT'D: PREVENT RUNOFF FROM FIRE CONTROL/DILUTION FROM ENTERING STREAMS, SEWERS/DRINKING WATER SUPPLY.

Chemical Properties

Boiling Pt:B.P. Text:>600F
Vapor Pres:Solubility in Water:NEGLIGIBLE
Appearance and Odor:BROWN LIQUID W/MILD ODOR

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS
Stability Condition to Avoid:EXTREME HEAT
Hazardous Decomposition Products:PHOSPHORUS OXIDES, SULFUR OXIDES, & CO.

Disposal

Waste Disposal Methods:PRODUCT IS SUITABLE FOR BURNING IN AN ENCLOSED, CONTROLLED BURNER FOR FUEL VALUE/DISPOSAL BY SUPERVISED INCINERATION. BURNING MAY BE LIMITED PURSUANT TO THE RCRA. DISPOSE OF AT AN APPROVED WASTE DISPO SAL FACILITY IAW/LOCAL, STATE & FEDERALREGULATION

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.