

## **THERMOGRIP 6363-15**

### **MSDS Number**

BBLPQ

### **National Stock Number**

8040-00F002729

### **Product Name**

THERMOGRIP 6363-15

### **Manufacturer**

BOSTIK INC

### **Product Identification**

Product ID:THERMOGRIP 6363-15

MSDS Date:04/30/1992

FSC:8040

NIIN:00F002729

MSDS Number: BBLPQ

### **Responsible Party**

BOSTIK INC

BOSTON ST

MIDDLETON , MA 01949

US

Emergency Phone: 508-777-0100

Info Phone: 508-777-0100 OR FAX 508-750-7212

Preparer: D C MOLBERG

Cage: EO689

### **Contractor**

BOSTIK INC.

MIDDLETON, MA 01949

US

978-777-0100/800-227-0332

Cage: 5W425

### **Ingredients**

PARAFFIN WAX FUME, PARAFFIN

CAS: 8002-74-2

RTECS: RV0350000

Fraction By Weight: 2%

OSHA PEL2 MG/CUM

ACGIH TLV: 2 MG/CUM

BISPHENOL A DIGLYCIDYL ETHER RESIN, EPOXY RESIN,

CAS: 25068-38-6

RTECS: KD4380000

Fraction By Weight: 4.4%

### **Hazards**

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYES/SKIN: IRRITATION. INHALATION:  
HAZARDOUS.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:INHALATION: IRRITATION, DIZZINESS, GIDDINESS,  
RESPIRATORY IRRITATION, HEADACHE.

## First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING GIVE  
ARTIFICIAL RESPIRATION, PREFERABLY MOUTH TO MOUTH. IF BREATHING IS  
DIFFICULT GIVE OXYGEN. EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST  
15 MINS. SKI N: IMMERSE AREA IN COLD WATER. DON'T ATTEMPT TO PEEL  
ADHESIVE FROM SKIN. IF PHYSICIAN AGREES, MINERAL OIL MAY PROVE  
USEFUL IN SOFTENING THE ADHESIVE AFTER IT COOLS. OBTAIN MED  
ATTENTION IN ALL CASES.

## Fire Fighting

Extinguishing Media:WATER SPRAY, FOAM, DRY CHEMICAL, CO2  
Fire Fighting Procedures:USE SELF CONTAINED BREATHING APPARATUS &  
PROTECTIVE CLOTHING.

## Accidental Release

Spill Release Procedures:IF LIQUID, ALLOW TO HARDEN, THEN SWEEP UP OR  
PEEL FROM FLOOR & PACKAGE SOLID PRODUCT IN STEEL DRUMS WHICH ARE IN  
GOOD CONDITION. THOROUGHLY CLEAN AREA WHERE SPILL OCCURRED.

## Handling

Handling and Storage Precautions:STORE IN A COOL LOCATION (60-80F) AWAY  
FROM SUNLIGHT & ANY SOURCE OF HEAT. KEEP CONTAINER TIGHTLY CLOSED  
WHEN NOT BEING USED.  
Other Precautions:USE W/ADEQUATE VENTILATION. AVOID PROLONGED OR  
REPEATED BREATHING OF VAPORS & CONTACT W/SKIN.

## Exposure Controls

Ventilation:LOCAL EXHAUST: PREFERRED TO KEEP VAPORS/PARTICULATE BELOW  
TLV. MECHANICAL: ACCEPTABLE.  
Protective Gloves:CLOTH  
Eye Protection:SAFETY GLASSES OR FULL FACE SHIELD  
Other Protective Equipment:SAFETY SHOWER & EYE BATH  
Supplemental Safety and Health

## Chemical Properties

HCC:N1  
Spec Gravity:0.98  
Solubility in Water:INSOLUBLE  
Appearance and Odor:AMBER SOLID W/LITTLE ODOR.  
Percent Volatiles by Volume:0%

## Stability

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZERS  
Stability Condition to Avoid:SUNLIGHT OR OTHER SOURCES OF HEAT  
Hazardous Decomposition Products:CO2, CO, WATER VAPOR, OXIDES OF  
NITROGEN OR A WIDE VARIETY OF INNOCUOUS OR TOXIC FUMES. ACETIC  
ACID/ACROLEIN/ALDEHYDES.

## Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, &  
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.