

## **KRYLON FLUORESCENT SPRAY PAINT 3104**

### **MSDS Number**

BBLRB

### **National Stock Number**

8010-00F002759

### **Product Name**

KRYLON FLUORESCENT SPRAY PAINT 3104

### **Manufacturer**

BORDEN INC KRYLON DEPARTMENT

### **Product Identification**

Product ID:KRYLON FLUORESCENT SPRAY PAINT 3104

MSDS Date:01/01/1985

FSC:8010

NIIN:00F002759

MSDS Number: BBLRB

### **Responsible Party**

BORDEN, INC., KRYLON DEPARTMENT

Emergency Phone: 215/278-2400 OR 245

Cage: EO430

### **Contractor**

KRYLON PRODUCTS

OLON, OH 44139

US

800-832-2541/216-566-2917

Cage: 87187

### **Ingredients**

ACRYLIC ESTER RESIN

Fraction By Weight: 5.8%

PROPANE/ISOBUTANE

CAS: 75-28-5

RTECS: TZ4300000

Fraction By Weight: 28%

ACGIH TLV: 1000

HEXANE (N-HEXANE)

CAS: 110-54-3

RTECS: MN9275000

Fraction By Weight: 18%

OSHA PEL500 PPM

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

N-HEPTANE

CAS: 142-82-5

RTECS: MI7700000

Fraction By Weight: 15%

OSHA PEL500 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9293

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 14 - 21%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

## Hazards

Effects of Overexposure:DIZZINESS, CONFUSION, WEAKNESS

## First Aid

First Aid:GET FRESH AIR. IF SPRAYED IN EYES, WASH WITH WATER FOR 15 MINUTES.

## Fire Fighting

Extinguishing Media:SOLVENT FIRE CLASS B MEDIA

Fire Fighting Procedures:SPRAY CAN BURN LIKE BLOWTORCH;RELEASE BUTTON TO EXTINGUISH.

Unusual Fire/Explosion Hazard:CAN MAY BURST WITH VIOLENCE IF IN A FIRE;THIS WILL RELEASE ITS FLAMMABLE CONTENT.

## Accidental Release

Spill Release Procedures:REMOVE SOURCES OF IGNITION. SOAK UP WITH ABSORBENT MATERIAL. VENTILATE AREA.

## Handling

Handling and Storage Precautions:DO NOT STORE AT TEMPERATURES OVER 120F. CONTENTS UNDER PRESSURE AND EXPOSURE TO HIGH TEMP MAY USE BURSTING. AVOID ANY HEAT SOURCE.

Other Precautions:INCINERATION WILL CAUSE CONTAINER TO BURST VIOLENTLY. AVOID INCINERATION OR USE ONLY A STRONG, CLOSED CONTAINER. AVOID PUNCTING. IF SPRAY IS BURNED DO NOT BREATHE IRRITATING FUMES.

## Exposure Controls

Respiratory Protection:VENTILATE ADEQUATELY

Ventilation:SUPPLY NATURAL VENTILATION AS NEEDED TO KEEP BELOW TLV.

Protective Gloves:NOT NEEDED

Eye Protection:DESIRABLE;NOT MANDATORY

Supplemental Safety and Health

ALSO CONTAINS 8% VM&P NAPHTHA TLV 200PPM.

## Chemical Properties

Vapor Density:>1

Spec Gravity:Evaporation Rate & Reference:>1

Solubility in Water:SLIGHT

Percent Volatiles by Volume:82.4

## Stability

Stability Indicator/Materials to Avoid: YES

Hazardous Decomposition Products: TOXIC AND IRRITATING COMPOUNDS IF BURNED.

## Disposal

Waste Disposal Methods: WHEN DRY, DISCARD AS NON-DANGEROUS TRASH TO BE BURIED OR BURNED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.