
KRYLON CRYSTAL CLEAR 1304

MSDS Number

BBLRM

National Stock Number

8010-00F002769

Product Name

KRYLON CRYSTAL CLEAR 1304

Manufacturer

BORDEN INC KRYLON DEPT

Product Identification

Product ID:KRYLON CRYSTAL CLEAR 1304

MSDS Date:01/25/1985

FSC:8010

NIIN:00F002769

MSDS Number: BBLRM

Responsible Party

BORDEN INC., KRYLON DEPT

FORD & WASHINGTON

NORRISTOWN , PA 19404

US

Emergency Phone: (215) 278-2400

Info Phone: (215) 278-2456

Preparer: CASS

Cage: EO688

Contractor

KRYLON PRODUCTS

SOLON, OH 44139

US

800-832-2541/216-566-2917

Cage: 87187

Ingredients

N-HEPTANE

CAS: 142-82-5

RTECS: MI7700000

Fraction By Weight: 15-30%

OSHA PEL500 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9293

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 15-30%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

AROMATIC HYDROCARBON SOLVENT NAPHTHA (AROMATIC 150)

CAS: 64742-94-5

Fraction By Weight: 1-5%

OSHA PEL210 PPM

ACGIH TLV: 210 PPM

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 5-15%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 5-15%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIAN; 9192

ISOBUTANE

CAS: 75-28-5

RTECS: TZ4300000

Fraction By Weight: 15-30%

OSHA PEL1800 MG/CUM

ACGIH TLV: 1000 PPM

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 5-15%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: CENTRAL NERVOUS SYSTEM DEPRESSION, HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS, ASPHYXIATION, CYANOSIS, RESPIRATORY DISTRESS, LIVER & KIDNEY DAMAGE, PERMANENT BRAIN & NERVOUS SY STEM DAMAGE. SKIN/EYES: IRRITATION.

Explanation of Carcinogenicity:METHYLENE CHLORIDE IS AN A2 CARCINOGEN BY ACGIH.

Effects of Overexposure:INHALATION: PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE, CENTRAL NERVOUS SYSTEM DEPRESSION, HEADACHE, NAUSEA, DIZZINESS, VOMITING, UNCONSCIOUSNESS, ASPHYXIATION, CYANOSIS RESPIRATORY DISTRESS, LIVER & KID NEY DAMAGE. SKIN/EYES: IRRITATION.

First Aid

First Aid:INGESTION: DILUTE BY DRINKING LARGE QUANTITIES OF WATER. GET MED ATTN. INHALATION: REMOVE TO FRESH AIR IF NOT BREATHING GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH. IF BREATHING IS DIFFICUL T GIVE OXYGEN. CALL PHYSICIAN. SKIN: FLUSH W/WATER. CALL PHYSICIAN. EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINUTES.

Fire Fighting

Flash Point:FLAMMABLE

Extinguishing Media:DRY CHEMICAL, FOAM, CO2, WATER

Fire Fighting Procedures:IF VAPORS COLLECT IN A CONFINED AREA IT MAY IGNITE. SPRAY MAY CATCH FIRE & BURN LIKE A BLOWTORCH. WATER MAY BE INEFFECTIVE. BUT USE TO KEEP CONTAINERS COOL.

Unusual Fire/Explosion Hazard:CONTENTS UNDER PRESSURE, EXPOSURE TO HIGH TEMPERATURE MAY CAUSE BURSTING. AVOID RADIATORS, STOVES, DIRECT SUNLIGHT/ HEAT SOURCE. DON'T PUNCTURE/INCINERATE.

Accidental Release

Spill Release Procedures:REMOVE SOURCES OF IGNITION. SOAK UP WITH ABSORBENT MATERIAL. REMOVE TO A CHEMICAL DISPOSAL AREA. PREVENT ENTRY INTO NATURAL BODIES OF WATER.

Handling

Handling and Storage Precautions:DON'T STORE AT TEMPERATURES OVER 120F. HIGH TEMP MAY CAUSE BURSTING. AVOID RADIATORS, STOVES, DIRECT SUNLIGHT, OR OTHER AT SOURCE. AVOID SKIN CONTACT.

Other Precautions:INCINERATION WILL CAUSE CONTAINER TO BURST VIOLENTLY USE ONLY STRONG, CLOSED INCINERATORS. AVOID PUNCTURING. IF SPRAY IS BURNED DON'T BREATHE IRRITATING/TOXIC FUMES. AVOID EYE CONTACT & UNNECESSARY EX POSURE. REMOVE MATERIAL FROM CLOTHING.

Exposure Controls

Respiratory Protection:WHERE AIR CONTAMINANTS CAN EXCEED ACCEPTABLE CRITERIA USE NIOSH/MSHA APPROVED RESPIRATORY PROTECTION EQUIPMENT RESPIRATORS SHOULD BE SELECTED BASED ON THE FORM & CONCENTRATION OF CONTAMINANTS IN AIR I N ACCORDANCE W/OSHA STANDARDS.

Ventilation:SUFFICIENT VENTILATION IN VOLUME & AIR FLOW PATTERNS SHOULD BE PROVIDED TO KEEP AIR CONTAMINANT LEVELS Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING. HANDLE IN ACCORDANCE W/GOOD INDUSTRIAL HYGIENE & SAFETY PRACTICES.

Supplemental Safety and Health

Chemical Properties

Vapor Density:> 1

Spec Gravity:< 1

Evaporation Rate & Reference:(BU AC = 1): >1

Solubility in Water:SLIGHT

Appearance and Odor:CLEAR PAINT. INTERNAL PRESSURE IS 60 POUNDS PER SQUARE INCH

Percent Volatiles by Volume:94

Stability

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: TEMP > 120F, STOVES, RADIATOR, DIRECT
SUNLIGHT, PUNCTURING

Hazardous Decomposition Products: CO, CO₂

Disposal

Waste Disposal Methods: DISPOSE OF ACCORDING TO LOCAL, STATE, & FEDERAL
REGULATIONS. EMPTY CONTAINER MAY CONTAIN EXPLOSIVE VAPORS. DON'T
CUT, PUNCTURE/WELD ON OR NEARBY. INCINERATION WILL CAUSE CONTAINER
TO BURST VIOLENTLY.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.