

826W472 HI MAXTONE LATEX SEMI GLOSS

MSDS Number

BBLSX

National Stock Number

8010-00F002803

Product Name

826W472 HI MAXTONE LATEX SEMI GLOSS

Manufacturer

DAVIS PAINT CO

Product Identification

Product ID:826W472 HI MAXTONE LATEX SEMI GLOSS

MSDS Date:12/03/1984

FSC:8010

NIIN:00F002803

MSDS Number: BBLSX

Responsible Party

DAVIS PAINT CO

1311 IRON ST

NORTH KANSAS CITY , MO 64116-4010

US

Emergency Phone: 816-471-4447

Info Phone: 816-471-4447

Cage: 06655

Contractor

DAVIS PAINT CO

NORTH KANSAS CITY, MO 64116-4010

US

816-471-4447

Cage: 06655

Ingredients

ETHYLENE GLYCOL, GLYCOL

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 4%

ACGIH TLV: C 127 MG/CUM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

10.66

RTECS: 9999999WG

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: INHALATION: DIZZINESS, NAUSEA, NOSE & THROAT IRRITATION. SKIN/EYES: IRRITATION.

Explanation of Carcinogenicity: NONE

Effects of Overexposure: INHALATION: INJURY TO LIVER, KIDNEYS, & POSSIBLY THE BLOOD.

First Aid

First Aid: INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. KEEP WARM & QUIET. EYES: FLUSH W/PLENTRY OF WATER FOR AT LEAST 15 MINS. SKIN: WASH W/WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point: >200F

Lower Limits: 3.2%

Extinguishing Media: NFPA CLASS B EXTINGUISHERS (CO₂, DRY CHEMICALS, OR FOAM)

Fire Fighting Procedures: WATER MAY SPREAD FLAMES FROM BURNING LIQUID. USE WATER SPRAY TO COOL CONTAINERS.

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY DEVELOP PRESSURE WHEN HEATED.

Accidental Release

Spill Release Procedures: VENTILATE AREA WELL. CONTAIN LIQUID AND MOP UP WITH INERT ABSORBENT.

Handling

Handling and Storage Precautions: DO NOT FREEZE. AVOID EXTREMES OF TEMPERATURE.

Other Precautions: DO NOT TAKE INTERNALLY. AVOID CONTACT W/CONTAMINATED CLOTHING.

Exposure Controls

Respiratory Protection: IN VENTILATED AREAS, USE BUREAU OF MINES APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY DURING SPRAY APPLICATION. IN CONFINED AREAS, USE BUREAU OF MINES APPROVED AIRLINE TYPE RESPIRATORS OR HOODS.

Ventilation: SUFFICIENT TO KEEP BELOW TLV

Protective Gloves: RECOMMENDED

Eye Protection: SAFETY GLASSES

Work Hygienic Practices: REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

DISCONTINUED PRODUCT. PRODUCT HAS BEEN REPLACED BY 826P972 HI MAXTONE S/G WHITE, NSN # IS 801000F028099.

Chemical Properties

Boiling Pt: B.P. Text: 212F

Vapor Density: >1

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 72%

Stability

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: EXCESSIVE TEMPERATURES

Hazardous Decomposition Products: CARBON

Disposal

Waste Disposal Methods: DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.