

E-BOND 1241 EPOXY HARDENER

MSDS Number

BBLSY

National Stock Number

8040-00F002804

Product Name

E-BOND 1241 EPOXY HARDENER

Manufacturer

E BOND EPOXIES INC FT LAUDERDALE FL

Product Identification

Product ID:E-BOND 1241 EPOXY HARDENER

MSDS Date:01/01/1987

FSC:8040

NIIN:00F002804

MSDS Number: BBLSY

Responsible Party

E-BOND EPOXIES, INC. /FT.LAUDERDALE, FL

Emergency Phone: (305) 566-6555

Cage: F6245

Contractor

E-BOND EPOXIES, INC. /FT.LAUDERDALE, FL

Cage: F6245

Ingredients

NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

Hazards

Effects of Overexposure:SKIN: BURNS, RASH, SENSITATION. EYE: IRRITANT

First Aid

First Aid:SKIN & EYE: FLUSH WITH PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING AND SHOES. EYE: FLUSH WITH WATER 15 MIN. CALL PHYS. WASH SKIN WITH SOAP AND WATER. WASH CLOTHING BEFORE RE-USE.

Fire Fighting

Flash Point:215 F TCC

Extinguishing Media:SMALL FIRES: CO2, DRY CHEMICAL. LARGE FIRES: WATER OR FOAM.

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS. PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:AVOID: EXCESSIVE HEAT, OPEN FLAMES CONTACT WITH EPOXY RESINS IN MASSES GREATER THAN 1LB.

Accidental Release

Spill Release Procedures:REMOVE EXCESS. FLUSH WITH WATER. SOAK UP IN ABSORBENT AND FLUSH WITH PLENTY OF WATER

Handling

Handling and Storage Precautions:CAUTION-CAUSES BURNS. KEEP CONTAINER CLOSED. AVOID BREATHING VAPORS, SKIN & EYE CONTACT, WASH OROUGHLY AFTER HANDLING. USE ADEQUATE VENTILATION.

Other Precautions:KEEP CONTAINER CLOSED. USE WITH ADEQUATE VENTILATION

Exposure Controls

Respiratory Protection: AIR SUPPLY MASKS/ORGANIC CANISTER MASKS, IF NEEDED.
Ventilation: LOCAL EXHAUST (PREFERRED) MECHANICAL EXHAUST
Protective Gloves: RUBBER
Eye Protection: SAFETY GLASSES W/SHIELDS
Other Protective Equipment: SAFETY SHOWER, EYE BATH, OVERALLS OR APRONS
Supplemental Safety and Health

Chemical Properties

Boiling Pt: B.P. Text: DECOMPOSES
Vapor Pres: Vapor Density: >AIR
Evaporation Rate & Reference: SLOWER THAN ETHER
Percent Volatiles by Volume: 20

Stability

Stability Indicator/Materials to Avoid: YES
STRONG MINERAL ACIDS, STRONG OXIDIZING AGENTS, EPOXY RESIN.
Stability Condition to Avoid: TEMP. ABOVE 300C.
Conditions to Avoid Polymerization: FIRES, EXOTHERM WHEN CURING IN A LARGE MASS.

Disposal

Waste Disposal Methods: INCINERATE FREE LIQUID. TREAT, STORE, TRANSPORT & DISPOSE OF ONLY IN A HAZARDOUS WASTE MANAGEMENT FACILITY PERMITTED UNDER AN AUTHORITY OF THE HAZARDOUS WASTE REGULATIONS OF RESOURCE CONSERVATION AND RECOVERY ACT.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.