https://msdsreport.com/msds/BBLSZ

ELKALOY A

MSDS Number

BBLSZ

National Stock Number

6850-00F002805

Product Name

ELKALOY A

Manufacturer

C M W INC

Product Identification

Product ID:ELKALOY A MSDS Date:11/02/1992 FSC:6850 NIIN:00F002805 MSDS Number: BBLSZ

Responsible Party

C M W INC

70 S GRAY ST

INDIANAPOLIS , IN 46206

US

Emergency Phone: 317-634-8884

Info Phone: 317-634-8884 OR FAX 317-638-2706

Cage: 58300

Contractor

C M W INC

INDIANAPOLIS, IN 46206

US

317-634-8884 OR FAX 317-638-27

Cage: 58300 Ingredients

COPPER (DUST & MIST), BRONZE POWDER CAS: 7440-50-8 RTECS: GL5325000 Fraction By Weight: 99% OSHA PEL0.1 MG(CU)/M3 (FUME) ACGIH TLV: 0.2 MG/M3 (FUME) EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

CADMIUM, CADMIUM PIGMENT (SUSPECTED HUMAN CARCINOGEN BY CAS: 7440-43-9 RTECS: EU9800000 Fraction By Weight: 1%



OSHA PELSEE 1910.1027

ACGIH TLV: 0.01 MG/M3 DUST;9394

EPA Report Quantity: 10 LBS

DOT Report Quantity: 10 LBS

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic:INHALATION: COUGH, CHILLS, GENERAL MALAISE, KIDNEY DISFUNCTION, DRYNESS OF THROAT, HEADACHE, CHEST PAIN, SHORTNESS OF BREATH. INGESTION: LIVER DISFUNCTION, VOMITING. EYES/SKIN: IRRITATION &/OR DISCOLO RING. Explanation of Carcinogenicity:SEE INGREDIENTS Effects of Overexposure:INHALATION: LUNG, LIVER OR KIDNEY DAMAGE. Medical Cond Aggravated by Exposure:ANEMIA OR PULMONARY DISEASE.

•

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. SKIN/EYES: FLUSH W/WATER. INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Extinguishing Media:TYPE C OR ABC EXTINGUISHER. TO EXTINGUISH A METAL POWDER FIRE USE DRY SAND, DRY GRAPHITE OR OTHER CLASS D EXTINGUISHER.

Fire Fighting Procedures: USE SCBA W/A FULL FACE PIECE OPERATED IN PRESSURE DEMAND OR POSITIVE PRESSURE MODE. Unusual Fire/Explosion Hazard: IF THIS MATERIAL IS REDUCED TO POWDER FORM, CAUTION MUST BE USED TO PREVENT FIRE OR EXPLOSION.

Accidental Release

Spill Release Procedures:SCOOP UP LARGE QUANTITIES. USE SWEEPING COMPOUND TO REMOVE THE REST. AVOID CREATING AIRBORNE PARTICLES.

Handling

Handling and Storage Precautions: AVOID GENERATING DUST OR FUMES.

Exposure Controls

Respiratory Protection:USE NIOSH APPROVED CARTRIDGE RESPIRATOR Ventilation:RECOMMENDED Protective Gloves:RECOMMENDED Eye Protection:SAFETY GLASSES OR GOGGLES Supplemental Safety and Health

Chemical Properties

Melt/Freeze Pt:M.P/F.P Text:1052-1080C Spec Gravity:7.6 G/CC Solubility in Water:INSOLUBLE Appearance and Odor:COPPER COLOR METAL

Stability

Stability Indicator/Materials to Avoid:YES OXIDIZERS, ALKALIS, SODIUM AZIDE, ACETYLENE Hazardous Decomposition Products:MELTING MAY GENERATE HARMFUL FUMES

Disposal

Waste Disposal Methods: COPPER ALLOYS CAN BE RECYCLED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their



https://msdsreport.com/msds/BBLSZ

.....

particular situation.