

## **C 200**

### **MSDS Number**

BBLTS

### **National Stock Number**

3439-00F002820

### **Product Name**

C 200

### **Manufacturer**

G O CARLSON INC

### **Product Identification**

Product ID:C 200  
MSDS Date:06/03/1992  
FSC:3439  
NIIN:00F002820  
MSDS Number: BBLTS

### **Responsible Party**

G O CARLSON INC  
350 MARSHALLTON RD  
THORNDALE , PA 19372  
US  
Emergency Phone: 215-384-2800  
Info Phone: 215-384-2800  
Cage: GOCAR

### **Contractor**

G O CARLSON INC  
THORNDALE, PA 19372  
US  
215-384-2800  
Cage: GOCAR

### **Ingredients**

COBALT  
CAS: 7440-48-4  
RTECS: GF8750000  
Fraction By Weight:  
OSHA PEL0.1 MG/M3;AS CO  
ACGIH TLV: 0.05 MG/M3;DUST 9293

CHROMIUM METAL, CHROMIUM, CHROME (SUSPECTED A1 HUMAN  
CAS: 7440-47-3  
RTECS: GB4200000  
Fraction By Weight:  
OSHA PEL1 MG/CUM (CEILING)  
ACGIH TLV: 0.5 MG/CUM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

NICKEL (SOLUBLE) (SUSPECTED HUMAN CARCINOGEN BY NTP, IARC,

CAS: 7440-02-0

RTECS: QR5950000

Fraction By Weight: >99%

OSHA PEL1 MG/CUM

ACGIH TLV: 0.05 MG/CUM IC

MANGANESE, MN COMPOUNDS

CAS: 7439-96-5

RTECS: OO9275000

Fraction By Weight: 0-15%

OSHA PEL(C) 5 MG/M3 DUST

ACGIH TLV: 5 MG/M3 DUST 9293

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:NO TOXIC EFFECTS EXPECTED FROM INERT FORM. EXPOSURE TO FUMES OR DUSTS GENERATED DURING HEATING, CUTTING, BRAZING OR WELDING MAY CAUSE ADVERSE HEALTH EFFECTS. INHALATION: IRRITATION OF NOSE & THROAT. E YES: IRRITATION. INGESTION: IRRITATION OF THE MOUTH & THROAT.

Explanation of Carcinogenicity:SEE INGREDIENTS

Effects of Overexposure:INHALATION: PNEUMONITIS. CNS INVOLVEMENT.

INTERSTITIAL PNEUMONITIS & SENSITIZATION. NODULAR PULMONARY DISEASE. SKIN: DERMATITIS DUE TO SENSITIZATION.

## First Aid

First Aid:SKIN: WASH W/SOAP OR MILD DETERGENT & WATER FOR 5 MINS. EYES: WASH W/PLENTY OF WATER FOR 15 MINS. INHALATION/INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES.

## Handling

Handling and Storage Precautions:DURING WELDING, PRECAUTIONS SHOULD BE TAKEN FOR AIRBORNE CONTAMINANTS & NOXIOUS GASES FROM THE WELDING PROCESS OR COMPONENTS OF THE WELDING ROD.

Other Precautions:ARC & SPARKS GENERATED WHEN WELDING W/THIS PRODUCT COULD BE A SOURCE OF IGNITION FOR COMBUSTIBLE & FLAMMABLE MATERIALS.

## Exposure Controls

Respiratory Protection:USE A PROPERLY FITTED NIOSH APPROVED DUST-FUME RESPIRATOR DURING WELDING OR BURNING.

Ventilation:RECOMMENDED TO KEEP BELOW TLV

Protective Gloves:RECOMMENDED

Eye Protection:SAFETY GLASSES OR GOGGLES

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

SOME CONSTITUENTS POSE MORE POTENTIAL HAZARDS THAN OTHERS, DEPENDING UPON THEIR INHERENT TOXICITY & CONCENTRATION. OF SPECIAL CONCERN ARE CHROMIUM, NICKEL & PERHAPS MANGANESE.

## Chemical Properties

Spec Gravity:8-8.9

Appearance and Odor:ODORLESS SOLID W/METALLIC LUSTRE. AVAILABLE PLATES, DISCS, HEADS & SLABS.

## Stability

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:METAL FUMES & CERTAIN NOXIOUS GASES SUCH AS CO. ACID PICKLING MAY RESULT IN THE FORMATION OF HEXAVALENT CHROMIUM.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.