

3180 SPRED LO-LUSTRE LATEX WALL & TRIM ENAMEL

MSDS Number

BBLVK

National Stock Number

8010-00F002835

Product Name

3180 SPRED LO-LUSTRE LATEX WALL & TRIM ENAMEL

Manufacturer

GLIDDEN COMPANY

Product Identification

Product ID:3180 SPRED LO-LUSTRE LATEX WALL & TRIM ENAMEL

MSDS Date:03/01/1990

FSC:8010

NIIN:00F002835

MSDS Number: BBLVK

Responsible Party

GLIDDEN COMPANY

925 EUCLID AVENUE

CLEVELAND , OH 44115

US

Emergency Phone: 216-344-8000

Info Phone: 216-344-8000

Cage: 01PD6

Contractor

GLIDDEN PAINT, ICI PAINTS NORTH AMERICA

CLEVELAND, OH 44115

US

800-545-2643/216-344-8207

Cage: 01PD6

Ingredients

CLAY (KAOLIN)

CAS: 1332-58-7

RTECS: GF1670500

Fraction By Weight: 5-10%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 2 MG/M3 TDUST; 9293

1,2-PROPANEDIOL (PROPYLENE GLYCOL)

CAS: 57-55-6

RTECS: TY2000000

Fraction By Weight: 1-5%

TITANIUM DIOXIDE, TIO2

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 1-5%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

VINYL ACRYLIC RESIN *92-4*

CAS: 25067-01-0

Fraction By Weight: 10-20%

WATER

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight: 60-70%

STYRENE POLYMER, POLYSTYRENE

CAS: 9003-53-6

RTECS: WL6475000

Fraction By Weight: 1-5%

9.1

RTECS: 9999999WG

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: IRRITATION OF RESPIRATORY TRACT. SKIN: ABSORPTION. EYES: IRRITATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHALATION: DIZZINESS &/OR LIGHTHEADEDNESS, HEADACHE, NAUSEA. SKIN: DERMATITIS, DIZZINESS &/OR LIGHTHEADEDNESS, NAUSEA. MAY BE ABSORBED. INGESTION: LARGE AMOUNTS COULD CAUSE SERIOUS INJURY.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE & SUPPORT BREATHING. GIVE OXYGEN IF NECESSARY & IF BREATHING DIFFICULTY. SKIN: WASH W/PLENTY OF WATER & SOAP. EYES: FLUSH W/WATER FOR AT LEAST 15 MINUTES. INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point:>200F

Extinguishing Media:DRY CHEMICAL, FOAM

Fire Fighting Procedures:WATER MAY BE USED TO COOL & PROTECT EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE.

Accidental Release

Spill Release Procedures:VENTILATE AREA. SPILLS MAY BE COLLECTED W/ABSORBENT MATERIAL. COMPLY W/APPLICABLE & ENVIRONMENTAL REGULATIONS.

Handling

Handling and Storage Precautions:STORE ONLY W/ADEQUATE VENTILATION. DON'T TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:KEEP CONTAINERS TIGHTLY CLOSED & UPRIGHT WHEN NOT IN USE. AVOID CONTACT W/SKIN, EYES & BREATHING OF VAPORS.

Exposure Controls

Respiratory Protection:IF SANDING IS DONE WEAR A DUST MASK. WHERE RESPIRATORY PROTECTION IS REQUIRED, USE ONLY NIOSH/MSHA APPROVED RESPIRATORS.

Ventilation:DILUTE VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD UP OF VAPORS.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES, GOGGLES

Other Protective Equipment:EYE WASH, SAFETY SHOWER

Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER HANDLING, BEFORE EATING OR SMOKING. REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text: 212F

Percent Volatiles by Volume:75%

Stability

Stability Indicator/Materials to Avoid:YES

OXIDIZERS

Stability Condition to Avoid:ELEVATED TEMPERATURES

Hazardous Decomposition Products:CO, CO2

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.