

3587 SPRED HOUSE GLIDE-ON MASONRY & STUCCO FLAT

MSDS Number

BBLVN

National Stock Number

8010-00F002838

Product Name

3587 SPRED HOUSE GLIDE-ON MASONRY & STUCCO FLAT

Manufacturer

GLIDDEN COMPANY

Product Identification

Product ID:3587 SPRED HOUSE GLIDE-ON MASONRY & STUCCO FLAT

MSDS Date:05/21/1993

FSC:8010

NIIN:00F002838

MSDS Number: BBLVN

Responsible Party

GLIDDEN COMPANY

925 EUCLID AVENUE

CLEVELAND , OH 44115

US

Emergency Phone: 800-545-2643

Info Phone: 216-344-8000

Cage: 01PD6

Contractor

GLIDDEN PAINT, ICI PAINTS NORTH AMERICA

CLEVELAND, OH 44115

US

800-545-2643/216-344-8207

Cage: 01PD6

Ingredients

ETHYLENE GLYCOL, GLYCOL

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 1-5%

ACGIH TLV: C 127 MG/CUM

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

GROG; CALCIUM-BARIUM PHOSPHOSILICATE *93-1*

CAS: 66402-68-4

Fraction By Weight: 1-5%

OSHA PEL15 MG/CUM

ACGIH TLV: 10 MG/CUM

PROPANOIC ACID, 2-METHYL, MONOESTER

CAS: 25265-77-4

RTECS: UF6000000

Fraction By Weight: 1-5%

TITANIUM DIOXIDE, TIO2

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 5-10%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

SILICA DIOXIDE, CRYSTALLINE QUARTZ, SAND (SUSPECTED HUMAN

CAS: 14808-60-7

RTECS: VV7330000

Fraction By Weight: 20-30%

OSHA PELSEE TABLE Z3

ACGIH TLV: 0.1 MG/M3 RDUST;9293

ACRYLIC COPOLYMER

Fraction By Weight: 10-20%

WATER

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight: 40-50%

10.96

RTECS: 9999999WG

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: RESPIRATORY TRACT/MUCOUS
MEMBRANE IRRITATION.

DROWSINESS/DIZZINESS/LIGHTHEADEDNESS/HEADACHE/GI

DISTURBANCES/APATHY/CNS DEPRESSION/RESPIRATORY PROBLEMS/ANESTHETIC
EFFECT/NARCOSIS/BLOOD ABNO RMALITIES/KIDNEY DAMAGE/UNCONSCIOUSNESS.

EYES: IRRITATION. INGESTION: DIZZINESS/LIGHTHEADEDNESS/HEADACHE.

SEE SUPP.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:SKIN: IRRITATION, DEFATTING. ABSORPTION MAY
CAUSE APATHY.

Medical Cond Aggravated by Exposure:EYE, SKIN, RESPIRATORY OR KIDNEY
DISORDERS

First Aid

First Aid: INHALATION: REMOVE TO FRESH AIR. RESTORE & SUPPORT CONTINUED BREATHING. HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. SKIN: FLUSH W/WATER, THEN WASH W/SOAP & WATER. EYES: FLUSH W/PLENTY OF WATER FOR A T LEAST 15 MINS. INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method: SCC
Flash Point: NONE
Upper Limits: 15.3%
Extinguishing Media: DRY CHEMICAL OR FOAM, WATER FOG, CO2
Fire Fighting Procedures: USE WATER TO COOL & PROTECT EXPOSED CONTAINERS. USE FULL PROTECTIVE CLOTHING & SCBA.
Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT OR FIRE. IN CLOSED TANKS, WATER OR FOAM MAY CAUSE FROTHING OR ERUPTION.

Accidental Release

Spill Release Procedures: ELIMINATE IGNITION SOURCES. VENTILATE AREA. COLLECT SPILLS W/ABSORBENT MATERIALS. EVACUATE AREA. SMALL SPILLS: USE ABSORBENT TO PICK UP RESIDUE & DISPOSE OF PROPERLY.

Handling

Handling and Storage Precautions: STORE HEAT/SPARKS/OPEN FLAME. KEEP FROM FREEZING. DON'T TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.
Other Precautions: AVOID CONTACT W/SKIN/EYES & BREATHING OF VAPORS. KEEP CONTAINERS TIGHTLY CLOSED/UPRIGHT WHEN NOT IN USE. AVOID CONDITIONS WHICH RESULT IN FORMATION OF INHALABLE PARTICLES SUCH AS SPRAYING OR ABRADING (SANDING) PAINTED SURFACES.

Exposure Controls

Respiratory Protection: WHERE RESPIRATORY PROTECTION IS REQUIRED, USE ONLY NIOSH/MSHA APPROVED RESPIRATORS.
Ventilation: PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD UP OF VAPORS.
Protective Gloves: IMPERVIOUS
Eye Protection: SAFETY GLASSES OR GOGGLES
Other Protective Equipment: EYE WASH, SAFETY SHOWER, IMPERVIOUS CLOTHING
Work Hygienic Practices: REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WASH HANDS AFTER HANDLING & BEFORE EATING OR SMOKING.
Supplemental Safety and Health
CON'T INGESTION: VOMITING/SEVERE ABDOMINAL PAIN/APATHY/CNS DEPRESSION/RESPIRATORY PROBLEMS/INTOXICATION/KIDNEY/BRAIN/DAMAGE. PULMONARY EDEMA/UNCONSCIOUSNESS/ACUTE POISONING/RESPIRATORY FAILURE/CARDIAC FAILURE/DEATH.

Chemical Properties

Boiling Pt: B.P. Text: 212-477F
Spec Gravity: 1.316
Appearance and Odor: WHITE LIQUID
Percent Volatiles by Volume: 62.82%

Stability

Stability Indicator/Materials to Avoid: YES
OXIDIZERS, ACIDS
Stability Condition to Avoid: ELEVATED TEMPERATURES, FREEZING, SPARKS, OPEN FLAME.
Hazardous Decomposition Products: CO, CO2

Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.