

1240, RUSTMASTER SPRAY - OSHA YELLOW

MSDS Number

BBLVP

National Stock Number

8010-00F002839

Product Name

1240, RUSTMASTER SPRAY - OSHA YELLOW

Manufacturer

GLIDDEN COMPANY SCM

Product Identification

Product ID:1240, RUSTMASTER SPRAY - OSHA YELLOW

MSDS Date:11/01/1988

FSC:8010

NIIN:00F002839

MSDS Number: BBLVP

Responsible Party

GLIDDEN COMPANY/SCM

925 EUCLID AVENUE

CLEVELAND, OH 44115

Emergency Phone: (216) 826-5566

Info Phone: (216) 826-5566

Cage: EO697

Contractor

GLIDDEN PAINT, ICI PAINTS NORTH AMERICA

CLEVELAND, OH 44115

US

800-545-2643/216-344-8207

Cage: 01PD6

Ingredients

ALKYD RESIN, SAFFLOWER OIL, POLYMER W/PENTAERYTHRITOL,

CAS: 68072-13-9

Fraction By Weight: 6-11%

ACGIH TLV: NONE

ALIPHATIC NAPHTHA, V.M. & P. NAPHTHA, LACOLENE

CAS: 64742-89-8

Fraction By Weight: 3-8%

OSHA PEL500 PPM ACGIH TLV: 100 PPM

TITANIUM DIOXIDE CAS: 13463-67-7

RTECS: XR2275000



Fraction By Weight: 6-11% OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 27-32%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 13-18%
OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 17-22%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIANT; 9192

ISOBUTANE, 2-METHYLPROPANE

CAS: 75-28-5

RTECS: TZ4300000

Fraction By Weight: 2-7% OSHA PEL1800 MG/CUM ACGIH TLV: 1000 PPM

BUTANE

CAS: 106-97-8

RTECS: EJ4200000

Fraction By Weight: 4-9%

OSHA PEL800 PPM

ACGIH TLV: 800 PPM; 9192



Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN: IRRITATION/DERMATITIS/DEFATTING.

EYES: REDNESS & CORNEAL INJURY. INHALATION:

DROWSINESS/DIZZINESS/LIGHT

HEADEDNESS/HEADACHE/NAUSEA/VOMITING/DIARRHEA/DIGESTIVE SSYTEM

PROBLEMS/MENTAL APATHY/ANEST HETIC EFFECT/NARCOSIS/BLOOD

ABSORMALITIES/LIVER/KIDNEY

DAMAGE/CONVULSIONS/UNCONSCIOUSNESS/PARALYSIS. INGESTION: HARMFUL.

Explanation of Carcinogenicity: NONE

Effects of Overexposure: INHALATION: PROLONGED EXPOSURE TO SOLVENT SCAN

RESULT IN PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. INGESTION:
LARGER AMOUNTS MAY CAUSE LUNG INFLAMMATION & DAMAGE DUE TO

ASPIRATION OF MATERIAL INTO LUNG S.

First Aid

First Aid:INHALATION: MOVE PERSON TO WELL VENT. AREA. GET MEDICAL ATTENTION. ADMINISTER OXYGEN. SKIN: FLUSH W/WATER, THEN WASH WITH SOAP/WATER. EYE: FLUSH W/WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. INGESTION: GET EMERGENCY MEDICAL ATTENTION.

Fire Fighting

Flash Point:Lower Limits:0.9%

Extinguishing Media: DRY CHEMICAL OR FOAM

Fire Fighting Procedures: WATER MAY BE USED TO COOL & PROTECT EXPOSED

CONTAINERS.

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY EXPLODE WHEN

EXPOSED TO EXTREME HEAT OR FIRE.

Accidental Release

Spill Release Procedures: ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA WITH EXPLOSION-PROOF EQUIPMENT. SML SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS. USE NON-SPARKING TOO.

Handling

Handling and Storage Precautions:STORE BELOW 80F. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME.

Other Precautions: USE ONLY WITH ADEQUATE VENTILATION. DON'T TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. KEEP CONTAINERS TIGHTLY CLOSED ANDPRIGHT WHEN NOT IN USE.

Exposure Controls

Respiratory Protection:USE ONLY NIOSH/MSHA APPROVED RESPIRATORS. Ventilation:PROVIDE LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.

Protective Gloves: RUBBER/NEOPRENE

Eye Protection: SAFETY GLASSES OR GOGGLES

Other Protective Equipment: EYE WASH & SAFETY SHOWER.

Work Hygienic Practices: REMOVE CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:133-290F Percent Volatiles by Volume:85.0%

Stability

Stability Indicator/Materials to Avoid:YES OXIDIZERS, ACIDS, BASES, ALDEHYDES, ALKYLHALIDES, HALOGENS, AMINES Stability Condition to Avoid:ELEVATED TEMPERATURES Hazardous Decomposition Products:CO, CO2

Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.



Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.