

Y-908 SPRED FLAT BLACK

MSDS Number

BBLVV

National Stock Number

8010-00F002844

Product Name

Y-908 SPRED FLAT BLACK

Manufacturer

SCM GLIDDEN COATINGS AND RESINS DIV

Product Identification

Product ID:Y-908 SPRED FLAT BLACK

MSDS Date:01/01/1987

FSC:8010

NIIN:00F002844

MSDS Number: BBLVV

Responsible Party

SCM GLIDDEN COATINGS & RESINS DIVISION

925 EUCLID AVENUE

CLEVELAND , OH 44115

Emergency Phone: (216) 826-5566

Info Phone: (216) 826-5566

Cage: DO862

Contractor

SCM GLIDDEN COATINGS&RESINS DIVISION

15049

CLEVELAND, OH 44115

US

216-344-8000

Cage: DO862

Ingredients

ALIPHATIC HYDROCARBONS

Fraction By Weight: 37%

ACGIH TLV: 500 PPM

SILICA

CAS: 7631-89-9

Fraction By Weight: 21%

ACGIH TLV: 100 TLV

MINERAL SPIRITS

CAS: 64742-86-5

RTECS: LX3296500

Fraction By Weight: 11%

CARBON BLACK

CAS: 1333-86-4

RTECS: FF5800000

Fraction By Weight: 3 - 5%

OSHA PEL3.5 MG/M3

ACGIH TLV: 3.5 MG/M3; 9192

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN: DERMATITIS & IRRITATION. EYES: IRRITATION. INHALATION: RESPIRATORY TRACT IRRITATION, HEADACHE, DIZZINESS, & UNCONSCIOUSNESS.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:SKIN: DERMATITIS & IRRITATION. EYES:

IRRITATION. INHALATION: HEADACHE, DIZZINESS, & UNCONSCIOUSNESS.

Medical Cond Aggravated by Exposure:DERMATITIS

First Aid

First Aid:INHALATION: MOVE PERSON TO WELL VENTED AREA. RESTORE BREATHING. GET MED ATTN. SKIN: WIPE W/CLEAN CLOTH. WASH THOROUGHLY W/SOAP & WATER. EYES: FLUSH THOROUGHLY W/WATER & GET MED ATTN. INGESTION: GET ME D ATTN.

Fire Fighting

Flash Point Method:SCC

Flash Point:102F

Lower Limits:1.0%

Extinguishing Media:CO2, DRY CHEMICAL, FOAM

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE ON FIRE BUT USE WATER SPRAY TO COOL CLOSED CONTAINERS EXPOSED TO EXTREME HEAT/FIRE TO PREVENT PRESSURE BUILD-UP/AUTOIGNITION/EXPLOSION.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT OR FIRE. VAPORS MAY IGNITE.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA. MOP SPILLS W/INERT ABSORBENT.

Handling

Handling and Storage Precautions:STORE BELOW 100F. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME.

Other Precautions:USE ONLY WITH ADEQUATE VENTILATION. DON'T TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE. AVOID CONTACT W/SKIN OR BREATHING OF VAPOR.

Exposure Controls

Respiratory Protection:USE NIOSH APPROVED RESPIRATOR W/CHEMICAL-MECHANICAL FILTER. IN CONFINED AREAS USE APPROVED SUPPLIED AIR APPARATUS.

Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO PREVENT BUILD-UP OF VAPORS.

Protective Gloves:SOLVENT RESISTENT

Eye Protection:SPLASH PROOF GOGGLES

Other Protective Equipment:EYE WASH AND SAFETY SHOWER.

Supplemental Safety and Health

WEIGHT PER GALLON: 8.4.

Chemical Properties

Boiling Pt:B.P. Text:313-386F

Evaporation Rate & Reference: SLOWER THAN ETHER
Percent Volatiles by Volume: 62.4%

Stability

Stability Indicator/Materials to Avoid: YES
OXIDIZERS, ACIDS, BASES, AMINES
Stability Condition to Avoid: HEAT, SPARKS, & OPEN FLAME
Hazardous Decomposition Products: CO, CO₂, POSSIBLE OXIDES OF NITROGEN

Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.