



5550 GLID GUARD GLID-TILE EPOXIDE - WHITE GLOSS

MSDS Number

BBLVW

National Stock Number

8010-00F002845

Product Name

5550 GLID GUARD GLID-TILE EPOXIDE - WHITE GLOSS

Manufacturer

GLIDDEN COMPANY

Product Identification

Product ID:5550 GLID GUARD GLID-TILE EPOXIDE - WHITE GLOSS

MSDS Date:05/21/1993

FSC:8010

NIIN:00F002845

MSDS Number: BBLVW

Responsible Party

GLIDDEN COMPANY

925 EUCLID AVENUE

CLEVELAND , OH 44115

US

Emergency Phone: 800-545-2643

Info Phone: 216-344-8000

Cage: 01PD6

Contractor

GLIDDEN PAINT, ICI PAINTS NORTH AMERICA

CLEVELAND, OH 44115

US

800-545-2643/216-344-8207

Cage: 01PD6

Ingredients

STODDARD SOLVENT (PETROLEUM DISTILLATE), MINERAL SPIRITS

CAS: 8052-41-3

RTECS: WJ8925000

Fraction By Weight: 1-5%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM; 9293

LIGHT ALIPHATIC NAPHTHA, VM & P NAPHTHA, LACOLENE *93/1*

CAS: 64742-89-8

Fraction By Weight: 1-5%

OSHA PEL300 PPM

ACGIH TLV: 300 PPM



ETHYL BENZENE

CAS: 100-41-4

RTECS: DA0700000

Fraction By Weight: 1-5%

OSHA PEL435 MG/CUM

ACGIH TLV: 434 MG/CUM

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

SOLVENT NAPHTHA, PETROLEUM, LIGHT AROMATIC, HIGH FLASH

CAS: 64742-95-6

RTECS: WF3400000

Fraction By Weight: 1-5%

TITANIUM DIOXIDE, TIO2

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 20-30%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

SYNTHETIC CRYSTALLINE-FREE SILICA GEL *93-1*

CAS: 112926-00-8

Fraction By Weight: 1-5%

ACGIH TLV: 10 MG/CUM

SILICA DIOXIDE, CRYSTALLINE QUARTZ, SAND (SUSPECTED HUMAN

CAS: 14808-60-7

RTECS: VV7330000

Fraction By Weight: 1-5%

OSHA PELSEE TABLE Z3

ACGIH TLV: 0.1 MG/M3 RDUST;9293

BENZENE (HUMAN CARCINOGEN BY ACGIH, IARC, OSHA, NTP)

CAS: 71-43-2

RTECS: CY1400000

Fraction By Weight: .01-.1%

OSHA PEL1 PPM (8 HR TWA)

ACGIH TLV: 0.3 MG/CUM (A2)

EPA Report Quantity: 10 LBS

DOT Report Quantity: 10 LBS



OXIRANE MODIFIED ESTERS

CAS: 68910-95-2

Fraction By Weight: 40-50%

10.73

RTECS: 9999999WG

ANTIFLOAT

Fraction By Weight: 1-5%

Hazards

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Reports of Carcinogenicity: NTP: YES IARC: YES OSHA: NO
Health Hazards Acute and Chronic: INHALATION: RESPIRATORY TRACT IRRITATION. SKIN/EYES: IRRITATION. INGESTION: LUNG INFLAMMATION & DAMAGE DUE TO ASPIRATION OF MATERIAL INTO LUNGS, FATIGUE, DROWSINESS, DIZZINESS &/OR LIGHTEADEDNESS, UN COORDINATION, NAUSEA, VOMITING, DIARRHEA, GI DISTURBANCES, CNS DEPRESSION, ANESTHETIC EFFECT OR NARCOSIS.

Explanation of Carcinogenicity: SEE INGREDIENTS

Effects of Overexposure: INHALATION: FATIGUE, DROWSINESS, DIZZINESS &/OR LIGHTEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, VOMITING, COUGHING, CNS DEPRESSION, INTOXICATION, TIGHTNESS OF CHEST, ANESTHETIC EFFECT OR NARCOSIS, DIFFICULTY BREATHING, UNCONSCIOUSNESS, ASPHYXIATION. TOXICITY TO LIVER/KIDNEYS/LUNGS/BLOOD. SEE SUPP FOR CON'T.

Medical Cond Aggravated by Exposure: EYES, SKIN, RESPIRATORY, LUNG DISORDERS. ASTHMA-LIKE CONDITIONS, KIDNEY DISORDERS

First Aid

First Aid: INHALATION: REMOVE TO FRESH AIR. RESTORE & SUPPORT CONTINUED BREATHING. HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. SKIN: FLUSH W/WATER. THEN WASH THOROUGHLY W/SOAP & WATER. EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method: SCC

Flash Point: 104F

Lower Limits: 1.3%

Upper Limits: 10.7%

Extinguishing Media: DRY CHEMICAL OR FOAM, CO2

Fire Fighting Procedures: USE WATER TO COOL & PROTECT EXPOSED CONTAINERS. USE FULL PROTECTIVE CLOTHING & SCBA.

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY EXPLODE W/HEAT/FIRE. VAPORS MAY IGNITE EXPLOSIVELY AT AMBIENT TEMPS. VAPORS ARE HEAVIER THAN AIR, TRAVEL TO IGNITION SOURCE & FLASHBACK.

Accidental Release

Spill Release Procedures: ELIMINATE IGNITION SOURCES. VENTILATE/EVACUATE AREA. COLLECT W/ABSORBENT MATL. LARGE SPILL: SHUT OFF LEAK, SAFELY. DIKE/CONTAN/PUMP TO STORAGE/SALVAGE VESSELS. USE NON-SPARKING TOOLS. COMPLETE PERSONAL PROTECTIVE EQUIPMENT MUST BE USED IN CLEAN-UP.

Handling

Handling and Storage Precautions: STORE BELOW 100F. KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME. USE ONLY W/ADEQUATE VENTILATION. DON'T TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.

Other Precautions: AVOID EYES/SKIN CONTACT & BREATHING OF VAPORS. KEEP



CONTAINERS TIGHTLY CLOSED & UPRIGHT WHEN NOT IN USE. AVOID RAISING DUST OR MIST FORMATION. EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES. GROUND E QUIPMENT WHEN TRANSFERRING.

Exposure Controls

Respiratory Protection: WHERE RESPIRATORY PROTECTION IS REQUIRED, USE ONLY NIOSH/MSHA APPROVED RESPIRATORS.

Ventilation: PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD UP OF VAPORS.

Protective Gloves: IMPERVIOUS

Eye Protection: SAFETY GLASSES OR GOGGLES

Other Protective Equipment: EYE WASH, SAFETY SHOWER, IMPERVIOUS CLOTHING, APRON, BOOTS.

Work Hygienic Practices: REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WASH HANDS AFTER HANDLING, ESPECIALLY BEFORE EATING OR SMOKING.

Supplemental Safety and Health

INHALATION: PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. SKIN: DERMATITIS, DEFATTING, BLISTERING. EYES: BLURRED VISION, TEARING, REDNESS, SEVERE IRRITATION. INGESTION: MODERATELY TOXIC. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING THE CONTENTS CAN BE HARMFUL OR FATAL.

Chemical Properties

Boiling Pt: B.P. Text: 176-400F

Spec Gravity: 1.289

Appearance and Odor: WHITE LIQUID

Percent Volatiles by Volume: 21.27%

Stability

Stability Indicator/Materials to Avoid: YES

OXIDIZERS, ACIDS, BASES, AMINES, ALUMINUM, ZINC, MAGNESIUM, SODIUM, POTASSIUM

Stability Condition to Avoid: ELEVATED TEMPS, SPARKS, OPEN FLAME, EXTREME HEAT, FIRE OR OTHER IGNITION SOURCES.

Hazardous Decomposition Products: CO, CO₂

Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. KEEP SALVAGEABLE MATERIAL & RINSE WATER OUT OF SEWERS & WATER COURSES. COMBUSTIBLE LIQUID. UN 1263

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.