

## **1227, RUSTMASTER AEROSOL SPRAY GLOSS WHITE**

### **MSDS Number**

BBLWH

### **National Stock Number**

8010-00F002854

### **Product Name**

1227, RUSTMASTER AEROSOL SPRAY GLOSS WHITE

### **Manufacturer**

GLIDDEN COMPANY SCM

### **Product Identification**

Product ID:1227, RUSTMASTER AEROSOL SPRAY GLOSS WHITE

MSDS Date:12/08/1989

FSC:8010

NIIN:00F002854

MSDS Number: BBLWH

### **Responsible Party**

GLIDDEN COMPANY/SCM

925 EUCLID AVENUE

CLEVELAND , OH 44115

Emergency Phone: (216) 826-5566

Info Phone: (216) 826-5566

Cage: EO697

### **Contractor**

GLIDDEN PAINT, ICI PAINTS NORTH AMERICA

CLEVELAND, OH 44115

US

800-545-2643/216-344-8207

Cage: 01PD6

### **Ingredients**

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 28-233%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 12-17%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 17-22%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIAN; 9192

ISOBUTANE, 2-METHYLPROPANE

CAS: 75-28-5

RTECS: TZ4300000

Fraction By Weight: 2-7%

OSHA PEL1800 MG/CUM

ACGIH TLV: 1000 PPM

BUTANE

CAS: 106-97-8

RTECS: EJ4200000

Fraction By Weight: 4-9%

OSHA PEL800 PPM

ACGIH TLV: 800 PPM; 9192

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 4-9%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

ALIPHATIC NAPHTHA, V.M. & P. NAPHTHA, LACOLENE

CAS: 64742-89-8

Fraction By Weight: 2-7%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

ALKYD RESIN, SAFFLOWER OIL, POLYMER W/PENTAERYTHRITOL,

CAS: 68072-13-9

Fraction By Weight: 6-11%

ACGIH TLV: NONE

CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS: 1317-65-3

RTECS: EV9580000

Fraction By Weight: 1-5%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9192

## Hazards

LD50 LC50 Mixture:ORAL LD50 (RATS): 9750.00 MG/KG  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:SKIN: IRRITATION. EYES: REDNESS & CORNEAL INJURY. INGESTION: DROWSINESS/DIZZINESS/LIGHT HEADEDNESS/HEADACHE/NAUSEA/VOMITING/DIARRHEA/DIGESTIVE SYSTEM PROBLEMS/MENTAL APATHY/ANESTHETIC EFFECT/NARCOSIS/ BLOOD ABNORMALITIES/LIVER/KIDNEY DAMAGE/CONVULSIONS/UNCONSCIOUSNESS & PARALYSIS. INHALATION: HARMFUL & FATAL.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:INHALATION: PROLONGED EXPOSURE TO SOLVENTS CAN RESULT IN PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. INGESTION: LARGER AMOUNTS MAY CAUSE LUNG INFLAMMATION & DAMAGE DUE TO ASPIRATION OF MATERIAL INTO LUNG S.

## First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE & SUPPORT CONTINUED BREATHING. GIVE OXYGEN IF NECESSARY. GET MED ATTN FOR BREATHING DIFFICULTY. SKIN: WASH W/PLENTY OF SOAP & WATER. REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. DISPOSE CONTAMINATED LEATHER ITEMS. EYES: FLUSH W/LARGE AMOUNTS OF WATER. OBTAIN MED ATTN. INGESTION: OBTAIN MED ATTN.

## Fire Fighting

Flash Point:Lower Limits:0.9%  
Extinguishing Media:DRY CHEMICAL OR FOAM  
Fire Fighting Procedures:WATER COOL CONTAINERS/PREVENT EXPLOSION.  
Unusual Fire/Explosion Hazard:VAPORS >AIR, MAY IGNITE EXPLOSIVELY, MAY DECOMPOSE EMITTING IRRITATING/TOXIC GASES.

## Accidental Release

Spill Release Procedures:VENTILATE AREA. SPILLS MAY BE COLLECTED W/ABSORBENT MATERIALS. EVACUATE ALL UNNECESSARY PERSONNEL. LARGE SPILL: SHUT OFF LEAK IF SAFE TO DO SO. DIKE & CONTAIN SPILL. PUMP TO STORAGE/SALVAGE VESSELS. KEEP OUT OF SEWERS & WATER COURSES.

## Handling

Handling and Storage Precautions:STORE BELOW 100F. USE ADEQUATE VENTILATION. DON'T TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT W/SKIN & EYES.  
Other Precautions:AVOID BREATHING OF VAPORS. WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING OR SMOKING. KEEP CONTAINERS TIGHTLY CLOSED & UPRIGHT WHEN NOT IN USE. EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES.

## Exposure Controls

Respiratory Protection:WEAR RESPIRATORY PROTECTION TO KEEP ONLY NIOSH/MSHA APPROVED RESIRATORS IN ACCORDANCE W/OSHA STANDARDS IF SANDING IS DONE, USE DUSKMASK TO AVOID BREATHING OF SANDING DUST.  
Ventilation:PROVIDE LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.  
Protective Gloves:IMPERVIOUS  
Eye Protection:SAFETY GLASSES, GOGGLES  
Other Protective Equipment:EYE WASH & SAFETY SHOWER.  
Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE

REUSE.

Supplemental Safety and Health

## Chemical Properties

Boiling Pt:B.P. Text:133-290F

Percent Volatiles by Volume:85.0

## Stability

Stability Indicator/Materials to Avoid:YES

OXIDIZERS, ACIDS, BASES, ALDEHYDES, ALKYLHALIDES, HALOGENS, AMINES

Stability Condition to Avoid:ELEVATED TEMPERATURES

Hazardous Decomposition Products:CO, CO2

## Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS. CONSUMER COMMODITY ORM-D.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.