



---

## **992 SPRED GLOSS ENAMEL METALLINTE ALUM**

### **MSDS Number**

BBLWM

### **National Stock Number**

8010-00F002858

### **Product Name**

992 SPRED GLOSS ENAMEL METALLINTE ALUM

### **Manufacturer**

GLIDDEN COMPANY

### **Product Identification**

Product ID:992 SPRED GLOSS ENAMEL METALLINTE ALUM

MSDS Date:01/22/1986

FSC:8010

NIIN:00F002858

MSDS Number: BBLWM

### **Responsible Party**

GLIDDEN COMPANY

925 EUCLID AVENUE

CLEVELAND , OH 44115

US

Emergency Phone: 800-545-2643

Info Phone: 216-344-8000

Cage: 01PD6

### **Contractor**

GLIDDEN PAINT, ICI PAINTS NORTH AMERICA

CLEVELAND, OH 44115

US

800-545-2643/216-344-8207

Cage: 01PD6

### **Ingredients**

LIGHT ALIPHATIC NAPHTHA, VM & P NAPHTHA, LACOLENE \*93/1\*

CAS: 64742-89-8

Fraction By Weight: 43%

OSHA PEL300 PPM

ACGIH TLV: 300 PPM

MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100), PARAFFIN-NAPHTHANES

CAS: 64742-88-7

Fraction By Weight: 9%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

XYLENE, DIMETHYLBENZENE, XYLOL



CAS: 1330-20-7  
RTECS: ZE2100000  
Fraction By Weight: 4%  
OSHA PEL100 PPM  
ACGIH TLV: 100 PPM, SKIN  
EPA Report Quantity: 1000 LBS  
DOT Report Quantity: 1000 LBS

7.47  
RTECS: 9999999WG

## Hazards

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES  
Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO  
Health Hazards Acute and Chronic: INHALATION: RESPIRATORY TRACT/MUCOUS MEMBRANE IRRITATION. FATIGUE/DIZZINESS/LIGHTHEADEDNESS/HEADACHE/UNCOORDINATION/NAUSEA/CNS DEPRESSION/ANESTHETIC EFFECT/NARCOSIS/DIFFICULTY BREATHING. EYES: IRRITATION/BLURRED VISION/TEARING/REDNESS. INGESTION: NAUSEA/VOMITING/DIARRHEA/CNS DEPRESSION.  
Explanation of Carcinogenicity: NONE  
Effects of Overexposure: INHALATION: CARDIAC OR BLOOD ABNORMALITIES, CORNEAL INJURY, LIVER/KIDNEY/PERMANENT BRAIN/NERVOUS SYSTEM DAMAGE. SKIN: DERMATITIS, DEFATTING, IRRITATION.

## First Aid

First Aid: INHALATION: REMOVE TO FRESH AIR. RESTORE & SUPPORT CONTINUED BREATHING. HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. SKIN: FLUSH W/WATER, THEN WASH W/ SOAP & WATER. EYES: FLUSH W/ PLENTY OF WATER FOR AT LEAST 15 MINS. INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES.

## Fire Fighting

Flash Point Method: SCC  
Flash Point: 70F  
Lower Limits: 0.9%  
Extinguishing Media: DRY CHEMICAL OR FOAM  
Fire Fighting Procedures: USE WATER TO COOL & PROTECT EXPOSED CONTAINERS, THEY MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.  
Unusual Fire/Explosion Hazard: VAPORS MAY IGNITE EXPLOSIVELY AT AMBIENT TEMPS, VAPORS ARE HEAVIER THAN AIR, TRAVEL LONG DISTANCES TO IGNITION SOURCE & FLASH BACK.

## Accidental Release

Spill Release Procedures: ELIMINATE IGNITION SOURCES. SMALL SPILL: COLLECT W/ ABSORBENT MATERIALS. USE NON-SPARKING TOOLS. EVACUATE AREA. LARGE SPILL: SAME AS SMALL. SHUT OFF LEAK, SAFELY. DIKE/CONTAIN. PUMP TO STORAGE/SALVAGE VESSEL. USE ABSORBENT TO PICK UP EXCESS RESIDUE.

## Handling

Handling and Storage Precautions: STORE BELOW 80F. KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME. USE ONLY W/ ADEQUATE VENTILATION. DON'T TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.  
Other Precautions: AVOID CONTACT W/ SKIN/EYES & BREATHING OF VAPORS. KEEP CONTAINERS TIGHTLY CLOSED/ UPRIGHT WHEN NOT IN USE. EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING/ INHALING VAPORS CAN BE HARMFUL/ FATAL.

## Exposure Controls

Respiratory Protection: WHERE RESPIRATORY PROTECTION IS REQUIRED, USE



ONLY NIOSH/MSHA APPROVED RESPIRATORS.  
Ventilation:PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD UP OF VAPORS. USE EXPLOSION-PROOF & NON-SPARKING EQUIP.  
Protective Gloves:IMPERVIOUS  
Eye Protection:SAFETY GLASSES OR GOGGLES  
Other Protective Equipment:EYE WASH, SAFETY SHOWER  
Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. DISPOSE OF CONTAMINATED LEATHER ITEMS SUCH AS SHOES & BELTS.  
Supplemental Safety and Health  
WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING OR SMOKING.

## **Chemical Properties**

Boiling Pt:B.P. Text:249-374F  
Percent Volatiles by Volume:67%

## **Stability**

Stability Indicator/Materials to Avoid:YES  
OXIDIZERS, ACIDS, BASES, AMINES  
Stability Condition to Avoid:ELEVATED TEMPERATURES, EXTREME HEAT  
Hazardous Decomposition Products:CO, CO2

## **Disposal**

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS. KEEP SALVAGEABLE MATERIAL & RINSE WATER OUT OF SEWERS & WATER COURSES.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.