

# **3525 SPRED HOUSE MASONRY & STUCCO FINISH**

# **MSDS Number**

BBLWN

### **National Stock Number**

8010-00F002859

# **Product Name**

3525 SPRED HOUSE MASONRY & STUCCO FINISH

### Manufacturer

GLIDDEN COMPANY

# **Product Identification**

Product ID:3525 SPRED HOUSE MASONRY & STUCCO FINISH MSDS Date:03/01/1990 FSC:8010 NIIN:00F002859 MSDS Number: BBLWN

# **Responsible Party**

GLIDDEN COMPANY

925 EUCLID AVENUE

CLEVELAND, OH 44115

US

Emergency Phone: 800-545-2643

Info Phone: 216-344-8000

Cage: 01PD6

# Contractor

GLIDDEN PAINT, ICI PAINTS NORTH AMERICA

CLEVELAND, OH 44115

US

800-545-2643/216-344-8207

# Cage: 01PD6

# Ingredients

ETHYLENE GLYCOL, GLYCOL CAS: 107-21-1 RTECS: KW2975000 Fraction By Weight: 1-5% ACGIH TLV: C 127 MG/CUM EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

SILICA DIOXIDE, CRYSTALLINE QUARTZ, SAND (SUSPECTED HUMAN CAS: 14808-60-7 RTECS: VV7330000 Fraction By Weight: 10-20% OSHA PELSEE TABLE Z3



https://msdsreport.com/msds/BBLWN

ACGIH TLV: 0.1 MG/M3 RDUST;9293

TITANIUM DIOXIDE, TIO2 CAS: 13463-67-7 RTECS: XR2275000 Fraction By Weight: 10-20% OSHA PEL15 MG/M3 TDUST ACGIH TLV: 10 MG/M3 TDUST; 9293

PROPANOIC ACID, 2-METHYL, MONOESTER CAS: 25265-77-4 RTECS: UF6000000 Fraction By Weight: 1-5%

ACRYLIC COPOLYMER

Fraction By Weight: 10-20%

WATER CAS: 7732-18-5 RTECS: ZC0110000 Fraction By Weight: 40-50%

1); CAS: 1302-76-7 RTECS: BD1450000 Fraction By Weight: 1-5% OSHA PEL15 MG/CUM ACGIH TLV: 2 MG/CUM

FORMALDEHYDE, FORMALIN (2A CARCINOGEN BY NTP, IARC, OSHA) CAS: 50-00-0 RTECS: LP8925000 Fraction By Weight: OSHA PELSEE 1910.1048 ACGIH TLV: C 0.3 PPM; A2; 9293 EPA Report Quantity: 100 LBS DOT Report Quantity: 100 LBS

11.2 RTECS: 9999999WG

Hazards



Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic:INHALATION: RESPIRATORY TRACT IRRITATION. SKIN/EYES: IRRITATION. INGESTION: LARGE AMOUNTS COULD CAUSE SERIOUS INJURY. Explanation of Carcinogenicity:SEE INGREDIENTS Effects of Overexposure:INHALATION: MUCOUS MEMBRANE IRRITATION, DROWSINESS, DIZZINESS, &/OR LIGHTHEADEDNESS, HEADACHE, NAUSEA, ALLERGIC SENSITIZATION, SILICOSIS. SKIN: DERMATITIS, DIZZINESS, &/OR LIGHTHEADEDNESS, HEADACHE, N AUSEA. MAY BE ABSORBED. INGESTION: KIDNEY DAMAGE &/OR FAILURE. Medical Cond Aggravated by Exposure:EYES, SKIN, RESPIRATORY, LUNG, KIDNEY, LIVER & NERVOUS SYSTEM DISORDERS.

•

### **First Aid**

First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE & SUPPORT CONTINUED BREATHING. HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. SKIN: WASH OFF QUICKLY W/PLENTY OF WATER, THEN SOAP & WATER. EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES.

# **Fire Fighting**

Flash Point:>200F Extinguishing Media:DRY CHEMICAL OR FOAM Fire Fighting Procedures:CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE. Unusual Fire/Explosion Hazard:WATER MAY BE USED TO COOL & PROTECT EXPOSED CONTAINERS.

# **Accidental Release**

Spill Release Procedures: VENTILATE AREA. COLLECT SPILLS W/ABSORBENT MATERIAL.

# Handling

Handling and Storage Precautions:STORE ONLY W/ADEQUATE VENTILATION. KEEP CONTAINERS TIGHTLY CLOSED & UPRIGHT WHEN NOT IN USE. DON'T TAKE INTERNALLY. Other Precautions:KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT W/SKIN, EYES & BREATHING OF VAPORS. AVOID CONDITIONS WHICH RESULT IN FORMATION OF INHALABLE PARTICLES SUCH AS SPRAYING OR ABRADING (SANDING) PAINTED SURFAC ES.

#### **Exposure Controls**

Respiratory Protection:USE ONLY NIOSH/MSHA APPROVED RESPIRATORS Ventilation:DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS. Protective Gloves:IMPERVIOUS Eye Protection:SAFETY GLASSES OR GOGGLES Other Protective Equipment:EYE WASH, SAFETY SHOWER Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WASH HANDS THOROUGHLY AFTER HANDLING, BEFORE EATING OR SMOKING.

Supplemental Safety and Health

# **Chemical Properties**

Boiling Pt:B.P. Text: 212F Percent Volatiles by Volume:69%

# Stability

Stability Indicator/Materials to Avoid:YES OXIDIZERS, HYDROFLUORIC ACID Stability Condition to Avoid:ELEVATED TEMPERATURES Hazardous Decomposition Products:CO, CO2

# Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE W/ALL APPLICABLE REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.



https://msdsreport.com/msds/BBLWN

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.