

1225 RUSTMASTER AEROSOL SPRAY GLOSS BLACK

MSDS Number

BBLWP

National Stock Number

8010-00F002860

Product Name

1225 RUSTMASTER AEROSOL SPRAY GLOSS BLACK

Manufacturer

GLIDDEN COMPANY SCM

Product Identification

Product ID:1225 RUSTMASTER AEROSOL SPRAY GLOSS BLACK

MSDS Date:09/06/1988

FSC:8010

NIIN:00F002860

MSDS Number: BBLWP

Responsible Party

GLIDDEN COMPANY/SCM

925 EUCLID

CLEVELAND , OH 44115

Emergency Phone: (216) 826-5566

Info Phone: (216) 826-5566

Cage: EO697

Contractor

GLIDDEN PAINT, ICI PAINTS NORTH AMERICA

CLEVELAND, OH 44115

US

800-545-2643/216-344-8207

Cage: 01PD6

Ingredients

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS: 1317-65-3

RTECS: EV9580000

Fraction By Weight: 1-5%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9192

ALIPHATIC NAPHTHA, V.M. & P. NAPHTHA, LACOLENE

CAS: 64742-89-8

Fraction By Weight: 8-13%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 18-23%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 18-23%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ISOBUTANE, 2-METHYLPROPANE

CAS: 75-28-5

RTECS: TZ4300000

Fraction By Weight: 2-7%

OSHA PEL1800 MG/CUM

ACGIH TLV: 1000 PPM

ALKYD RESIN, SAFFLOWER OIL, POLYMER W/PENTAERYTHRITOL,

CAS: 68072-13-9

Fraction By Weight: 12-17%

ACGIH TLV: NONE

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 17-22%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIAN; 9192

ISOBUTANE, 2-METHYLPROPANE

CAS: 75-28-5

RTECS: TZ4300000

Fraction By Weight: 2-7%

OSHA PEL1800 MG/CUM

ACGIH TLV: 1000 PPM

Hazards

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: EYES: IRRITATION, REDNESS & CORNEAL INJURY. SKIN: IRRITATION. INHALATION: RESPIRATORY TRACT IRRITATION, DIZZINESS, UNCOORDINATION, COUGHING, CENTRAL NERVOUS SYSTEM DEPRESSION, NARCOSIS, LIVER/KIDNEY DAMAGE, UNCONSCIOUSNESS & PARALYSIS. INGESTION: VOMITING, DIARRHEA, NAUSEA & DIGESTIVE SYSTEM PROBLEMS.

Explanation of Carcinogenicity: NONE

Effects of Overexposure: INHALATION: PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. INGESTION: LUNG INFLAMMATION & DAMAGE DUE TO ASPIRATION OF MATERIAL INTO LUNGS.

Medical Condition Aggravated by Exposure: ASTHMA-LIKE CONDITIONS

First Aid

First Aid: INHALATION: REMOVE TO FRESH AIR. RESTORE & SUPPORT CONTINUED BREATHING. HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY, GET MEDICAL ATTENTION. SKIN: WASH OFF WITH PLENTY OF SOAP & WATER. REMOVE CONTAMINATED CLOTHING BEFORE REUSE & DISCARD SHOES. EYES: FLUSH WITH LARGE AMOUNTS OF WATER. OBTAIN MEDICAL ATTENTION. INGESTION: OBTAIN MEDICAL ATTENTION.

Fire Fighting

Flash Point Method: SCC

Flash Point: Lower Limits: 0.9%

Extinguishing Media: DRY CHEMICAL OR FOAM

Fire Fighting Procedures: WATER MAY BE USED TO COOL & PROTECT EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY BURST TO EXTREME HEAT OR FIRE.

Accidental Release

Spill Release Procedures: SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS. EVACUATE UNNECESSARY PERSONNEL. LARGE SPILLS SHUT OFF LEAK IF SAFE TO DO. DIKE & CONTAIN SPILL. PUMP TO STORAGE/SALVAGE VESSELS. USE ABSORBENT TO PICK UP EXCESS RESIDUE. KEEP OUT OF SEWERS/WATER COURSES.

Handling

Handling and Storage Precautions: STORE VENTILATED. DON'T TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN, EYES & BREATHING VAPORS.

Other Precautions: WASH HANDS THOROUGHLY AFTER HANDLING, BEFORE EATING OR SMOKING. KEEP CONTAINERS TIGHTLY CLOSED & UPRIGHT WHEN NOT IN USE. IF SANDING IS DONE, WEAR A DUSTMASK TO AVOID BREATHING OF SANDING DUST. EMPTY CONTAINERS CONTAIN HAZARDOUS RESIDUES.

Exposure Controls

Respiratory Protection: CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE STANDARDS. WHERE RESPIRATORY PROTECTION IS REQUIRED. USE NIOSH/MSHA APPROVED RESPIRATORS IN ACCORDANCE WITH OSHA STANDARDS.

Ventilation: PROVIDE LOCAL EXHAUST VENTILATION TO PREVENT BUILD-UP OF VAPORS.

Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY GLASSES, GOGGLES
Other Protective Equipment:EYE WASH & SAFETY SHOWER
Work Hygienic Practices:REMOVE/WASH CONTAMINATED CLOTHING BEFORE REUSE
& DISCARD SHOES.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:133-290F
Appearance and Odor:BLACK AEROSOL
Percent Volatiles by Volume:85.0%

Stability

Stability Indicator/Materials to Avoid:YES
OXIDIZERS, ACIDS, BASES, ALDEHYDES, ALKYLHALIDES, HALOGENS, AMINES
Stability Condition to Avoid:ELEVATED TEMPERATURES,
Hazardous Decomposition Products:CO, CO2

Disposal

Waste Disposal Methods:COMPLY W/ALL APPLICABLE HEALTH & ENVIRONMENTAL
REGULATIONS. DISPOSE IN ACCORDANCE W/ALL APPLICABLE REGULATIONS.
AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.