

3718 SPRED ENAMEL LATEX SG PASTEL TINT BASE

MSDS Number

BBLWS

National Stock Number

8010-00F002863

Product Name

3718 SPRED ENAMEL LATEX SG PASTEL TINT BASE

Manufacturer

GLIDDEN COMPANY SCM CORP

Product Identification

Product ID:3718 SPRED ENAMEL LATEX SG PASTEL TINT BASE

MSDS Date:06/29/1991

FSC:8010

NIIN:00F002863

MSDS Number: BBLWS

Responsible Party

GLIDDEN COMPANY/SCM CORPORATION

925 EUCLID AVENUE

CLEVELAND , OH 44115

Emergency Phone: (800) 545-2643

Info Phone: (800) 545-2643

Cage: EO697

Contractor

GLIDDEN PAINT, ICI PAINTS NORTH AMERICA

CLEVELAND, OH 44115

US

800-545-2643/216-344-8207

Cage: 01PD6

Ingredients

1,2-PROPANEDIOL (PROPYLENE GLYCOL)

CAS: 57-55-6

RTECS: TY2000000

Fraction By Weight: 1-5%

MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-REFINED HEAVY

CAS: 64741-88-4

RTECS: PY8040500

Fraction By Weight: 1-5%

OSHA PEL5 MG/CUM

ACGIH TLV: 5 MG/CUM

KAOLIN

CAS: 1332-58-7

RTECS: GF1670500

Fraction By Weight: 5-10%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 2 MG/M3 TDUST; 9293

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 10-20%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

VINYL ACETATE (SARA III)

CAS: 108-05-4

RTECS: AK0875000

Fraction By Weight: 1-1%

OSHA PEL10 PPM/15 STEL

ACGIH TLV: 10 PPM/15,A3 STEL;93

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

BUTYL ACRYLATE, METHACRYLIC ACID, METHYL METHACRYLATE

CAS: 25035-69-2

Fraction By Weight: 1-5%

STYRENE ACRYLIC COPOLYMER

Fraction By Weight: 1-5%

VINYL ACRYLIC RESIN

CAS: 25067-01-0

Fraction By Weight: 10-20%

WATER, H2O

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight: 40-50%

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: IRRITATION OF RESPIRATORY TRACT & PROBLEMS. SKIN: IRRITATION, DERMATITIS, ABSORPTION, ALLERGIC RESPONSE. EYES: IRRITATION. INGESTION: VOMITING, DIARRHEA, CNS DEPRESSION, KIDNEY DAMAGE.

Explanation of Carcinogenicity:NONE

Effects of Overexposure: INHALATION: RESPIRATORY TRACT IRRITATION & PROBLEMS. SKIN: IRRITATION, DERMATITIS, ABSORPTION, ALLERGIC RESPONSE. EYES: IRRITATION. INGESTION: VOMITING, DIARRHEA, CNS DEPRESSION, KIDNEY DAMAGE.
Medical Cond Aggravated by Exposure: EYE, SKIN, RESPIRATORY DISORDERS, KIDNEY DISORDERS.

First Aid

First Aid: INHALATION: REMOVE TO FRESH AIR. RESTORE & SUPPORT CONTINUED BREATHING. HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. SKIN; WASH OFF QUICKLY W/PLENTRY OF WATER & SOAP. EYES: FLUSH W/PLENTRY OF WATER FOR AT LEAST 15 MINS. INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point: >200F
Upper Limits: 13.4%
Extinguishing Media: DRY CHEMICAL OR FOAM
Fire Fighting Procedures: WATER MAY BE USED TO COOL & PROTECT EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE.

Accidental Release

Spill Release Procedures: VENTILATE AREA. COLLECTED W/ABSORBENT MATERIALS.

Handling

Handling and Storage Precautions: STORE ONLY W/ADEQUATE VENTILATION. DON'T TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.
Other Precautions: AVOID CONTACT W/SKIN, EYES, & BREATHING OF VAPORS. KEEP CONTAINERS TIGHTLY CLOSED & UPRIGHT WHEN NOT IN USE. IF SANDING IS DONE, WEAR A DUSTMASK TO AVOID BREATHING OF SANDING DUST.

Exposure Controls

Respiratory Protection: WHERE RESPIRATORY PROTECTION IS REQUIRED, USE ONLY NIOSH/MSHA APPROVED RESPIRATORS IN ACCORDANCE W/OSHA STANDARD. IF SANDING IS DONE, WEAR A DUSTMASK TO AVOID BREATHING OF SANDING DUST.
Ventilation: PROVIDE MECHANICAL/LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.
Protective Gloves: IMPERVIOUS
Eye Protection: SAFETY GLASSES, GOGGLES
Other Protective Equipment: EYE WASH, SAFETY SHOWER
Work Hygienic Practices: REMOVE/WASH CONTAMINATED CLOTHING BEFORE REUSE. WASH HANDS THOROUGHLY AFTER HANDLING BEFORE EATING OR SMOKING.
Supplemental Safety and Health

Chemical Properties

Boiling Pt: B.P. Text: 162-212F
Spec Gravity: 1.193
Appearance and Odor: WHITE LIQUID
Percent Volatiles by Volume: 62.01%

Stability

Stability Indicator/Materials to Avoid: YES
OXIDIZERS, METALS, NITRIC ACID, HYDROFLUORIC ACID, ALCOHOLS.
Stability Condition to Avoid: HEAT, FIRE, ELEVATED TEMPS, FREEZING.
Hazardous Decomposition Products: CO, CO2

Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.