

## **5252 GLID-GUARD EPOXY CHROMATE METAL PRIMER**

### **MSDS Number**

BBLWV

### **National Stock Number**

8010-00F002865

### **Product Name**

5252 GLID-GUARD EPOXY CHROMATE METAL PRIMER

### **Manufacturer**

GLIDDEN COMPANY SCM CORP

### **Product Identification**

Product ID:5252 GLID-GUARD EPOXY CHROMATE METAL PRIMER

MSDS Date:11/01/1988

FSC:8010

NIIN:00F002865

MSDS Number: BBLWV

### **Responsible Party**

GLIDDEN COMPANY SCM CORPORATION

925 EUCLID AVENUE

CLEVELAND , OH 44115

Emergency Phone: (216) 826-5566

Info Phone: (216) 826-5566

Cage: 01PD6

### **Contractor**

GLIDDEN PAINT, ICI PAINTS NORTH AMERICA

CLEVELAND, OH 44115

US

800-545-2643/216-344-8207

Cage: 01PD6

### **Ingredients**

ANCAMINE 350 A (POLYAMIDE RESIN)

CAS: 88384-96-7

Fraction By Weight: 26-31%

ORGANOPHILIC CLAY

CAS: 68911-87-5

Fraction By Weight: 1-5%

OSHA PEL15 MG/CUM TOTAL DUST

ACGIH TLV: 10 MG/CUM TOTAL DUST

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 10-15%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight: 54-59%

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: IRRITATION OF RESPIRATORY TRACT/FATIGUE/DROWSINESS/DIZZINESS/LIGHTHEADEDNESS/HEADACHE/UNCOORDINATION/NAUSEA/COUGHING/VOMITING/MENTAL APATHY/CNS DEPRESSION/INTOXICATION/CONFUSION/ANESTHETIC EFFECT/NARCOSIS/BREATHING DIFFICULTY. SKIN: IRRITATION/DERMATITIS/DEFATTING. EYE: IRRITATION/TEARING/BLURRED VISION.

Explanation of Carcinogenicity:THIS PRODUCT CONTAINS ZINC CHROMATE WHICH CAN CAUSE RESPIRATORY TRACT CANCER.  
Effects of Overexposure:INGESTION: INJURY/LUNG INFLAMMATION/ASPIRATION INTO LUNGS. EYE: IRRITATION/BLURRED VISION/TEARING/REDNESS/SEVERE IRRITATION. SKIN: IRRITATION/DERMATITIS/DEFATTING/ALLERGIC RESPONSE/SENSITIVITY. INHALATION: PERMANENT BRAIN/NERVOUS SYSTEM DAMAGE/PNEUMONCONIOSIS/DECREASED CHEST EXPANSION/WEIGHT LOSS/WEAKNESS/DEATH.

Medical Cond Aggravated by Exposure:EYE, SKIN, RESPIRATORY/LUNG DISORDERS, ASTHMA-LIKE CONDITIONS, CARDIAC ABNORMALITIES, KIDNEY/LIVER DISORDERS, NERVOUS SYSTEM DISORDERS.

## First Aid

First Aid:EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. SKIN: WASH THOROUGHLY W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. GIVE CPR OR OXYGEN IF NEEDED. INGESTION: OBTAIN MEDICAL ATTENTION IF REQUIRED .

## Fire Fighting

Flash Point:40F

Lower Limits:1.2%

Extinguishing Media:DRY CHEMICAL OR FOAM

Fire Fighting Procedures:USE WATER TO KEEP FIRE-EXPOSED CONTAINERS COOL.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY BURST, VENT & EXPLODE DUE TO EXTREME HEAT & FLAME. VAPORS CAN FORM EXPLOSIVE MIXTURES IN AIR AT ELEVATED TEMPERATURES.

## Accidental Release

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. VENT AREA W/EXPLOSION-PROOF EQUIPEMENT. SMALL SPIS MAY BE COLLECTED W/ABSORBENT MATERIALS. USE NON-SPARKING TOOLS. LARGE ILLS-OBSERVE STEPS FOR SMALL SPILLS. SHUT OF F LEAK IF SAFE TO DO SO.

## Handling

Handling and Storage Precautions:STORE BELOW 80F. USE ONLY WITH ADEQUATE VENTILATION. DON'T TAKE INTERNALLY. KEEP OUT OF REACH CHILDREN. CONTACT W/COPPER SHOULD BE AVOIDED.

Other Precautions: AVOID CONTACT WITH SKIN/EYES/BREATHING OF VAPORS. WASH HANDS AFTER HANDLING/BEFORE EATING/SMOKING. KEEP CONTAINERS TIGHTLY CLOSED & UPRIGHT WHEN NOT IN USE. EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES. GROUND EQUIP WHEN TRANSFERRING.

## Exposure Controls

Respiratory Protection: IF SANDING IS DONE, WEAR A DUST MASK TO AVOID BREATHING OF SANDING DUST. IF >TLV, USE ONLY NIOSH/MSHA APPROVED RESPIRATORS.  
Ventilation: PROVIDE LOCAL EXHAUST/MECHANICAL VENTILATION TO PREVENT BUILD-UP OF VAPORS.  
Protective Gloves: IMPERVIOUS  
Eye Protection: SAFETY GLASSES OR GOGGLES  
Other Protective Equipment: EYE WASH & SAFETY SHOWER.  
Work Hygienic Practices: WASH HANDS THOROUGHLY AFTER HANDLING.  
Supplemental Safety and Health  
WT/GAL: 7.1 LBS.

## Chemical Properties

Boiling Pt: B.P. Text: 179-231F  
Percent Volatiles by Volume: 74.3%

## Stability

Stability Indicator/Materials to Avoid: YES  
OXIDIZERS, ACIDS, BASES, AMINES, ORGANIC MATERIALS  
Stability Condition to Avoid: ELEVATED TEMPERATURES, HEAT, FIRE  
Hazardous Decomposition Products: CO, CO<sub>2</sub>, OXIDES OF NITROGEN, FORMALDEHYDE, & CHROMIUM OXIDE

## Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.