

# **FLEXSEAL LACQUER**

# **MSDS Number**

**BBLYF** 

# **National Stock Number**

6520-00F002895

# **Product Name**

FLEXSEAL LACQUER

#### Manufacturer

AUSTENAL INC

# **Product Identification**

Product ID:FLEXSEAL LACQUER MSDS Date: 01/01/1987 FSC:6520 NIIN:00F002895 MSDS Number: BBLYF

# **Responsible Party**

AUSTENAL INC

4101 W 51ST ST

CHICAGO, IL 60632

US

Emergency Phone: 312-735-0601

Info Phone: 800-621-0381

Cage: 67532 **Contractor** 

**AUSTENAL INC** 

**UNKNOW** 

CHICAGO, IL 60632

US

800-621-0381 Cage: 67532

# **Ingredients**

ACETONE; DIMETHYL KETONE

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 40%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

ETHANOL (ETHYL ALCOHOL), TECSOL, ALCOHOL

CAS: 64-17-5

RTECS: KQ6300000



Fraction By Weight: 40% OSHA PEL1000 PPM

ACGIH TLV: 1000 PPM

#### Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: RESPIRATORY TRACT IRRITATION, HEADACHE, DIZZINESS, DROWSINESS. EYES: IRRITATION.

Explanation of Carcinogenicity: NONE

#### First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. SKIN: WASH THOROUGHLY W/SOAP & WATER. EYES: FLUSH W/WATER FOR AT LEAST 15 MINS. OBTAIN MEDICAL

ATTENTION IN ALL CASES.

# Fire Fighting

Flash Point Method:TCC

Flash Point:20C

Extinguishing Media: CO2 OR DRY CHEMICAL FOR SMALL FIRES.

#### **Accidental Release**

Spill Release Procedures: ELIMINATE ALL SOURCES OF IGNITION. COVER SPILL WITH SAND AND TRANSFER TO CONTAINER FOR DISPOSAL.

# Handling

Handling and Storage Precautions: DON'T HANDLE OR STORE NEAR FLAME OR HEAT. ADEQUATE VENTILATION REQUIRED. KEEP CONTAINER CLOSED WHEN NOT IN USE.

# **Exposure Controls**

Respiratory Protection: N/K

Ventilation: ADEQUATE

Supplemental Safety and Health

PRODUCT HAS BEEN DISCONTINUED, BUT HAS BEEN REPLACED BY FLEXSEAL LIQUID

ADHESIVE, NSN NR: 652000F028179.

# **Chemical Properties**

Boiling Pt:B.P. Text:153F Spec Gravity:0.87 Solubility in Water:PARTIAL

Appearance and Odor: AMBER FLAMMABLE LIQUID; SHARP NON-RESIDUAL ODOR

Percent Volatiles by Volume:

# Stability

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:FLAME OR HEAT

### **Disposal**

Waste Disposal Methods: DISPOSE OF MATERIAL IN APPROVED LANDFILL SITE. CHECK STATE AND LOCAL EPA REGULATIONS BEFORE DISPOSAL.

\_\_\_\_\_

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.