

## **1228, RUSTMASTER SPRAY- FLAT BLACK**

### **MSDS Number**

BBLYX

### **National Stock Number**

8010-00F002911

### **Product Name**

1228, RUSTMASTER SPRAY- FLAT BLACK

### **Manufacturer**

GLIDDEN COMPANY SCM

### **Product Identification**

Product ID:1228, RUSTMASTER SPRAY- FLAT BLACK

MSDS Date:11/01/1988

FSC:8010

NIIN:00F002911

MSDS Number: BBLYX

### **Responsible Party**

GLIDDEN COMPANY/SCM

925 EUCLID AVENUE

CLEVELAND , OH 44115

Emergency Phone: (216) 826-5566

Info Phone: (216) 826-5566

Cage: EO697

### **Contractor**

GLIDDEN COMPANY/SCM

15049

CLEVELAND, OH 44115

US

(216) 826-5566

Cage: EO697

### **Ingredients**

ALKYD RESIN, SAFFLOWER OIL, POLYMER W/PENTAERYTHRITOL,

CAS: 68072-13-9

Fraction By Weight: 4-9%

ACGIH TLV: NONE

ALIPHATIC NAPHTHA, V.M. & P. NAPHTHA, LACOLENE

CAS: 64742-89-8

Fraction By Weight: 2-7%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

TALC (CONTAINING NO ASBESTOS)

CAS: 14807-96-6

RTECS: WW2710000

Fraction By Weight: 4-9%

OSHA PEL2 MG/M3 RDUST

ACGIH TLV: 2 MG/M3 RDUST; 9192

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 36-41%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 11-16%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 17-22%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIAANT; 9192

ISOBUTANE, 2-METHYLPROPANE

CAS: 75-28-5

RTECS: TZ4300000

Fraction By Weight: 2-7%

OSHA PEL1800 MG/CUM

ACGIH TLV: 1000 PPM

BUTANE

CAS: 106-97-8

RTECS: EJ4200000

Fraction By Weight: 4-9%

OSHA PEL800 PPM

ACGIH TLV: 800 PPM; 9192

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:SKIN: IRRITATION, DERMATITIS, &  
DEFATTING. INGESTION: DROWSINESS/DIZZINESS/LIGHT  
HEADEDNESS/HEADACHE/NAUSEA/VOMITING/DIARRHEA/DIGESTIVE SYSTEM  
PROBLEMS/MENTAL APATHY/ANESTHETIC EFFECT/NARCOSIS/BLOOD A  
BNORMALITIES/LIVER/KIDNEY DAMAGE/CONVULSIONS/UNCONSCIOUSNESS &  
PARALYSIS. INHALATION: HARMFUL & FATAL.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:INHALATION: PROLONGED EQPOSURE TO SOLVENTS CAN  
RESULT IN PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. INGESTION:  
LARGER AMOUNTS MAY CAUSE LUNG INFLAMMATIOLN & DAMAGE DUE TO  
ASPIRATION OF MATERIAL INTO LUN GS.

## First Aid

First Aid:INHALATION: MOVE PERSON TO WELL VENTILATED AREA. GET MED ATT.  
ADMINISTER OXYGEN. SKIN: FLUSH W/WATER & WASH WITH SOAP/WATER. EYE:  
FLUSH W/WATER FOR AT LEAST 15 MINUTES. GET MED ATT. INGESTION: GET  
EME RGENCY MEDICAL ATTENTION.

## Fire Fighting

Flash Point:Lower Limits:0.9%  
Extinguishing Media:DRY CHEMICAL OR FOAM  
Fire Fighting Procedures:WATER COOL CONTAINERS AND EXPOSED EXPLOSIONS.  
Unusual Fire/Explosion Hazard:VAPOR >AIR MAY IGNITE EXPLOSIVELY, MAY  
DECOMPOSE EMITTING IRRITANT AND/OR TOXIC GASES.

## Accidental Release

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. VENTILATE  
AREA WITH EXPLOSION-PROOF EQUIPMENT. SML SPILLS MAY BE COLLECTED  
WITH ABSORBENT MATERIALS. USE NON-SPARKING TOO.

## Handling

Handling and Storage Precautions:STORE BELOW 80F. KEEP AWAY FROM  
HEAT/SPARKS/OPEN FLAME. USE ONLY W/ADEQUATE VENTILATION. KEEP  
NTAINERS TIGHTLY CLOSED/UPRIGHT WHEN NOT IN USE.  
Other Precautions:DON'T TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.  
AVOID CONTACT WITH EYES/SKIN/BREATHING OF VAPORS. WASH HANDS AFTER  
HANING, ESPECIALLY BEFORE EATING OR SMOKING.

## Exposure Controls

Respiratory Protection:USE ONLY NIOSH/MSHA APPROVED RESPIRATORS.  
Ventilation:PROVIDE LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS  
Protective Gloves:RUBBER/NEOPRENE  
Eye Protection:SAFETY GLASSES OR GOGGLES  
Other Protective Equipment:EYE WASH & SAFETY SHOWER.  
Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE  
REUSE.  
Supplemental Safety and Health

## Chemical Properties

Boiling Pt:B.P. Text:133-290%  
Percent Volatiles by Volume:85.0%

## Stability

Stability Indicator/Materials to Avoid:YES  
OXIDIZERS, ACIDS, BASES, ALDEHYDES, ALKYLHALIDES, HALOGENS, & AMINES  
Stability Condition to Avoid:ELEVATED TEMPERATURES  
Hazardous Decomposition Products:CO, CO2

## Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH ALL APPLICABLE  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.