

1234, RUSTMASTER SPRAY - DEEP BLUE

MSDS Number

BBLYZ

National Stock Number

8010-00F002913

Product Name

1234, RUSTMASTER SPRAY - DEEP BLUE

Manufacturer

GLIDDEN COMPANY SCM

Product Identification

Product ID:1234, RUSTMASTER SPRAY - DEEP BLUE

MSDS Date:11/01/1988

FSC:8010

NIIN:00F002913

MSDS Number: BBLYZ

Responsible Party

GLIDDEN COMPANY/SCM

925 EUCLID AVENUE

CLEVELAND , OH 44115

Emergency Phone: (216) 826-5566

Info Phone: (216) 826-5566

Cage: EO697

Contractor

GLIDDEN PAINT, ICI PAINTS NORTH AMERICA

CLEVELAND, OH 44115

US

800-545-2643/216-344-8207

Cage: 01PD6

Ingredients

ALIPHATIC NAPHTHA, V.M. & P. NAPHTHA, LACOLENE

CAS: 64742-89-8

Fraction By Weight: 6-11%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 1-5%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 26-31%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 12-17%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 17-22%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIAN; 9192

ISOBUTANE, 2-METHYLPROPANE

CAS: 75-28-5

RTECS: TZ4300000

Fraction By Weight: 2-7%

OSHA PEL1800 MG/CUM

ACGIH TLV: 1000 PPM

BUTANE

CAS: 106-97-8

RTECS: EJ4200000

Fraction By Weight: 4-9%

OSHA PEL800 PPM

ACGIH TLV: 800 PPM; 9192

ALKYD RESIN, SAFFLOWER OIL, POLYMER W/PENTAERYTHRITOL,

CAS: 68072-13-9

Fraction By Weight: 11-16%

ACGIH TLV: NONE

CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS: 1317-65-3

RTECS: EV9580000

Fraction By Weight: 1-5%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9192

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: DROWSINESS/DIZZINESS/LIGHT
HEADEDNESS/HEADACHE/NAUSEA/VOMITING/DIARRHEA/DIGESTIVE SYSTEM
PROBLEMS/MENTAL APATHY/ANESTHETIC EFFECT/NARCOSIS/BLOOD
ABNORMALITIES/LIVER/KIDNEY DAMAGE/CONVULSIONS/UNCONSCIOUSNESS &
PARALYSIS. SKIN: IRRITATION. EYES: REDNESS & CORNEAL INJURY.
INGESTION: HARMFUL & FATAL.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:INHALATION; PROLONGED EXPOSURE TO SOLVENTS CAN
RESULT IN PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. INGESTION:
LARGER AMOUNTS MAY CAUSE LUNG INFLAMMATION & DAMAGE DUE TO
ASPIRATION OF MATERIAL INTO LUNGS.

First Aid

First Aid:INHALATION: MOVE PERSON TO WELL VENTILATED AREA. GET MED ATT.
SKIN: FLUSH W/WATER & WASH WITH SOAP/WATER. EYE: FLUSH W/WATER FOR
AT LEAST 15 MINUTES. GET EMERGENCY MEDICAL ATTENTION. INGESTION:
GET EMERGENCY MEDICAL ATTENTION.

Fire Fighting

Flash Point:Lower Limits:0.9%
Extinguishing Media:DRY CHEMICAL OR FOAM
Fire Fighting Procedures:WATER COOL CONTAINERS & PROTECT FROM
EXPLOSIONS.
Unusual Fire/Explosion Hazard:VAPOR >AIR MAY IGNITE EXPLOSIVELY, MAY
DECOMPOSE EMITTING IRRITANT AND/OR TOXIC GASES.

Accidental Release

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. VENTILATE
AREA W/EXPLOSION-PROOF EQUIPMENT. SMALL SPILLS MAY BE COLLECTED
W/ABSORBENT MATERIALS. USE NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions:STORE BELOW 80F. USE ONLY WITH
ADEQUATE VENTILATION. DON'T TAKE INTERNALLY. KEEP OUT OF REACH
CHILDREN.
Other Precautions:AVOID CONTACT WITH SKIN/EYES/BREATHING OF VAPORS.
WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING OR
SMOKING.KEEP CONTAINERS TIGHTLY CLOSED & UPRIGHT WHEN NOT IN USE.

Exposure Controls

Respiratory Protection:USE ONLY NIOSH/MSHA APPROVED RESPIRATORS
Ventilation:PROVIDE LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS
Protective Gloves:RUBBER/NEOPRENE
Eye Protection:SAFETY GLASSES OR GOGGLES
Other Protective Equipment:EYE WASH & SAFETY SHOWER.
Work Hygienic Practices:REMOVE CONTAMINATED CLOTHING.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:133-290F
Percent Volatiles by Volume:85.0%

Stability

Stability Indicator/Materials to Avoid: YES

OXIDIZERS, ACIDS, BASES, ALDEHYDES, ALKYLHALIDES, HALOGENS, AMINES

Stability Condition to Avoid: ELEVATED TEMPERATURES

Hazardous Decomposition Products: CO, CO₂

Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.