

DAP BUTYL-FLEX CANADIAN CAULK

MSDS Number

BBMBY

National Stock Number

8030-00F002955

Product Name

DAP BUTYL-FLEX CANADIAN CAULK

Manufacturer

DAP INC

Product Identification

Product ID:DAP BUTYL-FLEX CANADIAN CAULK

MSDS Date:07/18/1989

FSC:8030

NIIN:00F002955

MSDS Number: BBMBY

Responsible Party

DAP INC

5300 HUBERVILLE RD

DAYTON , OH 45401-0277

US

Emergency Phone: 513-667-4461/800-543-3840

Info Phone: 513-667-4461/800-543-3840

Cage: 90300

Contractor

DAP INC.

277

DAYTON, OH 45401-0277

US

513-253-7154/800-543-3840

Cage: 90300

Ingredients

STODDARD SOLVENT (PETROLEUM DISTILLATE), MINERAL SPIRITS

CAS: 8052-41-3

RTECS: WJ8925000

Fraction By Weight: 5-10%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM; 9293

LIGHT ALIPHATIC NAPHTHA, VM & P NAPHTHA, LACOLENE *93/1*

CAS: 64742-89-8

Fraction By Weight: 5-10%

OSHA PEL300 PPM

ACGIH TLV: 300 PPM

211 G/L;

RTECS: 9999999VO

TRADE SECRET COMPONENT

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES/SKIN: IRRITATION. INHALATION:
UPPER RESPIRATORY TRACT IRRITATION. HARMFUL. MAY AFFECT THE BRAIN
OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. INGESTION:
HARMFUL OR FATAL. VOMITING, DIA RRHEA & DEPRESSED RESPIRATION.
ASPIRATION HAZARD.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:INHALATION: PERMANENT BRAIN & NERVOUS SYSTEM
DAMAGE.

First Aid

First Aid:EYES: FLUSH W/PLENTY OF WATER FOR 15 MINS. SKIN: WASH W/SOAP
& WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: DON'T INDUCE
VOMITING. ASPIRATION OF MATERIAL INTO THE LUNGS DUE TO VOMITING CAN
CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. OBTAIN MEDICAL
ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:TCC
Flash Point:14C
Extinguishing Media:FOAM, CO2 OR DRY CHEMICALS
Fire Fighting Procedures:USE FULL PROTECTIVE EQUIPMENT & SCBA. COOL
EXPOSED CONTAINERS W/WATER.
Unusual Fire/Explosion Hazard:CONTAINERS MAY EXPLODE IF EXPOSED TO
EXTREME HEAT. VAPORS ARE HEAVIER THAN AIR & WILL COLLECT IN LOW
AREAS. CHECK AREAS BEFORE ENTERING.

Accidental Release

Spill Release Procedures:USE ABSORBENT MATERIAL OR SCRAPE UP DRIED
MATERIAL & PLACE INTO CONTAINERS.

Handling

Handling and Storage Precautions:KEEP CONTAINERS FROM EXCESSIVE HEAT &
FREEZING. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. DON'T
STORE AT TEMPERATURES ABOVE 120F.
Other Precautions:STORE AWAY FROM CAUSTICS & OXIDIZERS. KEEP OUT OF
REACH OF CHILDREN. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING
& INHALING VAPORS MAY BE HARMFUL OR FATAL.

Exposure Controls

Respiratory Protection:IF 8-HR EXPOSURE LIMIT OR VALUE IS EXCEEDED FOR
ANY COMPONENT, USE AN APPROVED NIOSH/OSHA RESPIRATOR.
Ventilation:PROVIDE SUFFICIENT MECHANICAL VENTILATION (LOCAL OR GENERAL
EXHAUST) TO KEEP BELOW PEL & TLV.
Protective Gloves:SOLVENT IMPERVIOUS
Eye Protection:GOGGLES OR SAFETY GLASSES W/SIDE SHIELDS
Other Protective Equipment:EYEWASH & SOLVENT IMPERVIOUS APRON IF BODY
CONTACT W/PRODUCT OCCURS. BARRIER CREAMS MAY BE USED.
Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE
REUSE.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:212F
Vapor Pres:30 (VM&P)

Vapor Density:>1
Spec Gravity:1.46
Evaporation Rate & Reference:(N-BU AC = 1): Solubility in Water:NEGLIGIBLE
Appearance and Odor:OPAQUE PASTE W/A PETROLEUM DISTILLATE ODOR.
Percent Volatiles by Volume:27%

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS & CAUSTICS
Stability Condition to Avoid:EXCESSIVE HEAT & FREEZING
Hazardous Decomposition Products:NORMAL COMBUSTION PRODUCTS SUCH AS CO,
CO2, NITROGEN OXIDE.

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, &
FEDERAL REGULATIONS. DISCARDED MATERIAL SHOULD BE INCINERATED AT A
PERMITTED FACILITY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.