

# WELDWOOD ACRYLIC LATEX CONTACT CEMENT

### **MSDS Number**

BBMCK

### **National Stock Number**

8040-00F002964

### **Product Name**

WELDWOOD ACRYLIC LATEX CONTACT CEMENT

### Manufacturer

DAP INC

# **Product Identification**

Product ID:WELDWOOD ACRYLIC LATEX CONTACT CEMENT MSDS Date:08/07/1992 FSC:8040 NIIN:00F002964 MSDS Number: BBMCK

# **Responsible Party**

DAP INC

5300 HUBERVILLE RD

DAYTON , OH 45401-0277

US

Emergency Phone: 513-667-4461/800-543-3840

Info Phone: 513-667-4461/800-543-3840

Cage: 90300

### Contractor

DAP INC.

277

DAYTON, OH 45401-0277

US

513-253-7154/800-543-3840

Cage: 90300

# Ingredients

TRADE SECRET COMPONENT

95-105

RTECS: 9999999VO

# Hazards

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Explanation of Carcinogenicity:NONE

# First Aid

First Aid:EYES: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINS. SKIN: WASH W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

# **Fire Fighting**



#### Flash Point:NONE

Extinguishing Media:FOAM, WATER, DRY CHEMICALS Fire Fighting Procedures:USE WATER SPRAY TO COOL EXPOSED SURFACES

•

#### **Accidental Release**

Spill Release Procedures: DIKE SPILL AREA. ABSORB REMAINING LIQUID W/ABSORBENT MATERIAL & PLACE INTO CONTAINERS.

### Handling

Handling and Storage Precautions:STORE AWAY FORM CAUSTICS & OXIDIZERS. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. KEEP CONTAINERS FROM EXCESSIVE HEAT & FREEZING. Other Precautions:DON'T STORE AT TEMPERATURES ABOVE 120F. KEEP OUT OF REACH OF CHILDREN.

### **Exposure Controls**

Respiratory Protection:NONE REQUIRED UNDER NORMAL USAGE. Ventilation:NORMAL ROOM VENTILATION Protective Gloves:RECOMMENDED Eye Protection:SAFETY GLASSES W/SIDE SHIELDS Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health

# **Chemical Properties**

Boiling Pt:B.P. Text:212F Vapor Pres:17 Vapor Density:>1 Spec Gravity:1.06 Evaporation Rate & Reference:(WATER=1): 1 Solubility in Water:COMPLETE Appearance and Odor:TAN MOBILE LIQUID W/SLIGHT AMMONIA ODOR Percent Volatiles by Volume:45-50%

### Stability

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS & CAUSTICS Stability Condition to Avoid:EXCESSIVE HEAT & FREEZING Hazardous Decomposition Products:NORMAL COMBUSTION PRODUCTS SUCH AS CARBON OXIDE & NITROGEN OXIDE.

#### Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.