

DUNCAN MASK 'N PEEL SY658

MSDS Number

BBMCW

National Stock Number

8010-00F002972

Product Name

DUNCAN MASK 'N PEEL SY658

Manufacturer

DUNCAN ENTERPRISES

Product Identification

Product ID:DUNCAN MASK 'N PEEL SY658

MSDS Date:09/01/1987

FSC:8010

NIIN:00F002972

MSDS Number: BBMCW

Responsible Party

DUNCAN ENTERPRISES

5673 E. SHIELDS AVENUE

FRESNO , CA 93727

Emergency Phone: (303) 623-4884

Info Phone: (209) 291-4444

Preparer: CURT SATHRE

Cage: 21546

Contractor

DUNCAN ENTERPRISES

FRESNO, CA 93727

US

209-291-4444

Cage: 21546

Ingredients

AMMONIA (SARA III)

CAS: 7664-41-7

RTECS: BO0875000

OSHA PEL50 PPM

ACGIH TLV: 25 PPM/35 STEL; 9293

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: THROAT IRRITATION & RESPIRATORY DISTRESS. EYES: IRRITATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:EYES: IRRITATION. INHALATION: THROAT IRRITATION & RESPIRATORY DISTRESS.

First Aid

First Aid:EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. SKIN: WASH THOROUGHLY W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Extinguishing Media:WATER, CO2, DRY CHEMICAL, DRIED FILM
Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. FULL PROTECTIVE CLOTHING & SCBA.
Unusual Fire/Explosion Hazard:BURNING DRY LATEX PRODUCES DENSE, BLACK SMOKE W/THE POTENTIAL FOR TOXIC VAPORS.

Accidental Release

Spill Release Procedures:CONFINE SPILL TO PREVENT CONTAMINATION OF SEWER SYSTEM OF GROUND WATER. ABSORB LIQUID ONTO AN APPROPRIATE ABSORBENT. SPILLAGE WILL CAUSE SLIPPERY CONDITIONS.

Handling

Handling and Storage Precautions:AVOID TEMPERATURE EXTREMES. KEEP FROM FREEZING. WHEN USING, DON'T EAT, DRINK, OR SMOKE. KEEP SEALED. KEEP OUT OF REACH OF CHILDREN.
Other Precautions:NONE

Exposure Controls

Respiratory Protection:IF OTHER NIOSH APPROVED RESPIRATORY PROTECTION.
Ventilation:LOCAL EXHAUST/MECHANICAL: RECOMMENDED ESPECIALLY WHEN SPRAYING.
Protective Gloves:VINYL, RUBBER
Eye Protection:RECOMMENDED
Other Protective Equipment:SAFETY SHOWER, EYE WASH STATIONS
Work Hygienic Practices:USE GOOD WORK HYGIENE PRACTICES.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:212F
Vapor Density:AS WATER
Spec Gravity:0.96
Evaporation Rate & Reference:(BU AC = 1): 1
Appearance and Odor:CREAM COLORED LIQUID W/SLIGHT AMMONIA ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
SOLVENTS, ACIDS, METAL SALTS, & OTHER COMPOUNDS
Stability Condition to Avoid:ELEVATED TEMPERATURES
Hazardous Decomposition Products:TOXIC GASES

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.