

TRANSLUCENT ANTIQUE STAIN TS500 SERIES

MSDS Number

BBMDG

National Stock Number

8010-00F002978

Product Name

TRANSLUCENT ANTIQUE STAIN TS500 SERIES

Manufacturer

DUNCAN ENTERPRISES

Product Identification

Product ID:TRANSLUCENT ANTIQUE STAIN TS500 SERIES

MSDS Date:04/01/1991

FSC:8010

NIIN:00F002978

MSDS Number: BBMDG

Responsible Party

DUNCAN ENTERPRISES

5673 E SHIELDS AVE

FRESNO , CA 93727-7819

US

Emergency Phone: 209-445-1222

Info Phone: 209-291-4444

Preparer: CURT SATHRE

Cage: 21546

Contractor

DUNCAN ENTERPRISES

FRESNO, CA 93727

US

209-291-4444

Cage: 21546

Ingredients

AROMATIC PETROLEUM DISTILLATE, HEAVY STRAIGHT RUN NAPHTHA

CAS: 64741-41-9

OSHA PEL500 MG/CUM

ACGIH TLV: 100 MG/CUM

Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: NOSE/THROAT IRRITATION, DROWSINESS, DIZZINESS & FATIGUE. INGESTION: DIGESTIVE TRACT IRRITATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHALATION: BRAIN & NERVE SYSTEM DAMAGE.

Medical Cond Aggravated by Exposure:SKIN & RESPIRATORY DISORDERS

First Aid

First Aid:INGESTION: DON'T INDUCE VOMITING. EYES: FLUSH W/WATER FOR AT

LEAST 15 MINS. SKIN: WASH W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point:104F
Upper Limits:0.6-0.7%
Extinguishing Media:DRY CHEMICAL, CO2 OR FOAM
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS
Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR & MAY TRAVEL CONSIDERABLE DISTANCES. USE AWAY FROM IGNITION SOURCES.

Accidental Release

Spill Release Procedures:ELIMINATE ALL OPEN FLAMES IN VICINITY OF SPILL OR RELEASED VAPORS. CLEAN ALL SPILLS IMMEDIATELY.

Handling

Handling and Storage Precautions:ELIMINATE ALL OPEN FLAMES IN VICINITY OF SPILL OR RELEASED VAPOR.
Other Precautions:KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:USE NIOSH APPROVED VAPOR RESPIRATOR IF SPRAYING OR IF VAPORS EXCEED TLV.
Ventilation:LOCAL EXHAUST: RECOMMENDED. MECHANICAL (GENERAL): RECOMMENDED WHEN SPRAYING.
Protective Gloves:NEOPRENE, RUBBER
Eye Protection:RECOMMENDED
Work Hygienic Practices:USE GOOD HYGIENE. WASH W/SOAP & WATER BEFORE EATING OR SMOKING.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:310-405F
Vapor Pres:2.9
Vapor Density:4.9
Spec Gravity:0.776
Evaporation Rate & Reference:(BU AC = 1): 0.19
Solubility in Water: 0.1%
Appearance and Odor:COLORED TRANSLUCENT LIQUID W/MINERAL SPIRIT ODOR

Stability

Stability Indicator/Materials to Avoid:YES
ACIDS OR BASES, OXIDIZING AGENTS, SELECTED AMINES
Stability Condition to Avoid:OPEN FLAMES OR OTHER IGNITION SOURCES
Hazardous Decomposition Products:CO2 &/OR CO

Disposal

Waste Disposal Methods:PLACE CONTAMINATED MATERIAL IN SEALED CONTAINERS. FOLLOW FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.