

---

## **AS951 BISQ STAIN ANTIQUING SOLVENT**

### **MSDS Number**

BBMDR

### **National Stock Number**

6810-00F002987

### **Product Name**

AS951 BISQ STAIN ANTIQUING SOLVENT

### **Manufacturer**

DUNCAN ENTERPRISES

### **Product Identification**

Product ID:AS951 BISQ STAIN ANTIQUING SOLVENT

MSDS Date:04/01/1991

FSC:6810

NIIN:00F002987

MSDS Number: BBMDR

### **Responsible Party**

DUNCAN ENTERPRISES

5673 E SHIELDS AVE

FRESNO , CA 93727-7819

US

Emergency Phone: 209-445-1222

Info Phone: 209-291-4444

Preparer: CURT SATHRE

Cage: 21546

### **Contractor**

DUNCAN ENTERPRISES

FRESNO, CA 93727

US

209-291-4444

Cage: 21546

### **Ingredients**

AROMATIC PETROLEUM DISTILLATE, HEAVY STRAIGHT RUN NAPHTHA

CAS: 64741-41-9

OSHA PEL500 MG/CUM

ACGIH TLV: 100 MG/CUM

### **Hazards**

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: IRRITATION OF NOSE & THROAT. INGESTION: IRRITATION OF DIGESTIVE TRACT.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHALATION: DROWSINESS, DIZZINESS, FATIGUE, BRAIN & NERVE SYSTEM DAMAGE.

Medical Cond Aggravated by Exposure:SKIN DISORDERS & RESPIRATORY PROBLEMS

### **First Aid**

First Aid:INGESTION: DON'T INDUCE VOMITING. EYES: FLUSH W/WATER FOR AT LEAST 15 MINS. SKIN: WASH W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IN ALL CASES.

## Fire Fighting

Flash Point:104F  
Lower Limits:N/K%  
Upper Limits:0.6-0.7  
Extinguishing Media:DRY CHEMICAL, CO2, OR FOAM  
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS.  
Unusual Fire/Explosion Hazard:THE VAPORS ARE HEAVIER THAN AIR & MAY TRAVEL CONSIDERABLE DISTANCES.

## Accidental Release

Spill Release Procedures:ELIMINATE ALL OPEN FLAMES IN VICINITY OF SPILL OR RELEASED VAPOR. CLEAN ALL SPILLS IMMEDIATELY.

## Handling

Handling and Storage Precautions:KEEP OUT OF REACH OF CHILDREN. ELIMINATE ALL OPEN FLAMES IN VICINITY OF SPILL OR OPEN CONTAINERS.

## Exposure Controls

Respiratory Protection:USE NIOSH APPROVED VAPOR RESPIRATOR IF SPRAYING OR IF VAPORS EXCEED TLV.  
Ventilation:LOCAL EXHAUST: RECOMMENDED. MECHANICAL (GENERAL): RECOMMENDED WHEN SPRAYING.  
Protective Gloves:NEOPRENE/RUBBER  
Eye Protection:REQUIRED  
Work Hygienic Practices:USE GOOD HYGIENE. WASH W/SOAP & WATER BEFORE EATING OR SMOKING.  
Supplemental Safety and Health

## Chemical Properties

Boiling Pt:B.P. Text:310-405F  
Vapor Pres:2.9  
Vapor Density:4.9  
Spec Gravity:0.776  
Evaporation Rate & Reference:(BU AC = 1): 0.19  
Solubility in Water: 0.1%  
Appearance and Odor:COLORED TRANSLUCENT LIQUID W/MINERAL SPIRIT ODOR.

## Stability

Stability Indicator/Materials to Avoid:YES  
ACIDS OR BASES, OXIDIZING AGENTS, SELECTED AMINES  
Stability Condition to Avoid:OPEN FLAMES & OTHER IGNITION SOURCES  
Hazardous Decomposition Products:CO, CO2

## Disposal

Waste Disposal Methods:PLACE CONTAMINATED MATERIAL IN SEALED CONTAINERS. DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.