https://msdsreport.com/msds/BBMDS

•

# AS952 HAND & BRUSH CLEANER

### **MSDS Number**

BBMDS

### **National Stock Number**

6810-00F002988

### **Product Name**

AS952 HAND & BRUSH CLEANER

### Manufacturer

DUNCAN ENTERPRISES

### **Product Identification**

Product ID:AS952 HAND & BRUSH CLEANER MSDS Date:04/01/1991 FSC:6810 NIIN:00F002988 MSDS Number: BBMDS

### **Responsible Party**

DUNCAN ENTERPRISES

5673 E SHIELDS AVE

FRESNO , CA 93727-7819

US

Emergency Phone: 209-445-1222

Info Phone: 209-291-4444

Preparer: CURT SATHRE

Cage: 21546

### Contractor

DUNCAN ENTERPRISES

FRESNO, CA 93727

US

209-291-4444

Cage: 21546

## Ingredients

AROMATIC PETROLEUM DISTILLATE, HEAVY STRAIGHT RUN NAPHTHA

CAS: 64741-41-9

OSHA PEL500 MG/CUM

ACGIH TLV: 100 MG/CUM

### Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION: NOSE/THROAT IRRITATION, DROWSINESS, DIZZINESS & FATIGUE. INGESTION: DIGESTIVE TRACT IRRITATION. Explanation of Carcinogenicity:NONE Effects of Overexposure:INHALATION: BRAIN & NERVE SYSTEM DAMAGE. Medical Cond Aggravated by Exposure:SKIN & RESPIRATORY DISORDERS

# **First Aid**



LEAST 15 MINS. SKIN: WASH W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IN ALL CASES.

•

### **Fire Fighting**

Flash Point:104F Upper Limits:0.6-0.7% Extinguishing Media:DRY CHEMICAL, CO2 OR FOAM Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR & MAY TRAVEL CONSIDERABLE DISTANCES. USE AWAY FROM IGNITION SOURCES.

### **Accidental Release**

Spill Release Procedures: ELIMINATE ALL OPEN FLAMES IN VICINITY OF SPILL OR RELEASED VAPORS. CLEAN ALL SPILLS IMMEDIATELY.

### Handling

Handling and Storage Precautions: ELIMINATE ALL OPEN FLAMES IN VICINITY OF SPILL OR OPEN CONTAINERS. Other Precautions: KEEP OUT OF REACH OF CHILDREN.

### **Exposure Controls**

Respiratory Protection:USE NIOSH APPROVED VAPOR RESPIRATOR IF SPRAYING OR IF VAPORS EXCEED TLV. Ventilation:LOCAL EXHAUST: RECOMMENDED. MECHANICAL (GENERAL): RECOMMENDED WHEN SPRAYING. Protective Gloves:NEOPRENE, RUBBER Eye Protection:RECOMMENDED Work Hygienic Practices:USE GOOD HYGIENE. WASH W/SOAP & WATER BEFORE EATING OR SMOKING. Supplemental Safety and Health

### **Chemical Properties**

Boiling Pt:B.P. Text:310-405F Vapor Pres:2.9 Vapor Density:4.9 Spec Gravity:0.776 Evaporation Rate & Reference:(BU AC = 1): 0.19 Solubility in Water: 0.1% Appearance and Odor:COLORED TRANSLUCENT LIQUID W/MINERAL SPIRIT ODOR

### Stability

Stability Indicator/Materials to Avoid:YES ACIDS OR BASES, OXIDIZING AGENTS, SELECTED AMINES Stability Condition to Avoid:OPEN FLAMES OR OTHER IGNITION SOURCES Hazardous Decomposition Products:CO2 &/OR CO

### Disposal

Waste Disposal Methods:PLACE CONTAMINATED MATERIAL IN SEALED CONTAINERS. FOLLOW FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.