

IFB WET MORTAR

MSDS Number

BBMWK

National Stock Number

5640-00F003393

Product Name

IFB WET MORTAR

Manufacturer

BABCOCK AND WILCOX CO INSULATING PRODS DIV

Product Identification

Product ID:IFB WET MORTAR

MSDS Date:05/01/1987

FSC:5640

NIIN:00F003393

MSDS Number: BBMWK

Responsible Party

BABCOCK & WILCOX CO/INSULATING PRODS DIV

2102 OLD SAVANNAH ROAD

AUGUSTA , GA 30903

US

Emergency Phone: (404) 796-4200

Info Phone: (404) 796-4200

Cage: 19740

Contractor

BABCOCK & WILCOX

AUGUSTA, GA 30903

(404) 796-4200

Cage: 19740

Ingredients

SILICA CRYSTALLINE, SILICA (CRISTOBALITE) (SUSPECTED HUMAN

CAS: 14464-46-1

RTECS: VV7325000

Fraction By Weight: 0-15%

OSHA PELSEE TABLE Z3

ACGIH TLV: 0.05 MG/M3 RDUST9293

SILICA, CRYSTALLINE - FUSED

CAS: 60676-86-0

RTECS: VV7328000

Fraction By Weight: 0-20%

OSHA PELSEE TABLE Z3

ACGIH TLV: 0.1 MG/M3 RDUST;9293

PARTICULATES NOT OTHERWISE REGULATED (NUISANCE DUST)

Fraction By Weight: >80%

OSHA PEL5 MG/CUM

ACGIH TLV: 10 MG/CUM

FIBER SURFACE ORGANIC BINDERS

INORGANIC BINDERS

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO
Health Hazards Acute and Chronic:INHALATION: DUST MAY CAUSE DELAYED LUNG INJURY (SILICOSIS), IRRITATION OR DISCOMFORT OF NOSE/THROAT/LUNGS. SKIN/EYES: IRRITATION.
Explanation of Carcinogenicity:SILICA, CRYSTALLINE IS A SUSPECTED HUMAN CARCINOGEN.
Effects of Overexposure:INHALATION: DUST MAY CAUSE DELAYED LUNG INJURY (SILICOSIS), IRRITATION OR DISCOMFORT OF NOSE/THROAT/LUNGS. SKIN/EYES: IRRITATION.
Medical Cond Aggravated by Exposure:BRONCHIAL DISORDERS

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. INGESTION: DRINK PLENTY OF WATER. SKIN: WASH W/MILD SOAP & WATER. EYES: FLUSH W/PLENTY OF WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Accidental Release

Spill Release Procedures:FOLLOW ROUTINE HOUSEKEEPING PROCEDURES. COLLECT SPILLED MATERIAL PRODUCT IN CLOSED CONTAINER.

Exposure Controls

Respiratory Protection:USE A MSHA/NIOSH APPROVED, AIR PURIFYING, HALF MASK OR FULL FACEPIECE RESPIRATOR W/APPROPRIATE FILTER PAD OR CARTRIDGE.
Ventilation:LOCAL EXHAUST OR MECHANICAL
Protective Gloves:RECOMMENDED
Eye Protection:GOGGLES/SAFETY GLASSES
Supplemental Safety and Health
PRODUCTS ARE ALUMINOSILICATES WHICH MAY TRANSFORM UPON HEATING TO MULLITE & CRISTOBALITE. REMOVAL OF THESE PRODUCTS AFTER SERVICE MAY GENERATE DUST. PRODUCT CONTAINS MINOR AMOUNTS OF ORGANIC AND/INORGANIC BINDERS WHICH BURN OUT DURING FIRST HEAT-UP.

Chemical Properties

Spec Gravity:1.7-2.5
Solubility in Water:INSOLUBLE
Appearance and Odor:COLOR VARIES DEPENDING ON PRODUCT, NO ODOR.

Stability

Stability Indicator/Materials to Avoid:YES

Disposal

Waste Disposal Methods:LANDFILL IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.