

## **1695S ENAMEL PRIMERS, CHROMATE PRIMER VARIPRIME, CORLAR**

### **MSDS Number**

BBNBN

### **National Stock Number**

8010-00F003474

### **Product Name**

1695S ENAMEL PRIMERS, CHROMATE PRIMER VARIPRIME, CORLAR

### **Manufacturer**

E I DUPONT DE NEMOURS AND CO INC

### **Product Identification**

Product ID:1695S ENAMEL PRIMERS, CHROMATE PRIMER VARIPRIME, CORLAR

MSDS Date:01/01/1991

FSC:8010

NIIN:00F003474

MSDS Number: BBNBN

### **Responsible Party**

E I DUPONT DE NEMOURS & CO INC

AUTOMOTIVE PRODUCTS DEPT

WILMINGTON , DE 19898

Emergency Phone: (800) 441-3637

Info Phone: (800) 441-7515

Cage: 0ERJ7

### **Contractor**

E I DUPONT DE NEMOURS & CO, INC.

WILMINGTON, DE 19898

US

800-441-7515

Cage: 0ERJ7

### **Ingredients**

LIGHT ALIPHATIC NAPHTHA, VM & P NAPHTHA \*4/91\*

CAS: 64742-89-8

OSHA PEL300 PPM

ACGIH TLV: 300 PPM

XYLENE, DIMETHYLBENZENE, XYLOL

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 10%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM, SKIN

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ZINC OXIDE

CAS: 1314-13-2

RTECS: ZH4810000

Fraction By Weight: 6%

OSHA PEL15MG/M3 TDUST/5 FUME

ACGIH TLV: 10MG/M3 TDUST; 9293

6.94-13.51

RTECS: 9999999WG

SOYBEAN OIL, POLYMER W/GLYCEROL & PHTHALIC ANHYDRIDE

CAS: 66070-61-9

SOLVENT NAPHTHA, PETROLEUM, LIGHT AROMATIC C8-C10 (AROMATIC

CAS: 64742-95-6

ACGIH TLV: 100 PPM

BARIUM SULFATE, BARYTES

CAS: 7727-43-7

RTECS: CR0600000

Fraction By Weight: 20%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

ISOPARAFFINIC HYDROCARBONS (NAPHTHA PETROLEUM),

CAS: 64742-48-9

TALC (POWDER), (ASBESTOS FREE), TALCUM; HYDROUS MAGNESIUM

CAS: 14807-96-6

RTECS: WW2710000

OSHA PEL20 MPPCF

ACGIH TLV: 2 MG/CUM (RESP DUST)

LEAD NAPHTHENATE

CAS: 61790-14-5

RTECS: QK9150000

Fraction By Weight: 0.11%

OSHA PEL50 MG/CUM

ACGIH TLV: 0.15 MG/CUM INORG PB

MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100), PARAFFIN-NAPTHANES

CAS: 64742-88-7  
OSHA PEL500 PPM  
ACGIH TLV: 100 PPM

TITANIUM DIOXIDE, TITANIUM(IV) OXIDE, TIO2

CAS: 13463-67-7  
RTECS: XR2275000  
OSHA PEL15 MG/M3 TDUST  
ACGIH TLV: 10 MG/M3 TDUST; 9293

## Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INGESTION: GASTROINTESTINAL DISTRESS.  
INHALATION: NOSE & THROAT IRRITATION, PERMANENT BRAIN & NERVOUS  
SYSTEM DAMAGE, EYE WATERING, HEADACHE, NAUSEA, DIZZINESS, & LOSS OF  
COORDINATION. EYES: IRRITATION , & BURNING. SKIN: IRRITATION,  
DISCOMFORT, & DERMATITIS.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:INGESTION: GASTROINTESTINAL DISTRESS.  
INHALATION: NOSE & THROAT IRRITATION, PERMANENT BRAIN & NERVOUS  
SYSTEM DAMAGE, EYE WATERING, HEADACHE, NAUSEA, DIZZINESS & LOSS OF  
COORDINATION. EYES: IRRITATION, & BURNING. SKIN: IRRITATION,  
DISCOMFORT, & DERMATITIS.

## First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH W/WATER. SKIN:  
WASH W/SOAP & WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

## Fire Fighting

Flash Point Method:CC  
Flash Point:73F  
Lower Limits:0.2%  
Upper Limits:13.1%  
Extinguishing Media:WATER SPRAY, FOAM, CO2, OR DRY CHEMICAL  
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS & FULL  
PROTECTIVE EQUIPMENT. WATER FROM FOG NOZZLES MAY BE USED TO COOL  
CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP.  
Unusual Fire/Explosion Hazard:WHEN HEATED >73F, EMITS FLAMMABLE VAPORS  
WHICH, WHEN MIXED W/AIR, CAN BURN OR BE EXPLOSIVE. FINE MISTS/SPRAY  
MISTS MAY BE FLAMMABLE AT TEMPERATURES

## Accidental Release

Spill Release Procedures:VENTILATE AREA. REMOVE SOURCES OF IGNITION.  
WEAR PROPERLY FITTED VAPOR/PARTICULATE RESPIRATOR (NIOSH/MSHA  
TC-23C). CONFINE & REMOVE W/INERT ABSORBENT.

## Handling

Handling and Storage Precautions:DON'T STORE >120F. CLOSE CONTAINER  
AFTER EACH USE. GROUND CONTAINERS WHEN POURING.  
Other Precautions:PREVENT SKIN & EYE CONTACT. DON'T BREATHE VAPORS OR  
MISTS. OBSERVE LABEL PRECAUTIONS.

## Exposure Controls

Respiratory Protection:USE PROPERLY FITTED VAPOR/PARTICULATE RESPIRATOR  
APPROVED BY NIOSH/MSHA (TC-23C) DURING APPLICATION. IN CONFINED  
SPACES, USE POSITIVE-PRESSURE, SUPPLIED-AIR RESPIRATOR (TC-19C).  
Ventilation:SUFFICIENT IN VOLUME & PATTERN TO KEEP Protective Gloves:NEOPRENE  
Eye Protection:SPLASH GUARDS OR SIDE SHIELDS  
Other Protective Equipment:COVERALLS  
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING & BEFORE EATING  
OR SMOKING.

Supplemental Safety and Health  
BOILING RANGE: 129F-711F.

## Chemical Properties

Boiling Pt:B.P. Text:SEE SUPP.  
Vapor Density:>AIR  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Solubility in Water:MISCIBLE  
Percent Volatiles by Volume:40-99%

## Stability

Stability Indicator/Materials to Avoid:YES  
Hazardous Decomposition Products:CO, CO2, & SMOKE

## Disposal

Waste Disposal Methods:DON'T ALLOW MATERIAL TO CONTAMINATE GROUND WATER SYSTEMS. INCINERATE ABSORBED MATERIAL IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS. DON'T INCINERATE IN CLOSED CONTAINERS.  
FLAMMABLE LIQUID. UN1 263.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.