

## **TRACTOR & IMPLEMENT ENAMEL 389S**

### **MSDS Number**

BBNFL

### **National Stock Number**

8010-00F003527

### **Product Name**

TRACTOR & IMPLEMENT ENAMEL 389S

### **Manufacturer**

E I DUPONT DE NEMOURS

### **Product Identification**

Product ID:TRACTOR & IMPLEMENT ENAMEL 389S

MSDS Date:01/01/1987

FSC:8010

NIIN:00F003527

MSDS Number: BBNFL

### **Responsible Party**

E.I. DUPONT DE NEMOURS/WILMINGTON, DE 19898

Emergency Phone: (800) 441-3637

Cage: 19898

### **Contractor**

E.I. DUPONT DE NEMOURS & CO., INC.

1635

WILMINGTON, DE 19898

US

800-441-3637

Cage: 19898

### **Ingredients**

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

OSHA PEL100 PPM

ACRYLIC RESIN

### **Hazards**

Effects of Overexposure:NOSE/THROAT IRRITATION. HEADACHE, DIZZINESS, NAUSEA, STAGGERING GAIT, CONFUSION, UNCONSCIOUSNESS

### **First Aid**

First Aid:IN CASE OF EYE CONTACT, IMMEDIATELY FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINUTES; CALL A PHYSICIAN. IN CASE OF SKIN CONTACT WASH W/SOAP & WATER. IF IRRITATION OCCURS, CONTACT A PHYSICIAN. IF AFFECT ED BY INHALATION OF VAPOR, REMOVE TO FRESH AIR

### **Fire Fighting**

Flash Point:20-73F (CC)

Lower Limits:1.1%

Upper Limits:14%

Extinguishing Media:FOAM, CO2, DRY CHEMICAL  
Fire Fighting Procedures:WEAR SCBA. WATER COOL CONTAINERS/PREVENT  
PRESSURE BUILD UP  
Unusual Fire/Explosion Hazard:FINE MISTS OR SPRAYS MAY BE FLAMMABLE AT  
TEMPERATURES BELOW THE FLASH POINT.

## Accidental Release

Spill Release Procedures:VENTILATE AREA. REMOVE SOURCES OF IGNITION.  
PREVENT SKIN CONTACT AND BREATHING OF VAR. CONFINE AND REMOVE WITH  
INERT ABSORBANT.

## Handling

Handling and Storage Precautions:OBSERVE LABEL PRECAUTIONS. KEEP AWAY  
FROM HEAT, SPARKS & FLAME. CLOSE CONTAINER AFTER EACH USEGROUND  
CONTAINERS WHEN POURING.  
Other Precautions:WASH THOROUGHLY AFTER HANDLING & BEFORE EATING OR  
SMOKING. DON'T STORE ABOVE 120F. DON'T SAND/FLAME CUT/BRAZE OR WELD  
DRY COING W/OUT A NIOSH/MSHA APPROVED RESP/APPROPRIATE VENTILATION.

## Exposure Controls

Respiratory Protection:WEAR A PROPERLY FITTED NIOSH/MSHA APPROVED PAINT  
SPRAY RESPIRATOR  
Ventilation:PROVIDE VENTILATION TO KEEP BELOW TLV  
Protective Gloves:NEOPRENE  
Eye Protection:SPLASH GUARDS/SIDE SHIELD  
Supplemental Safety and Health

## Chemical Properties

Boiling Pt:B.P. Text:212-401F  
Vapor Density:>AIR  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Solubility in Water:SLIGHT  
Percent Volatiles by Volume:68.7

## Stability

Stability Indicator/Materials to Avoid:YES  
NONE REASONABLY FORESEEABLE  
Hazardous Decomposition Products:CO, CO2, SMOKE

## Disposal

Waste Disposal Methods:DON'T ALLOW MATERIAL TO CONTAMINATE GROUND WATER  
SYSTEMS. INCINERATE ABSORBED MATERIAL IN ACCORDANCE WITH FEDERAL,  
STATE AND LOCAL REQUIREMENTS. DON'T INCINERATE IN CLOSED  
CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.